

Republic of the Philippines **QUEZON CITY GOVERNMENT** BIDS AND AWARDS COMMITTEE



2nd Floor, Procurement Department, Finance Building, Quezon City Hall Compound

REQUEST FOR QUOTATION

Shopping 52.1b

Date:

OCTOBER 26, 2021

PR No:

GF-21-10-00414

			VI TO VVIII
Name of Company	1		
Address	1		
Contact No.	:		
Project Title	PROCUREMENT OF USB/FLASH DRIVE AND OTHERS	5	
Approved Budget for the Contract	Php 448,251.50		
the Contract			
End-User /	DEPARTMENT OF ENGINEERING		

Implementing Office:

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than OCTOBER 29, 2021, 10:00 A.M. Philippine Standard Time, together with the following documents of your company:

- PhilGEPS certificate (not expired on the time of opening of quotations);
- Business Registration (DTI / SEC); 2
- 3 Mayor's/Business Permit (2021);
- 4 Tax Clearance;
- Income/Business Tax Return (for FY 2020) (For ABCs above P500,000.00); 5
- 6 Omnibus Sworn Statement prescribed by the Government Procurement Policy Board (GPPB).
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized 7 statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** shall:

- Contain the Project Name and PR Number of the contract to be bid in capital letters:
- Bear the name and address of the Bidder in capital letters; 2

Be addressed to the Procuring Entity's BAC.

Project Title: PROCUREMENT OF USB/FLASH DRIVE AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE 2/F Procurement Department, Finance Building

Quezon City Hall Compound

For any clarification you may contact us at 89884242 loc. 8505/8709.

ATTY. DOMINIC B. GARCIA Officer-In-Charge Head, BAC Secretariat

TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	ITEM & DESCRIPTION	UNIT OF ISSUE	QTY.	UNIT PRICE	ITEM TOTAL
1	USB/Flash Drive - 32GB, Dimension: 2.25 inches x 0.68 inches x 0.39 inches (57.18mm x 17.28mm x 10.00mm), Operating Temperatures: 32°F to 140°F (0°C to 60°C), Storage Temperatures: -4°F to 185°F (-20°C to 85°C), Convenient: pocket-sized for easy transportability, Simple: just plug into a USB port, Handy: capless design; no cap to lose, Guaranteed: free technical support, Color: Purple, Compatible with: Windows 8, Windows 7, Windows Vista, Windows XP, MAC OS X v.10.6.x+, Linux v.2.6.x+	pieces	125		
2	Mouse - Optical USB Mouse, comfortable, ambidextrous design, 800 DPI Optical Precision, 3 buttons optical tracking, for left or right handed, USB connectivity cable: approximately 5 feet 9 inches or 180 cm, works with Windows XP, Windows Vista and Windows 7, System requirements: Windows-based PC: Windows XP, Windows Vista or Windows 7; USB Port Linux-based PC: Linux kernel 24+; USB port MAC Computer: MAC OS x 1039 or later; USB port	pieces	100		

3	Keyboard Computer - Color: Black, Rugged good looks, comfortable, quiet typing, spill resistant design, durable keys, thin profile, sturdy, adjustable tilt legs, plug-and-play USB connection, easy to read keys, curved space bar, Windows-based computer: Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10, USB Bort	pieces	130	
	Windows 8, Windows 10, USB Port			
4	Battery Rechargeable AA, 2 pcs, 1.2 V, work in all NiMH battery chargers, great for remotes, label makers, PC mice, clocks, calculators and motor driven toys, NiMH batteries with a capacity of 1,300 mAh and no memory effect.	set	25	
5	Battery Rechargeable AAA, 2 pcs, Rechargeable Universal 2S, Weight: 0.045kg, Length: 9.4cm, Width 0.5 cm, Height 11.5 cm, NiMH batteries, 700 mAh	set	25	
6	UTP Cable CAT6-305m, 1,000 feet, Ethernet Cable Cat6, Gauge Size: 24AWG, Category: 6 Cat6, Color: Blue, Solid Pure Copper, 4pairs, 100% Brand New, 100% High Quality	units	3	
7	Ethernet hub - Gigabit switch hub, 24 ports, branded, Port Standards & Functions: IEEE 802.3, 802.3u, 802.3ab compliant, IEEE 802.3az EEE compliant, IEEE 802.3af/at compliant, Half/Full-duplex operation at 10/100Mbps, Full-duplex operation at 1000Mbps, Auto-Negotiation for each port, Auto MDI/MDIX, Switching Capacity: 48 Gbps, Max. Forwarding Rate: 35.71 Mpps, Addr. Table Size: 8K Entries, Packet Buffer: 512KBytes, Flash Memory: 8 MBytes, PoE Standards: 802.3af/at, PoE Capable Ports: Ports 1-12, PoE Power Budget: 100 W, Power Input: 100 to 240 VAC, 50 to 60 Hz Internal Universal Power Supply, Max. Power Consumption: 128.3 W (PoE on) 21.2 W (PoE off), Standby Power Consumption: 13.0 W, Ventilation: One Fan, Acoustics: 41.9 dB(A) rev B1 27.6 dB(A) rev B2, Heat Dissipation: 437.9 BTU/hr, Operating Temp.: 23°F to 122°F (-5°C to 50°C), Storage Temp.: -40°F to 158°F (-40°C to 70°C), Operating Humidity: 0% to 95% non-condensing, Storage Humidity: 0% to 95% non-condensing,	pcs	2	

8	Ethernet hub - Gigabit switch hub, 8	nce	3		
	G	pcs	3		
	ports, branded, Port Standards &				
	Functions: IEEE 802.3, 802.3u, 802.3ab				
	compliant, IEEE 802.3x Flow Control,				
	IEEE 802.3az EEE compliant, IEEE				
	802.3af compliant, IEEE 802.3af/at			67	
	compliant, Half/Full-duplex operation				
	at 10/100, Full-duplex operation at				
	1000Mbps, Auto-Negotiation for each				
	port, Auto MDI/MDIX, Switching				
	Capacity: 16 Gbps, Max. Forwarding				
	Rate: 11.9 Mpps, Address Table Size: 4K				
	Entries, Packet Buffer: 1.5 Mbits, Flash	•			
	Memory: 2 Mbytes, PoE Standard:				
	802.3af/at, PoE Capable Ports: Ports 1-8,				
	The state of the s				
	PoE Power Budget: 64W, Power Input:				
	100 to 240 VAC; 50 to 60 Hz External				
	Universal Power Supply, Max. Power				-
	Consumption: 77.9 W (PoE on) 4.6 W				
	(PoE off), Standby Power Consumption:				
	2.0 W, Ventilation: Fanless, Acoustics: 0				
	dB(A), Heat Dissipation: 265.85 BTU/hr,				
	Operating Temperature: 32°F to 104°F				
	(0°C to 40°C), Storage Temperature: -				
	40°F to 158°F (-40°C to 70°C), Operating				
	Humidity: 0% to 90% non-condensing,	2			
	Storage Humidity: 0% to 95% non-				
	condensing, Dimensions (W x D x H):				
	6.73 x 3.85 x 1.13 (171 x 97.8 x 28.6				25
	mm), Weight: 0.95 lbs (0.43 kg), EMI				
	Certifications: FCC Class B, CE Class B,				
	VCCI Class B, BSMI, CCC, Safety: cUL,				
		27			
	CE LVD, CB, BSMI, CCC, MTBF: 786,841				
	hours				
9	Cable Ties - 250 pcs per pack, Size: 4 mm	pack	5		
	x 250 mm, zip ties, white, Material:				
	nylon, yield stress: 60MPa, Elongation at				
	Break: 18%, Tensile Modulus: 1500MPa,				ėl.
	Flammability: V2 0.8mm, Resistance to				
	UV, Oil and Greases, Petrol - Very				
	Good, Resistance to Solvents - Good,				
	Heat Deflection Temperature 1.8MPa: 70				
10	Degrees Celsius, Density: 1.14	7	F0		
10	RJ 45 Connector - 12 pcs per pack, for	pack	50		
	CAT 5, CAT 5e and CAT 6, high-quality				
	gold plated				
11	RJ45 Crimping Tool Kit - Inclusions: 1	set	6		
	pc. RJ45 Crimp Tool Pass Through Cat5				
	Cat5e Cat6; 1 pc 6 in 1 Multipurpose				
	mini screw driver; 1 pc Network Cable				
	Tester (Main Tester and Remote Tester,				
	9V Battery not included); 1 pc Mini	*			
	Wire Stripper; 20pcs. RJ45 Cat6 Pass				
	Through Connectors and Covers		040000		
12	Battery AA - 2pcs per pack, Alkaline	set	60		
	Battery, Nominal Voltage: 1.5 volts,				
	Typical Weight: 23.0 grams (0.8 oz.),				
	Typical Volume: 8.1 cubic centimeters				-
	(0.5 cubic inch.), Shelf Life: 10 years at			e	
	21°C, Terminal: Flat Contact				
					l.

13	Battery AAA - 4 pcs per pack, Alkaline	set	40		
	Battery, Nominal Voltage: 1.5 volts,			9	
	Typical Weight: 11.5 grams (0.4 oz.),				
	Typical Volume: 3.8 cubic centimeters				
	(0.2 cubic inch.), Chemical System: Zinc-				
	Manganese Dioxide, No added mercury				
	or cadmium, Shelf Life: 10 years at 21°C,				
	Terminal: Flat Contact				
14	Spray Paint - 400ml, red, premium	pcs	109		
	quality, 100 pure acrylic, highly durable,				
	fast drying				

		Т	otal Quot	ed Amount	

ER INSTRUCTIONS/SP			
Statement of Warrar	ty: Minimum of One (1) Year.		
	Delivery Period	:	Thirty (30) Calendar Days
	Warranty	:	
			Signature over printed name
			Office Telephone No./Fax/Mobile No.
			Date