

Republic of the Philippines QUEZON CITY GOVERNMENT

BAC – Goods and Services ^{2nd} floor, Procurement Department, Finance Building, Quezon City Hall Compound



REQUEST FOR QUOTATION SHOPPING 52.1(b)

Name of Company
Address
Contact No.

Project Title
Approved Budget of the Contract
Approved Budget of the Contract
End-User / Implementing Office

PASS INDICATE No.

PARMBGH-21-CMS-662B

RMBGH-21-CMS-662B

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **November 19, 2021 10:00 a.m.** Philippine Standard Time, together with the following documents of your company:

- PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2021);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2020) (For ABC P500,000.00 above)
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** shall:

- 1. Contain the Project Name and PR Number of the contract to be bid in capital letters;
- 2. Bear the name and address of the Bidder in capital letters;
- 3. Be addressed to the Procuring Entity's BAC.

PROJECT TITLE: PROCUREMENT OF ANGLE GRINDER AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE

2/F Procurement Department, Finance Building

Quezon City Hall Compound

For any clarification you may contact us at 89884242 loc. 8506/8709.

ATTY. DOMINIC B. GARCIA
Head, BAC-Secretariat

5

TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows: ITEM **UNIT OF** ITEM & DESCRIPTION QTY. ITEM TOTAL UNIT PRICE NO. ISSUE 1 ANGLE GRINDER Unit 2 Angle Grinder Corded GWS 900-100 S Professional 900 W built for tough jobs! FEATURES: 1 Superior grinding/cutting performance due to high power and torque at 900 W 23.+ 3 Long lifetime under tough working conditions and heavy working load due to robust design and components SPECIFICATIONS: - Rated input power: 900 W - No-load speed: 2.800 - 11.000 rpm - Power output: 450 W - Grinding spindle thread: M 10 - Disc diameter: 100 mm - Tool dimensions (width); 73 mm - Tool dimensions (length): 280 mm - Tool dimensions (height): 100 mm - Weight: 1.9 kg Switch: 2 way Quality 1. Heavy Duty - Power, Performance and Robustness redefined! 2. Variable Speed: Easy and precise control of the RPM thanks to variable speed 2 **ELECTRIC DRILL** Unit 2 Power Consumption 550 W No Load Speed 2800 RPM Warranty 1 YEAR Class of Tool ELECTRICIAN KIT Voltage 220V is It Variable Speed NON VARIABLE SPEED Reverse Rotation YES CORDED Suitable for professionals, technicians and DIY enthusiasts. The multifunction drilling machine can be used to make holes on walls, concrete, metal, wood and plastic. Fix your picture frames, paintings, hangers, lightings. Contains:

5 Masonry Drill Bits: 3, 4, 5, 6, 8 mm

	E Wood Drill Bitu 2 4 5 4 6		1	
	5 Wood Drill Bits: 3, 4, 5, 6, 8 mm			
	8 Allen Keys: #1.5, #2, #2.5, #3, #4, #5, #5.5, #6			
	10 CRV Bits: 50 mm			
	18 Sockets: #1/4, #5/16, #11/32, #3/8, #7/16,			
	#1/2, #9/16, #5/8, #3/4, #7, #8, #9, #10, #12,			
	#13, #14, #15, #17			
	30 Screws: 10 x 3/30, 10 x 4/40, 10 x 5/50 mm			
	30 Wall Plugs: 10 x 5/25, 10 x 6/30, 10 x 8/35 mm			
	7 Wrenches: #8, #10, #12, #13, #14, #15, #17			
	Magnetic Bit Holder			
	Plier			
	1/4 Inch Adapter			
	Cutter			
	Long Nose Pliers			
	Socket Wrench			
	Hammer			
	Wire Cutter			
	Case			
	Cross screwdriver			
	Flat screwdriver			
	Pliers			
	N production in			
	Long nose pliers			
	Adapter			
	Socket			
	Wrench			
	Screw set			
	Wall plug set			
3	GRINDER PORTABLE	Unit	2	
	Cordless - Angle			
	Powered by 48V Lithium Ion Battery 2 Batteries			
	included with Charger			
	Comes with Professional Hard Carrying Case 48V			
	Capacity 100mm			
	Wheel Diameter No-Load Speed: 8,500 r/min			
	Comes with PROFESSIONAL			
à.	HARD CASE for easy Transporting, Automatic			
	speed change technology			
	adjusts speed and torque during operation for			
	optimum performance.			
	Active feedback-sensing technology (aft) turns			
	the motor off if rotation			
	of the wheel is suddenly forced to stop. Electric			
	brake stops the grinding			
	or cut-off wheel in 2 seconds or less for maximum			
	productivity.			
4	HAMMER DRILL	Unit	2	
200 • 0	Extended life brushes are longer for more work	OHIII		
	between service intervals and less downtime.			
	Rotation reversing system using brush holder unit			
	features: No load speed reduction of motor			
	even in reverse -Longer life of carbon brushes.			
	Keyed chuck. Depth gauge for increased drilling			
	consistency. Powerful 680 W motor with 0-2,800			
	RPM & 0-44,800 IPM for the most demanding			
	applications. Soft grip handle provides increased			
	comfort on the job. In-line positive grip design			
	maximizes power thrust. Lightweight with large			
	drilling capacity up to 16 mm in concrete. Large			
	2-finger trigger for added convenience.			
	Recessed lock-on button for continuous use.			22
	Reversing switch is conveniently located. 360°			
	Swivel side handle. Variable speed control dial			
	enables user to match the			

	Email Address							
				Da	ite			
	Office Telephone No./Fax/Mobile No.							
	Signature over printed name							
	atement of Warranty (Parts And Services) – minimum of O	ne (1) Yea	r					
Other	Requirements:							
Delivery : <u>Thirty (30) Calendar Days</u> Warranty :								
Amount in Words:								
				TOTAL				
	platform for convenient cylinder access. Rolls smoothly with 2 swivel, 2 rigid rubber casters; foot operated floor lock helps keep the unit in a fixed position. Durable orange powder coat finish.			The state of the s				
5	LIFTER HYDRAULIC Portable Scissor Lift is ideal for transporting loads to and from work cells, where it can then be used as a work platform or raised and lowered to facilitate load transfer to tables or benches. Scissor Lift features ½ inch steel plate scissor legs, lifetime lubricated bearings and a hinged	Unit	3					
	With 74 Pcs Accessories Specifications: Continuous rating input: 680W Capacity: Concrete: 16mm (5/8 inch) / Steel: 13 mm (1/2 inch) / Wood: 30 mm (1-3/16 inches) Chuck Capacity: 1.5 - 13 mm (1/16 inches - 1 ½ inches) Blows Per Minute (BPM) 0 - 44,800 No Load Speed (RPM): 0 - 2,800 Vibration Level Hammer Drilling into Concrete: 19m/s2 Vibration K Factor Hammer Drilling into Concrete: 2.0 m/s2 Vibration Level Drilling into Metal: 2.5 m/s2 Vibration K Factor Drilling into Metal: 1.5 m/s2 Sound Pressure Level92 dB(A) Sound Power Level 103 dB(A) Noise K Factor 3 dB(A) Dimensions (L x W x H) 303x72x222 mm (11 - 7/8 inches x 2-1 3/16 inches x 8-3/4 inches) Net weight 2 kg (4.4 lbs.) Power supply cord 2.0 m (6.6ft).							
	speed to the application .2-Mode operation for "Rotation Only" or "Hammering with Rotation" for multiple applications. Ideal for small selfanchoring concrete screws. Double insulated.							