

## Republic of the Philippines QUEZON CITY GOVERNMENT BIDS AND AWARDS COMMITTEE



2nd Floor, Procurement Department, Finance Building, Quezon City Hall Compound

## REQUEST FOR QUOTATION SMALL VALUE PROCUREMENT (SECTION 53.9)

Date:

MARCH 29, 2022

PR No:

ENGINEERING-22-

ITPAP-403

Name of Company	:	
Address	:	
Contact No.	:	
Project Title	: .	PROCUREMENT OF ETHERNET HUB AND OTHERS
Approved Budget for the Contract		Php 257,078.00
End-User / Implementing Office	:	DEPARTMENT OF ENGINEERING

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than

APRIL 01, 2022; 10:00 A.M. Philippine Standard Time, together with the following documents of your company:

- 1 PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI / SEC);
- 3 Mayor's/Business Permit (2022);
- 4 Tax Clearance;
- Income/Business Tax Return (for FY 2020) (For ABCs above P500,000.00);
- Omnibus Sworn Statement prescribed by the Government Procurement Policy Board (GPPB).
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

## in a **SEALED LONG BROWN ENVELOPE** shall:

- Contain the Project Name and PR Number of the contract to be bid in capital letters;
- Bear the name and address of the Bidder in capital letters;

3 Be addressed to the Procuring Entity's BAC.

Project Title: PROCUREMENT OF ETHERNET HUB AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE 2/F Procurement Department, Finance Building Quezon City Hall Compound

For any clarification you may contact us at 89884242 loc. 8505/8709.

ATTY. DOMINIC B. GARCIA
Officer-In-Charge/Head, BAC Secretariat

V

## TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	ITEM & DESCRIPTION	UNIT OF ISSUE	QTY.	UNIT PRICE	ITEM TOTAL
1	Battery AA - 2pcs per pack, Alkaline Battery, Nominal Voltage: 1.5 volts, Typical Weight: 23.0 grams (0.8 oz.), Typical Volume: 8.1 cubic centimeters (0.5 cubic inch.), Shelf Life: 10 years at 21°C, Terminal: Flat Contact	packs ,	30 -	-	
2	Battery AAA - 4 pcs per pack, Alkaline Battery, Nominal Voltage: 1.5 volts, Typical Weight: 11.5 grams (0.4 oz.), Typical Volume: 3.8 cubic centimeters (0.2 cubic inch.), Chemical System: Zinc-Manganese Dioxide, No added mercury or cadmium, Shelf Life: 10 years at 21°C, Terminal: Flat Contact	packs <sub>/</sub>	30 (	8	
3	Cable Ties - 250 pcs per pack, Size: 4 mm x 250 mm, zip ties, white, Material: nylon, yield stress: 60MPa, Elongation at Break: 18%, Tensile Modulus: 1500MPa, Flammability: V2 0.8mm, Resistance to UV, Oil and Greases, Petrol - Very Good, Resistance to Solvents - Good, Heat Deflection Temperature 1.8MPa: 70 Degrees Celsius, Density: 1.14	packs	2		
4	Ethernet hub - Gigabit switch hub, 24 ports, branded, Port Standards & Functions: IEEE 802.3, 802.3u, 802.3ab compliant, IEEE 802.3x Flow Control, IEEE 802.3az EEE compliant, IEEE 802.3af/at compliant, Half/Full-duplex operation at 10/100Mbps, Full-duplex operation at 1000Mbps, Full-duplex operation at 1000Mbps, Auto-Negotiation for each port, Auto MDI/MDIX, Switching Capacity: 48 Gbps, Max. Forwarding Rate: 35.71 Mpps, Addr. Table Size: 8K Entries, Packet Buffer: 512KBytes, Flash Memory: 8 MBytes, PoE Standards: 802.3af/at, PoE Capable Ports: Ports 1-12, PoE Power Budget: 100 W, Power Input: 100 to 240 VAC, 50 to 60 Hz Internal Universal Power Supply, Max. Power Consumption: 128.3 W (PoE on) 21.2 W (PoE off), Standby Power Consumption: 13.0 W, Ventilation: One Fan, Acoustics: 41.9 dB(A) rev B1 27.6 dB(A) rev B2, Heat Dissipation: 437.9 BTU/hr, Operating Temp.: 23°F to 122°F (-5°C to 50°C), Storage Temp.: -40°F to 158°F (-40°C to 70°C), Operating Humidity: 0% to 95% non-	pcs	2		

	condensing, Storage Humidity: 0% to 95% non-						
5	Ethernet hub - Gigabit switch hub, 8 ports,	ncc	3 .				
3	branded, Port Standards & Functions: IEEE 802.3,	pcs	3 1		e4		
	802.3u, 802.3ab compliant, IEEE 802.3x Flow				19		
	Control, IEEE 802.3az EEE compliant, IEEE				1		
	802.3af compliant, IEEE 802.3af/at compliant,				1		
				81			
	Half/Full-duplex operation at 10/100, Full-						
	duplex operation at 1000Mbps, Auto-						
	Negotiation for each port, Auto MDI/MDIX,						
	Switching Capacity: 16 Gbps, Max. Forwarding						
	Rate: 11.9 Mpps, Address Table Size: 4K Entries,						
	Packet Buffer: 1.5 Mbits, Flash Memory: 2						
	Mbytes, PoE Standard: 802.3af/at, PoE Capable						
	Ports: Ports 1-8, PoE Power Budget: 64W, Power						
	Input: 100 to 240 VAC; 50 to 60 Hz External						
	Universal Power Supply, Max. Power						
	Consumption: 77.9 W (PoE on) 4.6 W (PoE off),						
	Standby Power Consumption: 2.0 W, Ventilation:				2		
	Fanless, Acoustics: 0 dB(A), Heat Dissipation:						
	265.85 BTU/hr, Operating Temperature: 32°F to						
	104°F (0°C to 40°C), Storage Temperature: -40°F to						
	158°F (-40°C to 70°C), Operating Humidity: 0% to						
	90% non-condensing, Storage Humidity: 0% to						
	95% non-condensing, Dimensions (W $\times$ D $\times$ H):						
	6.73 x 3.85 x 1.13 (171 x 97.8 x 28.6 mm),						
	Weight: 0.95 lbs (0.43 kg), EMI Certifications: FCC						
	Class B, CE Class B, VCCI Class B, BSMI, CCC,	E					
	Safety: cUL, CE LVD, CB, BSMI, CCC, MTBF:						
	786,841 hours	<u></u>					
6	RJ 45 Connector - 12 pcs per pack, for CAT 5,	packs 🔻	10				
	CAT 5e and CAT 6, high-quality gold plated			-			
7	USB/Flash Drive - 32GB, Dimension: 2.25 inches	pieces	100				
	x 0.68 inches x 0.39 inches (57.18mm x 17.28mm x						
	10.00mm), Operating Temperatures: 32°F to 140°F						
	(0°C to 60°C), Storage Temperatures: -4°F to						
	185°F (-20°C to 85°C), Convenient: pocket-sized						
	for easy transportability, Simple: just plug into a						
	USB port, Handy: capless design; no cap to lose,						
	Guaranteed: free technical support, Color: Purple,						
	Compatible with: Windows 8, Windows 7,						
	Windows Vista, Windows XP, MAC OS X						
8	v.10.6.x+, Linux v.2.6.x+	*****	2.				
0	UTP Cable CAT6-305m/roll - 1,000 feet, Ethernet	units '	31				
	Cable Cat6, Gauge Size: 24AWG, Category: 6						
	Cat6, Color: Blue, Solid Pure Copper, 4pairs,						
9	100% Brand New, 100% High Quality		100				
9	Spray Paint - 400ml, red, all-purpose quick dry, high gloss acrylic	cans 🖟	100 '				
10			20				
10	Tape Measure - Length: 5meters (16ft.)/16inches;	pcs	30 .				
	blade width: 19mm; corrosion resistant long life						
	nylon coated blade; Bi-material case for improved						
	grip; belt clip; positive blade lock for accurate measurements, branded						
11	Tape Measure - Length: 8meters/ 26 inches;	nce	20				
11	metric & imperial scales; class 2 blade, bi-material	pcs ,	20				
	case; 25mm steel; corrosion resistant; positive						
	blade lock; 3-rivet true-zero end hook, branded						
	***						
		_					
		1	otal Quo	ted Amount			
Am	ount in Words:						
7 1111		Source House St.					
Delivery Period : Thirty (30) calendar days							
	Warrar	nty					
		70.					
			36 ag				
				Signature	over printed name		
			9 <u>8</u>				
				Office Telepho	ne No./Fax/Mobile No.		
					Date		

Email Address