

Republic of the Philippines QUEZON CITY GOVERNMENT

BAC – Goods and Services 2nd floor, Procurement Department, Finance Building, Quezon City Hall Compound



REQUEST FOR QUOTATION SMALL VALUE PROCUREMENT (SECTION 53.9)

DATE

MAY 24 2022

ENGINEERING-22-

PROJECT NO.

VPA-745

Name of Company	:	
Address	:	
Contact No.	:	
Project Title	:	PROCUREMENT OF PNEUMATIC GREASE GUN AND OTHERS
Approved Budget of the Contract	:	Php 641,738.00
End-User / Implementing Office		DEPARTMENT OF ENGINEERING

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than

MAY 27, 2022; 10:00 A.M. Philippine Standard Time, together with the following documents of your company:

- PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2022);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2021) (For ABCs above P500,000.00)
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** shall:

- Contain the Project Name and PR Number of the contract to be bid in capital letters;
- 2. Bear the name and address of the Bidder in capital letters;
- 3. Be addressed to the Procuring Entity's BAC.

PROJECT TITLE: PROCUREMENT OF PNEUMATIC GREASE GUN AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE

2/F Procurement Department, Finance Building

Quezon City Hall Compound

For any clarification you may contact us at 8-988-4242 loc. 8506/8709.

ATTY. DOMINIC B. GARCIA
Officer-in-Charge / Head, BAC-Secretariat

TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	ITEM & DESCRIPTION	UNIT OF ISSUE	QTY.	UNIT PRICE	ITEM TOTAL
1	Pneumatic Grease Gun - One-hand pistol grip; Load with 14 oz. cartridges or bulk-fill; 9 inches flexible grease hose and 6 inches extension included; 6,000 psi	Set *	1 .		
2	Waste Oil Drainer Tank - Heat treated and tempered steel for durability; Oil discharge: Pneumatic; Container capacity: 60L; Maximum height: 155 cm; Net weight: 18.8 kg.	Set	2 *		
3	Pneumatic Oil Pump and Oil Extractor - Capacity: 8 Liters; Product Material: Plastic; PSI: 40-170; BAR: 2.8-12; kg/cm2: 2.8-12	Set	1 .		
4	Car/Truck Diagnostic Scanner With Adaptor - Tablet PC: more powerful HW configuration with quadcore processor, more RAM, better quality and bigger screen 10.1" and powerful battery; Optimized software - optimized to big screen, more easy to use and for understand, new interface, more functions; Live data graphs quantity in the same time - up to 15 on the screen; Diagnostic trouble code searching and translating in the Internet directly from diagnostic menu; More capacity of integrated memory; Similar in comparing of top level equipment Euro Pad II by several parameters, but	set	1		

	without possibility to add external				
	modules and same other parameters; The				
	operating system: Android 4.2 and above				
	with updates; Processor: quad-core 1.2				
	GHz / 1.3 GHz processor ; Battery:				
	6600mAh / 6340mAh rechargeable				
	polymer lithium battery; Standby time:				
	more than 100 hours; Time of active				
	work in the diagnosis - approximately 6				
	- 8 hours.; Memory expansion card:				
	support Micro SD (TF) card up to 32 Gb				
	(included in the set); Built-in memory				
	capacity: 8 GB / 16GB; RAM: 1 GB;				
	Graphic card: 16 Core GPU HD; LCD				
	display: 10.1 inches, HD, with wide				
	viewing angle ; LCD resolution: 1280 X				
	800 ; Touch screen: capacitive touch				
	screen (10 points); Cameras: 3.2 mega				
	pixels rear and 0.3 mega pixels front / 5				
	mega pixels rear and 2 mega pixels front				
	; Wireless connections: Wi-Fi				
	(802.11a/b/g/h), Bluetooth; Operating				
	temperature: -10°C to 55°C (14°F to				
	131°F); Storage temperature: -20°C to				
	70°C (-4°F to 158°F); Operating voltage:				
	9 ~ 15V; Average operating current:				
	35mA; In the standby mode: 25mA;				
	Working temperature: from -20°C up to				
	55°C; Storage temperature: from -30°C				
	up to 70°C; Storage humidity: < 80%;				
	Working humidity: < 60%; Complete set				
	include; Tablet; Envelope with password				
	; Safety protector case ; Diagnostic				
	connector DBScar; Extension cable OBD				
	II; Power adapter; USB data cable;				
	Adapter set for older cars; Case for				
	equipment and adapters holding				
5	Tool Caddy - 5 Drawers Mobile Trolley;	Pc	1	2 /	
	Loading Capacity Per Drawer 45 kg;				
	Static Load Capacity 480 kg; Overall:				
	687x459x722 mm; Overall w/caster :				
	687x459x840 mm; 3 Drawer: 578x378x75				
	mm; 2 Drawer: 578x378x155 mm				
6	Gasoline Engine Driven Compressor -	Set	22	1 1	
	Pumping group capacity Single-phase				
	Electric Motor - 90 l/m - 5,40 m³/h - 3.18;				
	Three-phase Electric Motor - 100 l/m -				
	6,00 m ³ /h - 3.53; Low Consumption				
	Single-phase Electric Motor - 50 l/m - 3,00				
	m³/h - 1.77; Filling time: Cylinder filling				
	time from 10 l-0/200 bar (cylinder filling				
	measurement from 0 to 200 bar \pm 5%)				
	Single-phase Electric Motor - 25 min;				

## display of the content of the con					
Drum application330*420mm; Pressure ratio: 50:1; Working pressure:68bar; Max. free flowrate:850g/min; Max. fluid pressure:400bar; Cylinder dia:70mm; Air consumption:2501/min@6.2bar; 1/4" inlet and outlet air regulator with water filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/mir; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Fr/16 (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" 1D, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pe - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load;345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2		Electric Motor - 39.5 kg - 87 Lbs; Three- phase Electric Motor - 39 kg - 86 Lbs; Low Consumption - Single-phase Electric Motor - 39.5 kg - 87 Lbs; Noise level Single-phase Electric Motor - 91 db; Three-phase Electric Motor - 95 db; Low Consumption Single-phase Electric			
Drum application330*420mm; Pressure ratio: 50:1; Working pressure:68bar; Max. free flowrate:850g/min; Max. fluid pressure:400bar; Cylinder dia:70mm; Air consumption:2501/min@6.2bar; 1/4" inlet and outlet air regulator with water filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/mir; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Fr/16 (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" 1D, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pe - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load;345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	7	Air Grease Lubricator - Capacity:30L;	set	1 .	
Max. free flowrate:850g/min; Max. fluid pressure:400bar; Cylinder dia:70mm; Air consumption:250L/mine:6c.bar; 1/4" inlet and outlet air regulator with water filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Opcrated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1;2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/fb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 4ttachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 4ttachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 4ttachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 4ttachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 4ttachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting 7th hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height 3m; Number of load chaim:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg			J.		
pressure:400bar; Cylinder dia:70mm; Air consumption:2501/min@6,2bar; 1/4" inlet and outlet air regulator with water filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/min; Output: 1.34; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger. 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (7.6.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Torch handle: 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg					
consumption:250L/min@6.2bar; 1/4" inlet and outlet air regulator with water filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Opcrated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) of of (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chaim:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
and outlet air regulator with water filtering device; Grease hose: 5M; Weight-16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0- 450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2' (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain: 2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-1344; Low to Medium Temp. tank 2					
filtering device; Grease hose: 5M; Weight:16KG 8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0- 450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc- Oxygen Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chaim: 2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-1344; Low to Medium Temp. tank 2					
Weight-16KG Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/min; Output: 1.3A, Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 28m/s2 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain: 2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg Prevo - R-134A; Low to Medium Temp. tank 2					
8 Portable Hand Drill - cordless drill; Battery Voltage: 26V; No Load Speed: 0-450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" 1D, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain: 2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Battery Voltage: 26V; No Load Speed: 0-450t/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450t/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000tpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" 1D, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	0				
450r/min; Output: 1.3A; Size: approx. 21x19x10cm; delivers up to 12N.m of torque and 0-450r/min of speed; inclusions: 1x Electric Drill, 2x Battery, 1x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" IID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	8		Set	2	
21x19x10cm; delivers up to 12N.m of torque and 0.450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
torque and 0-450r/min of speed; inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
inclusions: 1 x Electric Drill, 2 x Battery, 1 x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Ouffit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Cutting Tip, Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain: 2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
x Charger 9 Battery Operated Impact Wrench - 1/2 inch drive with set of socket and air hose, heavy duty, Square Drive : 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional fips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
inch drive with set of socket and air hose, heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
heavy duty, Square Drive: 1/2" (13mm), Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	9		Set	2 .	
Free Speed: 5000rpm, Max Torque: 230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
230Ft/lb (310N.m), Avg. Air Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Consumption: 8Cfm(2281/min), Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 1ghter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. Set 2 4 2 4 5 6 7 7 7 7 1 1 1 1 1 1 1 1 1					
Operating Pressure: 90psi (6.3bar), Air Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Inlet Size: 1/4", Air Hose: 3/8" ID, Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. Set 2					
Vibration on handle: 2.8m/s2 10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2		N N N N N N N N N N N N N N N N N N N			
10 Cutting Torch and Gauges - Welding and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
and Cutting Outfit; cuts up to 3/4" (19.1 mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	10	107	Set	2	
mm) or 6" (152.4 mm) with optional tips; wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp.			Set	_	
wields up to 1/8" (3.2 mm) or 3" (76.2 mm) with optional nozzles; 1 pc - Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp.					
Oxygen Regulator; 1 pc - Acetylene Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Regulator; 1 pc - Torch handle; 1 pc - Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Cutting Attachment; 1 pc - Size 2 Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
Welding Nozzle; 1 pc - Cutting Tip, Size 1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
1; 1 pc - 25ft. Twin hose 1/4" with fittings; 1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
1 pc - lighter and goggles 11 Chain Block - Rating lift weight:2Ton; Pc 1 Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
11 Chain Block - Rating lift weight:2Ton; Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp.					
Lift height: 3m; Number of load chain:2; Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	11		D _C	1	
Hook to hook distance:380 mm; Chain pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2	11		10	1	
pull to lift full load:345 N; Net weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2					
weight:12.5kg 12 Freon - R-134A; Low to Medium Temp. tank 2		900			
12 Freon - R-134A; Low to Medium Temp. tank 2					
D (: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	12	0 0	tank /	2 .	
Kerrigeration; Weight:13.6kg/ tank;		Refrigeration; Weight:13.6kg/ tank;			

Pofrigorous Co. 1				
Refrigerant for medium temperature				
refrigeration; Refrigerant for air				
conditioning and car air-conditioning				
applications; Brand New; Non-				
Flammable				
			TOTAL	k.
Amount in Words:				
				- E
Other Requirements:				
Statement of Warranty – minimum of one (1)	V			
1. Statement of Wallanty - minimum of one (1)				
	,	Delivery Period	:Thi	rty (30) Calendar Days
		Warranty	:	272
			Signature or	er printed name
		Ot	ffice Telephone	No./Fax/Mobile No.
		-		Date
			Emai	Address