

## Republic of the Philippines QUEZON CITY GOVERNMENT

BAC – Goods and Services 2<sup>nd</sup> floor, Procurement Department, Finance Building, Quezon City Hall Compound



## REQUEST FOR QUOTATION SHOPPING – SECTION 52.1B

		DATE	:	JUNE 28, 2022
		PROJECT NO.	:	QCPL-22-OE-731C
Name of Company	:			
Address	:			
Contact No.	:			
Project Title	:	PROCUREMENT OF PRINTER, ROUTER AND OTHERS		
Approved Budget of the Contract	:	P 277,780.00		
End-User /		QUEZON CITY PUBLIC LIBRARY		

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **JULY 01, 2022, 10:00 AM** Philippine Standard Time, together with the following documents of your company:

- PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2022);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the QC BAC- Goods and Services
- 6 Income/Business Tax Return (for FY 2021) (For ABCs above P500,000.00)
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

## in a SEALED LONG BROWN ENVELOPE shall:

- 1. Contain the Project Name and PR Number of the contract to be bid in capital letters;
- 2. Bear the name and address of the Bidder in capital letters;
- 3. Be addressed to the Procuring Entity's BAC.

PROJECT TITLE: PROCUREMENT OF PRINTER, ROUTER AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE

2/F Procurement Department, Finance Building

Quezon City Hall Compound

For any clarification you may contact us at 8-988-4242 loc. 8506/8709.

ATTY. DOMINIC B. GARCIA
Officer-in-Charge/ Head, BAC-Secretariat

M

## TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	TTEM & DESCRIPTION		QTY.	UNIT PRICE	ITEM TOTAL
	With the following minimum Technical Specifications				
	PRINTER On-demand ink jet, 180 nozzles black 59 nozzles each colour Print Method: On-demand inkject (Piezoelectric) Maximum Print Resolution: 5760x1440 dpi (with variable-Sized Droplet Technology) Minimum Ink Droplet Volume: 1.5pl Automatic Duplex Printing: No Print Direction: Bi-directional printing, Unidirectional Printing Nozzle Configuration: 90 per colour (Cyan, Light Cyan, Magenta, Light Magenta, Yellow, Black) Print Speed: Draft, A4 (Black / Colour): Up to 15ppm / 15ppm Photo Default: 10x15cm/4x6inches – Approximately 45 sec per photo (Borderless) Paper Handling: Number of Paper Trays: 1 (one) Standard Paper Input Capacity: Up to 100 sheets, A4 Plain paper (75g/m²) Up to 30 sheets, Premium Glossy Photo Paper Output Capacity: Up to 50 sheets, A4 Plain Paper Up to 20 sheets, Premium Glossy Photo Paper Maximum Paper Size: 12.95 x 44 inches Paper Sizes: A3+, A3, B4, A4, A5, A6, B5, 10x15cm (4x6inches), 13x18cm (5x7inches), 16:9 wide size, Letter (8.5x11inches), Legal (8.5x14inches), Half Letter (505x8.5inches), 9x13cm (3.5x5inches), 12x20cm(5x8inches), 20x25cm(8x10inches), Envelopes: #10(4.125x9.5inches) DL (110x220mm), C4 (229x324mm), C6(114x162mm) Paper Feed Method: Friction feed Print Margin: 0mm top, left, right, bottom via custom settings. Otherwise 3mm top, left, right, bottom	unit	6		
2	Rackmount Gigabit Ethernet Router	unit	1		
	Specifications Details CPU core count: 9 CPU nominal frequency: 1.2 GHz Dimensions: 443 x 175 x 44 mm				

				· · · · · · · · · · · · · · · · · · ·	
	RouterOS license: 6				
	Operating System: RouterOS				
	Size of RAM: 2 GB				
	Storage size: 128 MB				
	Storage type: NAND				
	MTBF: Approximately 200'000 hours at 25C				
	Tested ambient temperature: -20°C to 60°C				
			- 25		
//	IPsec hardware acceleration: Yes				
	Powering Details			1	
	Number of AC inputs: 2				
	AC input range: 100-240				
	Number of DC inputs: 1 (PoE-IN)				
	Max power consumption: 39 W				
	and the second s				
	Max power consumption without attachments: 34 W				
	Cooling type: 2				
4					J
	PoE in: Passive PoE				
	PoE in input Voltage: 15-57 V				
	Ethernet Details				
	10/100/1000 Ethernet ports: 7				
1	Ethernet Combo ports: 1				
1	Fiber Details: SFP+ ports: 1		I.		
1	Peripherals Details:				
1	Number of SIM slots: 1 Smart card (Mini SIM)				
	Memory card type: microSD				
I					
A .	Memory Cards: 1				
1					
1	Serial console port: RS232				ľ.
	Number of USB ports: 1			1	
	USB Power Reset: Yes			1	
	USB slot type: microUSB type AB				
	Max USB current (A): 1				
	Other Details:				
	CPU temperature monitor: Yes				
	Current Monitor: Yes				
	PCB temperature monitor: Yes				
	Voltage Monitor: Yes				
	Voltage Monitor: 1es			A Comment of the Comm	
					I.
	Beeper: Yes	unit	5		
3	Beeper: Yes Gigabit Ethernet Switch 24 Port	unit	5		
3	Beeper: Yes Gigabit Ethernet Switch 24 Port	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details:	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details:  Dimensions: 443 x 144 x 44 mm	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details:  Dimensions: 443 x 144 x 44 mm	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C  Tested ambient temperature:	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details:	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C  Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN)	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C  Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH  MTBF: Approximately 200'000 hours at 25C  Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V  Max power consumption: 19 W  Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V  Ethernet Details:	unit	5		
3	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24	unit	5		
3	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature:  Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V  Ethernet Details:	unit	5		
3	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details:	unit	5		
	Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2				
3	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details:	unit	5		
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point				
	Beeper: Yes  Gigabit Ethernet Switch 24 Port  Specifications Details: Dimensions: 443 x 144 x 44 mm  Storage size: 2 MB  Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V  Ethernet Details: 10/100/1000 Ethernet ports: 24  Fiber Details: SFP+ ports: 2  Ceiling Access Point Specifications Details:				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C Tested ambient temperature: -40°C to 70°C				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C Tested ambient temperature: -40°C to 70°C Wireless				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2  Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C Tested ambient temperature: -40°C to 70°C Wireless Capabilities Details:				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2 Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C Tested ambient temperature: -40°C to 70°C Wireless				
	Gigabit Ethernet Switch 24 Port Specifications Details: Dimensions: 443 x 144 x 44 mm Storage size: 2 MB Storage type: FLASH MTBF: Approximately 200'000 hours at 25C Tested ambient temperature: Powering Details: Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 10-30 V Max power consumption: 19 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 10-30 V Ethernet Details: 10/100/1000 Ethernet ports: 24 Fiber Details: SFP+ ports: 2  Ceiling Access Point Specifications Details: CPU core count: 1 CPU nominal frequency: 650 MHz Dimensions: 185mm diameter, 31mm height RouterOS license: 4 Operating System: RouterOS Size of RAM: 64 MB Storage size: 16 MB Storage type: FLASH MTBF: Approximately 100'000 hours at 25C Tested ambient temperature: -40°C to 70°C Wireless Capabilities Details:				

	Wireless 2.4 GHz standards: 802.11b/g/n				
	Antenna gain dBi for 2.4 GHz: 2				
	Wireless 2.4 GHz chip model: QCA9533				
	Wireless 2.4 GHz generation: Wi-Fi 4				
	Ethernet Details:				
	10/100 Ethernet ports: 1				
	F 2				
	Powering Details:				
	Number of DC inputs: 1 (PoE-IN)				
	Max power consumption: 4 W				
	Cooling type: Passive				
	PoE in: 802.3af/at				
	PoE in input Voltage: 11-57 V				
	Other Details:				
	Mode button: Yes				
	Wireless specifications:				
	2.4 GHz Transmit (dBm) Receive Sensitivity				
	1 MBit/s 22 -96				
	6MBit/s 20 -93				
	54MBit/s18 -74				
	MCS0 20 -93				
	MCS7 16 -71				
5	8-Port Gigabit Switch	unit	10		
	Specifications:				
	1000Base-T Interface: 8				
	Auto MDI/MDIX: Yes				
	Switching Capacity: 16 Gbps				
	Max. Packet Forwarding Rate: 11.9 Mpps				
	Store & Forwarding: Yes				
	Dimension: 130 x 79 x 22mm				
	Weight: 0.13 kgs				
	Maximum Power Consumption: 4.80 W				
	Standby Power Consumption: 0.7 W				
	Maximum Heat Dissipation: 16.368 BTU/h				
	MTBF: 1,061,267 hours				
	Power Input AC: 100 ~ 240 V				
	Flash Memory Size: 64KBytes				
	Packet Buffer Size: 192KBytes	(			
	FAN: Fanless				
	Comply with RoHS 6: Yes				
	Energy Efficiency Ethernet (EEE): Yes				
	Power Saving By Link Status: Yes				
	Power Saving By Cable Length: Yes				
	MAC Address Table Size: 4K				
	802.3x Flow Control: Yes				
	Head-of-line (HOL) Blocking Prevention: Yes				
	Jumbo Frame: 9,720 Bytes				
	Surge/Lightning Protection (AC Power Inet): 1kV				
	Surge/Lightning Protection (All Ethernet Ports): 1kV				
	Air Discharge: 8kV Switch intelligence:				
	Unmanaged				
	Port count: 1000Base-T Interface x 8				
	Contact Discharge: 4kV"				
	Community of the				
				TOTAL	
					1

unt in Words:		

011	Requirem	
Ulther	Keamrem	ent:

1. Statement of Warranty: Minimum of one (1) year.

Delivery Perio	d :	Thirty (30) calendar days
Warranty	:	
-	5	Signature over printed name
-	77.577	
	Off	ice Telephone No./Fax/Mobile No.
		Date
-		
		Email Address