

Republic of the Philippines QUEZON CITY GOVERNMENT

BAC – Goods and Services 2nd floor, Procurement Department, Finance Building, Quezon City Hall Compound



REQUEST FOR QUOTATION SHOPPING – SECTION 52.1B

		DATE	: _	JUNE 21, 2022
		PROJECT NO.	: _	QCPL-22-OE-731B
			_	
Name of Company	:			
Address	:			
Contact No.	:			
Project Title	:	PROCUREMENT OF PRINTER, ROUTER AND OTHERS		
Approved Budget of the Contract	:	P 277,780.00		
End-User / Implementing Office	:	QUEZON CITY PUBLIC LIBRARY		

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **JUNE 24, 2022, 10:00 AM** Philippine Standard Time, together with the following documents of your company:

- PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2022);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2021) (For ABCs above P500,000.00)
- If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** shall:

- 1. Contain the Project Name and PR Number of the contract to be bid in capital letters;
- 2. Bear the name and address of the Bidder in capital letters;
- 3. Be addressed to the Procuring Entity's BAC.

PROJECT TITLE: PROCUREMENT OF PRINTER, ROUTER AND OTHERS

Quezon City Local Government BIDS AND AWARDS COMMITTEE

2/F Procurement Department, Finance Building

Quezon City Hall Compound

For any clarification you may contact us at 8-988-4242 loc. 8506/8709.

TERMS AND CONDITIONS

- 1. Bidders shall **provide correct and accurate** information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation exceeding the Approved Budget for the Contract (ABC) shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	ITEM & DESCRIPTION	UNIT OF ISSUE	QTY.	UNIT PRICE	ITEM TOTAL
	With the following minimum Technical Specifications				
1	PRINTER On-demand ink jet, 180 nozzles black 59 nozzles each colour Print Method: On-demand inkject (Piezoelectric) Maximum Print Resolution: 5760x1440 dpi (with variable-Sized Droplet Technology) Minimum Ink Droplet Volume: 1.5pl Automatic Duplex Printing: No Print Direction: Bi-directional printing, Unidirectional Printing Nozzle Configuration: 90 per colour (Cyan, Light Cyan, Magenta, Light Magenta, Yellow, Black) Print Speed: Draft, A4 (Black / Colour): Up to 15ppm / 15ppm Photo Default: 10x15cm/4x6inches – Approximately 45 sec per photo (Borderless) Paper Handling: Number of Paper Trays: 1 (one) Standard Paper Input Capacity: Up to 100 sheets, A4 Plain paper (75g/m²) Up to 30 sheets, Premium Glossy Photo Paper Output Capacity: Up to 50 sheets, A4 Plain Paper Up to 20 sheets, Premium Glossy Photo Paper Maximum Paper Size: 12.95 x 44 inches Paper Sizes: A3+, A3, B4, A4, A5, A6, B5, 10x15cm (4x6inches), 13x18cm (5x7inches), 16:9 wide size, Letter (8.5x11inches), Legal (8.5x14inches), Half Letter (505x8.5inches), 9x13cm (3.5x5inches), 12x20cm(5x8inches), 20x25cm(8x10inches), Envelopes: #10(4.125x9.5inches) DL (110x220mm), C4 (229x324mm), C6(114x162mm) Paper Feed Method: Friction feed Print Margin: 0mm top, left, right, bottom via custom settings. Otherwise 3mm top, left, right, bottom	Unit	6		
2	Rackmount Gigabit Ethernet Router Specifications Details CPU core count: 9 CPU nominal frequency: 1.2 GHz	unit	1		
	Dimensions: 443 x 175 x 44 mm				

2

		T	1	T	T
	RouterOS license: 6				
	Operating System: RouterOS				
	Size of RAM: 2 GB				
	Storage size: 128 MB				
	Storage type: NAND				
	MTBF: Approximately 200'000 hours at 25C				
	Tested ambient temperature: -20°C to 60°C				
	IPsec hardware acceleration: Yes				
	Powering Details				
	Number of AC inputs: 2				
	AC input range: 100-240				
	Number of DC inputs: 1 (PoE-IN)				
	Max power consumption: 39 W				
	Max power consumption without attachments: 34 W				
	Cooling type: 2				
	PoE in: Passive PoE				
	PoE in input Voltage: 15-57 V				
	Ethernet Details				
	10/100/1000 Ethernet ports: 7				
	Ethernet Combo ports: 1				
	Fiber Details: SFP+ ports: 1				
	· ·				
	Peripherals Details:				
	Number of SIM slots: 1 Smart card (Mini SIM)				
	Memory card type: microSD				
	Memory Cards: 1				
	Serial console port: RS232				
	Number of USB ports: 1				
	USB Power Reset: Yes				
	USB slot type: microUSB type AB				
	Max USB current (A): 1				
	Other Details:				
	CPU temperature monitor: Yes				
	Current Monitor: Yes				
	PCB temperature monitor: Yes				
	Voltage Monitor: Yes				
	Beeper: Yes				
3	Gigabit Ethernet Switch 24 Port	unit	5		
	Specifications Details:				
	Dimensions: 443 x 144 x 44 mm				
	Storage size: 2 MB				
	Storage type: FLASH				
	MTBF: Approximately 200'000 hours at 25C				
	Tested ambient temperature:				
	Powering Details:				
	Number of DC inputs: 2 (DC jack, PoE-IN)				
	DC jack input Voltage: 10-30 V				
	Max power consumption: 19 W				
	Cooling type: Passive				
	PoE in: Passive PoE				
	PoE in input Voltage: 10-30 V				
	Ethernet Details:				
	10/100/1000 Ethernet ports: 24				
	Fiber Details:				
	SFP+ ports: 2				
4	Ceiling Access Point	unit	8		
	Specifications Details:				
	CPU core count: 1				
	CPU nominal frequency: 650 MHz				
	Dimensions: 185mm diameter, 31mm height				
	RouterOS license: 4				
	Operating System: RouterOS				
	Size of RAM: 64 MB				
	Storage size: 16 MB				
	Storage type: FLASH				
	MTBF: Approximately 100'000 hours at 25C				
	Tested ambient temperature: -40°C to 70°C				
	Wireless				
	Capabilities Details:				
1	Wireless 2.4 GHz Max data rate: 300 Mbit/s Wireless 2.4 GHz number of chains: 2				
					•

Wireless 2.4 GHz standards: 802.11b/g/n Antenna gain dBi for 2.4 GHz: 2 Wireless 2.4 GHz chip model: QCA9533 Wireless 2.4 GHz peneration: Wi-Fi 4 Ethernet Details: 10/100 Ethernet ports: 1 Powerina Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/art PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1 MBit/s 22 -89 6 MBit/s 20 -93 5 4MBit/s18 -74 MCS0 20 -93 5 4MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-1 Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max, Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 16.368 BTU/h MIBE: 1.061.267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 44RBytes
Wireless 2.4 GHz chip model: QCA9533 Wireless 2.4 GHz generation: Wi-Fi 4 Ethernet Details: 10/100 Ethernet ports: 1 Powering Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/at PoE in input Voltage: 11-57 V Other Details: Mode butlon: Yes Wireless specifications; 2.4 GHz Transmit (dBm) Receive Sensitivity 11MBit/s 22 -96 11MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-1 Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTB: 1.061,267 hours Power Input AC: 100 ~ 240 V Flosh Memory Size: 64KBytes
Wireless 2.4 GHz generation: Wi-Fi 4 Ethernet Details: 10/100 Ethernet ports: 1 Powering Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/cat PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dbm) Receive Sensitivity 11MBit/s 22 -96 11MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-1 Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTB:: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64(Bytes
Ethernet Details: 10/100 Ethernet ports: 1 Powering Details; Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/at PoE in input Voltage: 11-57 V Other Details; Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 11MBit/s 22 -96 11MBit/s 22 -96 4MBit/s 20 -93 54MBit/s 18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 14 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MBE: 1.061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64(RSytes)
10/100 Ethernet ports: 1 Powering Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802,36f/at PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 11MBit/s 22 -96 11MBit/s 20 -93 54MBit/s 18 -74 MCSO 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
10/100 Ethernet ports: 1 Powering Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802_36f/at PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1MBit/s 22 -96 11MBit/s 20 -93 54MBit/s 20 -93 54MBit/s 18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Powering Details: Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/at PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1 MBit/s 22 -96 11 IMBit/s 22 -96 11 IMBit/s 22 -98 6 MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-1 Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Number of DC inputs: 1 (PoE-IN) Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/at PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications; 2.4 GHz Transmit (dBm) Receive Sensitivity IMBit/s 22 -96 11 MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 10008ase-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Max power consumption: 4 W Cooling type: Passive PoE in: 802.3af/at PoE in Input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1MBit/s 22 -96 11MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 10.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Cooling type: Passive PoE in: 802.3d/af PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1 MBit/s 22 -96 11 MBit/s 22 -96 11 MBit/s 20 -93 54MBit/s 20 -93 54MBit/s 18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1.061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
PoE in: 802.3af/at PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1MBit/s 22 -96 11MBit/s 22 -89 6MBit/s 20 -93 54MBit/s 18 -74 MC\$0 20 -93 MC\$7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
PoE in input Voltage: 11-57 V Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1MBit/s 22 -96 11MBit/s 20 -93 6MBit/s 20 -93 54MBit/s 18 -74 MCS0 20 -93 MCS7 16 -71 8 -Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1.061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Other Details: Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1 MBit/s 22 -96 11 MBit/s 22 -89 6 MBit/s 20 -93 5 4 MBit/s 18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Mode button: Yes Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 1MBit/s 22 -96 11MBit/s 22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Wireless specifications: 2.4 GHz Transmit (dBm) Receive Sensitivity 11MBit/s 22 -96 111MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
2.4 GHz Transmit (dBm) Receive Sensitivity 1
1MBit/s 22
11MBit/s22 -89 6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
6MBit/s 20 -93 54MBit/s18 -74 MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
54MBit/s18
MCS0 20 -93 MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
MCS7 16 -71 5 8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
8-Port Gigabit Switch Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Specifications: 1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
1000Base-T Interface: 8 Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Auto MDI/MDIX: Yes Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Switching Capacity: 16 Gbps Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Max. Packet Forwarding Rate: 11.9 Mpps Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Store & Forwarding: Yes Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Dimension: 130 x 79 x 22mm Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Weight: 0.13 kgs Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Maximum Power Consumption: 4.80 W Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Standby Power Consumption: 0.7 W Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Maximum Heat Dissipation: 16.368 BTU/h MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
MTBF: 1,061,267 hours Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Power Input AC: 100 ~ 240 V Flash Memory Size: 64KBytes
Flash Memory Size: 64KBytes
I Packet Butter Size: 1978 Bytes I I I I I I I I I I I I I I I I I I I
FAN: Fanless
Comply with RoHS 6: Yes
Energy Efficiency Ethernet (EEE): Yes
Power Saving By Link Status: Yes
Power Saving By Cable Length: Yes
MAC Address Table Size: 4K
802.3x Flow Control: Yes
Head-of-line (HOL) Blocking Prevention: Yes
Jumbo Frame: 9,720 Bytes
Surge/Lightning Protection (AC Power Inet): 1kV
Surge/Lightning Protection (All Ethernet Ports): 1kV
Air Discharge: 8kV Switch intelligence:
Unmanaged
Port count: 1000Base-T Interface x 8
Contact Discharge: 4kV"
TOTAL
IOIAL

Amount in Words:			

Other Requirement:

1. Statement of Warranty: Minimum of one (1) year.

Delivery Period	:	Inirty (30) calendar days
Warranty	:	
_		
	9	Signature over printed name
_	Off	ice Telephone No./Fax/Mobile No.
	0	receptione way was in the
_		
		Date
_		
		Email Address