



**REQUEST FOR QUOTATION
SECTION 52.1b
SHOPPING**

DATE : AUGUST 30, 2022

PROJECT NO. : QCCAC-22-HCS-938

Name of Company : _____
Address : _____
Contact No. : _____
Project Title : **VARIOUS HARDWARE SUPPLIES (CONCRETE NAIL, FLOOR OUTLET, AND OTHERS)**
Approved Budget of the Contract : **P 446,089.90**
End-User / Implementing Office : **QUEZON CITY COMPETENCY ASSESSMENT CENTER**

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **SEPTEMBER 02, 2022, 10:00 A.M.** Philippine Standard Time, together with the following documents of your company:

- 1 PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2022);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2021) (For ABCs above P500,000.00)
- 7 If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** issued by **QC BAC- Goods and Services**.

(Sgd.) ATTY. DOMINIC B. GARCIA
Officer-in-Charge / Head, BAC-Secretariat

TERMS AND CONDITIONS

1. Bidders shall **provide correct and accurate** information required in this form.
2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
4. Quotation **exceeding** the Approved Budget for the Contract (ABC) shall be **rejected**.
5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
7. The City General Services Department (CGSD) shall have the right to inspect the goods.
8. Non-submission of eligibility documents shall mean disqualification of Quotation.
9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

| ITEM NO. | ITEM & DESCRIPTION | UNIT OF ISSUE | QTY. | UNIT PRICE | ITEM TOTAL |
|----------|--|---------------|------|------------|------------|
| 1 | TIE WIRE galvanized iron tie wire No. 16 | kilo | 30 | | |
| 2 | COMMON WIRE NAIL 2 inches | kilo | 30 | | |
| 3 | COMMON WIRE NAIL 3 inches | kilo | 30 | | |
| 4 | COMMON WIRE NAIL 4 inches | kilo | 30 | | |
| 5 | CONCRETE NAIL 1 inch | kilo | 30 | | |
| 6 | CONCRETE NAIL 2 inches | kilo | 30 | | |
| 7 | CONCRETE NAIL 3 inches | kilo | 30 | | |
| 8 | RSC/IMC Size: 1/2-4inches, Packing: Accepted Thickness: 0.7mm-2.1mm, Length: 10'/3.05m | piece | 30 | | |
| 9 | ENTRANCE CAP Package Dimensions 6.57 x 4.17 x 3.54 inches, Item Weight 9.4 ounces | piece | 30 | | |
| 10 | LOCKNUT AND BUSHING 1/2, 3/4, 1 1/4, 1-1/2, 2 metal | pair | 50 | | |
| 11 | GROUND FAULT CURRENT INTERRUPTING DEVICE (GFCI) Rated Voltage (UN): 250VAC, Rated Current (In): 16A, Rated Power (Pn): 3500W, Rated Frequency (Fn): 50Hz / 60Hz, Mechanical and Electrical Life: 6000 times | piece | 20 | | |
| 12 | 3/16inch X 1 METAL SCREW Carbon Steel, Head type Hex Washer, Thread type High-Low, Maximum Fixture Thickness 1/4inch to 3/4inch | piece | 100 | | |
| 13 | CONDUIT STRAP/CLAMP size 1/2inch, 3/4inch, 1inch, stainless | piece | 50 | | |
| 14 | WIRING BOARDS 3/4 INCH x 4 FT x 8 FT | set | 10 | | |

| | | | | | |
|----|---|-------|-----|--|--|
| | Plywood Size: 3/4 inch x 4 ft x 8 ft marine plywood for various applications. Marine-grade plywood is a sturdier, higher-quality material | | | | |
| 15 | FLOOR OUTLET Floor Mounted Pop-out Outlet Shape: Round or Square, Color: Gold and Silver, Current: 16A, Voltage: 250V, Conforms to IEC standards, High impact aluminum enclosure | piece | 30 | | |
| 16 | WORKING GLOVES Knit Work Gloves, Textured Rubber Latex Coated for Construction, 12-Pairs | piece | 30 | | |
| 17 | HARD HAT 55cm-65cm, Shell material ABS, Head protector, durable and lightweight, elastic suspension | piece | 30 | | |
| 18 | SAFETY GOGGLES Material: PC (lens) + PVC (frame), Size: 17x8 (cm) | piece | 30 | | |
| 19 | WIRE AWG # 12 (3.5MM2) (3.5MM2), Size #12AWG / 3.5mm2, Length: 150 meters stranded | box | 30 | | |
| 20 | WIRE AWG # 14 (2.0MM2) (2.0MM2), Size #14 AWG; 7 x 0.0147; -25 °C; 600 V; Stranded Bare Copper; PVC, Olympic Wire and Cable, MPN: THHN 14G/ST BLU stranded | box | 30 | | |
| 21 | ELECTRICAL TAPE Use at not more than 600V and at no more than 80°C (176°F) BIG | roll | 100 | | |
| 22 | WOOD SCREW 1/2x8inches Great for softer materials works for pine, plywood, particle board, MDF and melamine, Hard to Strip deep cut Philips Drive, no stripping heads any more (pre-drilling recommended), 100 screws per pack | box | 30 | | |
| 23 | RECEPTACLE SURFACE TYPE 4 - 1/4inches Ceiling Bulb Receptacle, Non-Conductive, Heat Resistant, Flame Retardant, Maximum Voltage: 250V, Current: 4A-6A | piece | 30 | | |
| 24 | RECEPTACLE FLUSH TYPE 2 -1/4inches Ceiling Bulb Receptacle, Non-Conductive, Heat Resistant, Flame Retardant, Maximum Voltage: 250V, Current: 4A-6A | piece | 30 | | |
| 25 | INCANDESCENT BULB 50 W/ 250V AC, Incandescent Bulb gives off heat as it lights up a warm yellow hue. 50W and 250V | piece | 30 | | |
| 26 | CONVENIENT OUTLET C.O (GROUNDING TYPE, / FLUSH TYPE) 2 GANG W/ PLATE AND COVER Universal Outlet, Electrical Rating: 13A 250V~, Unit Weight: 0.1 kg, Unit Dimension: 12 x 7.5 x 4 cm, Box Weight: 0.1 kg, Box Dimension: 14 x 9 x 7 cm | set | 30 | | |
| 27 | PVC SQUARE BOX, 4x4 (inches), Poly PVC Large Square Box 4 x 4 with Cover is the leading brand of covered square box preferred by electricians in the Philippines. It comes with eight (8) covered detachable flexible hose outlet on the sides and four (4) Punchable Holes in the bottom. The box comes with a cover. | piece | 30 | | |
| 28 | FLEXIBLE CONDUIT 1/2, 3/4 Size Variation: 1/2inch, 3/4inch, 1inch, same as Polyflex / Euroflex / CC; Sold per roll of 50 meters | meter | 50 | | |

| | | | | | |
|----|---|-------|----|--|--|
| 29 | PVC CONDUIT 1/2, 3/4, 1/2inch 20mm outside diameter, 17mm inside diameter 3/4inch, 25mm outside diameter, 23mm inside diameter | piece | 30 | | |
| 30 | JUNCTION BOX PVC Material: Plastic Junction Box Cover: 10cm (Length) x 10cm (Width) | piece | 30 | | |
| 31 | UTILITY BOX PVC Utility Box 2 x 4 fire Retardant at 750°C shock resistant, can withstand high impact, comes with mounting screws | piece | 30 | | |
| 32 | CONNECTORS PVC 1/2 Flexible connector size 1/2 Pvc connector size 1/2 | piece | 50 | | |
| 33 | CONNECTORS PVC 3/4 Flexible connector size 3/4 Pvc connector size 3/4 | piece | 50 | | |
| 34 | CONNECTORS RSC 3/4 Size: 3/4inch steel or stainless | piece | 50 | | |
| 35 | ELBOW PVC 1/2 Fits any regular 1/2 orange PVC pipe in the market. Connect with PVC pipe cements for sturdier build | piece | 20 | | |
| 36 | ELBOW PVC 3/4 Fits any regular 3/4 orange PVC pipe in the market. Connect with PVC pipe cements for sturdier build | piece | 20 | | |
| 37 | ELBOW RSC 1/2 standard piping materials, Higher flow capacity, most secured connection and strongest joint, Patented Built-in slope design, Air tight and leak free pvc pipe | piece | 20 | | |
| 38 | ELBOW RSC 3/4 standard piping materials, Higher flow capacity, most secured connection and strongest joint, Patented Built-in slope design, Air tight and leak free pvc pipe | piece | 20 | | |
| 39 | SWITCH (SINGLE POLE WITH PLATE AND COVER) Power Gear, White, Single Rocker Toggle Switch Oversized Wall Plate Cover, 1 Gang, Unbreakable Faceplate, 3.1inches x 4.9inches, screws included, 1pack | piece | 20 | | |
| 40 | TRY SQUARE 300MM LONG 300mm Green Base Stainless Steel Framing Square Right Angle Ruler Thicken Try Square Ruler | piece | 30 | | |
| 41 | STEEL SQUARE 300MM LONG 150mmx300mm Thickened High-end Square Stainless Steel Framing Square Right Angle Ruler Thicken Try Square Ruler | piece | 30 | | |
| 42 | FILES-HALF ROUND Half Round File – Durable Steel File for Concave, Convex, and Flat Surfaces, Comfortable Anti-Slip Grip, Double Cut and Single Cut | piece | 30 | | |
| 43 | FILLET GAUGE Fillet Weld Gauge Gage Set Stainless Steel Welding Inspection Gauge Inch/Metric | piece | 30 | | |
| 44 | CUTTING DISC Specification: A 30 R BF, Diameter (mm): 180, Bore diameter (mm): 22.23, Thickness (mm): 3.0, Product Type: Cutting disc, Wheel Shape: Straight | piece | 30 | | |

| | | | | | |
|--------------|---|-------|----|--|--|
| 45 | GRINDING DISC Disc Diameter: 100mm, Thickness: 6.0mm, Specification: A24PBF, Bore Diameter: 16mm | piece | 30 | | |
| 46 | STEEL BRUSH Carbon Steel Welding Wire Scratch Brushes Heavy Duty | piece | 50 | | |
| TOTAL | | | | | |

Amount in Words: _____

Delivery Period : **THIRTY (30) CALENDAR DAYS**

Warranty : _____

Signature over printed name

Office Telephone No./Fax/Mobile No.

Date

Email Address