

REPUBLIC OF THE PHILIPPINES QUEZON CITY GOVERNMENT BIDS AND AWARDS COMMITTEE – GOODS AND SERVICES



PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

PROCUREMENT OF AUTOMATED EXTERNAL DEFIBRILLATOR AND OTHERS

PROJECT NO. QCU-23-HME-1096

Government of the Republic of the Philippines

Sixth Edition July 2020

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.
- b. Specific details, such as the "name of the Procuring Entity" and "address for bid submission," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.
- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.

- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

Glossa	ry of Acronyms, Terms, and Abbreviations	4
Section	ı I. Invitation to Bid	7
Section	II. Instructions to Bidders	11
1.	Scope of Bid	12
2.	Funding Information	12
3.	Bidding Requirements	12
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	12
5.	Eligible Bidders	12
6.	Origin of Goods	13
7.	Subcontracts	13
8.	Pre-Bid Conference	13
9.	Clarification and Amendment of Bidding Documents	13
10.	Documents comprising the Bid: Eligibility and Technical Components	14
11.	Documents comprising the Bid: Financial Component	14
12.	Bid Prices	14
13.	Bid and Payment Currencies	15
14.	Bid Security	15
15.	Sealing and Marking of Bids	15
16.	Deadline for Submission of Bids	16
17.	Opening and Preliminary Examination of Bids	16
18.	Domestic Preference	16
19.	Detailed Evaluation and Comparison of Bids	16
20.	Post-Qualification	17
21.	Signing of the Contract	17
Section	n III. Bid Data Sheet	18
Section	IV. General Conditions of Contract	20
1.	Scope of Contract	21
2.	Advance Payment and Terms of Payment	21
3.	Performance Security	21
4.	Inspection and Tests	21
5.	Warranty	21
6.	Liability of the Supplier	22
Section	N. Special Conditions of Contract	23
Section	N. Schedule of Requirements	27
Section	NII. Technical Specifications	29
Section	vIII. Checklist of Technical and Financial Documents	34

Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF - Cost Insurance and Freight.

CIP - Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

EXW – Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project—Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC – Government-owned and/or –controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency

which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.

Section I. Invitation to Bid

Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (*e.g.*, the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IB must conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



QUEZON CITY GOVERNMENT BAC – GOODS AND SERVICES



INVITATION TO BID

August 03, 2023

	PROJECT NO.	OFFICE	PROJECT NAME	AMOUNT	SOURCE OF FUND	DELIVER PERIOD
1.	ASSESSORS-23-OSD-1076	CITY ASSESSOR'S OFFICE	VARIOUS OFFICE SUPPLIES (BALLPEN AND OTHERS)	P 934,282.00	GENERAL FUND	30 CD
2.	CGSD-23-GARMENTS- 0423	CITY GENERAL SERVICES DEPARTMENT	T-SHIRT WITH COLLAR	P 148,049.95	GENERAL FUND	30 CD
3.	CLIMATE-23-CS1-0631B	CLIMATE CHANGE AND ENVIRONMENTAL SUSTAINABILITY DEPARTMENT	FOOD & DRINKS AND OTHERS	P 744,787.00	GENERAL FUND	4 MONTH:
4.	CLIMATE-23-PS2-1118	CLIMATE CHANGE AND ENVIRONMENTAL SUSTAINABILITY DEPARTMENT	PRINTING OF POSTER AND OTHERS	P 226,080.00	GENERAL FUND	30 CD
5.	CPDD-23-MSLI-0698E	CITY PLANNING AND DEVELOPMENT DEPARTMENT	VARIOUS MEDICAL SUPPLIES AND OTHERS	P 136,192.70	GENERAL FUND	30 CD
6.	CPDD-23-OE-0690C	CITY PLANNING AND DEVELOPMENT DEPARTMENT	PHOTOCOPYING MACHINE AND OTHERS	P 413,804.00	GENERAL FUND	30 CD
7.	CPDD-23-OESC-0791D	CITY PLANNING AND DEVELOPMENT DEPARTMENT	TONER AND INK CARTRIDGES	P 874,165.60	GENERAL FUND	30 CD
8.	CPO-23-OSD-1093	CITY PROSECUTOR'S OFFICE	VARIOUS OFFICE SUPPLIES AND OTHERS	P 475,943.30	GENERAL FUND	30 CD
9.	DPOS-23-VPA-1107	DEPARTMENT OF PUBLIC ORDER AND SAFETY	TIRES AND BATTERIES	P 631,040.00	GENERAL FUND	30 CD
10.	DSQC-23-OESC-1056	DEPARTMENT OF SANITATION AND CLEANUP WORKS OF QUEZON CITY	INK CARTRIDGE AND OTHERS	P 535,578.25	GENERAL FUND	15 CD
11.	ENGINEERING-23-CE2- 0975	DEPARTMENT OF ENGINEERING	WALK BEHIND ROLLER	P 975,000,00	GENERAL FUND	30 CD
12.	HCDRD-23-OSD-1084	HOUSING, COMMUNITY DEVELOPMENT AND RESETTLEMENT DEPARTMENT	VARIOUS OFFICE SUPPLIES	P 229,931.37	GENERAL FUND	30 CD
13.	HEALTH-23-OE-0857B	QUEZON CITY HEALTH DEPARTMENT	LCD PROJECTOR	P 930,033.00	GENERAL FUND	30 CD
14.	HEALTH-23-SERVICES- 0516	QUEZON CITY HEALTH DEPARTMENT	PREVENTIVE MAINTENANCE AND CALIBRATION FOR NEGATIVE PRESSURE AND AIRCONDITIONING UNITS	P 162,000.00	TRUST FUND	30 CD
15.	MDAD-23-AAS2-0330	MARKET DEVELOPMENT AND ADMINISTRATION DEPARTMENT	SUPPLY AND INSTALLATION OF AIRCONDITIONING UNIT	P 302,000.00	GENERAL FUND	30 CD
16.	MDAD-23-SOP-0328	MARKET DEVELOPMENT AND ADMINISTRATION DEPARTMENT	RAINCOAT AND SAFETY SHOES	P 380,971.50	GENERAL FUND	30 CD
17.	NDC-23-OSD-1095	NOVALICHES DISTRICT CENTER	VARIOUS OFFICE SUPPLIES	P 552,690.60	GENERAL FUND	30 CD
18.	OCM(PDAO)-23-MSLI-0483	OFFICE OF THE CITY MAYOR (PERSON WITH DISABILITY AFFAIRS OFFICE)	FOLDABLE BLIND STICKS AND FIRST AID KITS	P 208,231.98	GENERAL FUND	30 CD
19.	OCM(PDAO)-23-OE-0484	OFFICE OF THE CITY MAYOR (PERSON WITH DISABILITY AFFAIRS OFFICE)	ANDROID TABLET AND OTHERS	P 101,933.00	GENERAL FUND	30 CD
20.	OCM-23-HCS-1155	OFFICE OF THE CITY MAYOR	VARIOUS HARDWARE SUPPLIES (HDPE HOSE AND OTHERS)	P 988,850.80	GENERAL FUND	30 CD
21.	OCM-23-OESC-1091	OFFICE OF THE CITY MAYOR	TONER AND OTHERS	P 633,038.90	GENERAL FUND	30 CD

OCVGENEROSO-23-OE- 0997	OFFICE OF COUN. VITO SOTTO GENEROSO	LAPTOP AND PRINTER	P200,000.00	GENERAL FUND	30 CD
PAISD-23-PPSA-0570	PUBLIC AFFAIRS AND INFORMATION SERVICES DEPARTMENT	CAMERA ACCESSORIES, HDMI EXTENDER AND OTHERS	P 715,197.50	GENERAL FUND	60 CD
QCCCD-23-OSD-0677B	QUEZON CITY CENTER FOR CHILDREN WITH DISABILITIES	VARIOUS OFFICE SUPPLIES (BALLPEN, COLORED PAPER, AND OTHERS)	P 466,682.69	GENERAL FUND	30 CD
QCGH-23-MSLI-0991C	QUEZON CITY GENERAL HOSPITAL	VARIOUS REAGENTS AND CONSUMABLES	P 173,400.00	GENERAL FUND	30 CD
QCGH-23-SERVICES-1228	QUEZON CITY GENERAL HOSPITAL	COMPREHENSIVE PREVENTIVE MAINTENANCE OF ELEVATOR	P 728,000.00	GENERAL FUND	4 MONTHS
QCPL-23-OSD-1075	QUEZON CITY PUBLIC LIBRARY	VARIOUS OFFICE SUPPLIES (BOOK CARDS, BOOK POCKETS AND OTHERS)	P 420,324.00	GENERAL FUND	30 CD
QCSBCDPO-23-CS1-1116	QC SMALL BUSINESS AND COOPERATIVES DEVELOPMENT AND PROMOTIONS OFFICE	FOOD AND DRINKS	P 300,000.00	GENERAL FUND	30 CD
QCU-23-HME-1096	QUEZON CITY UNIVERSITY	AUTOMATED EXTERNAL DEFIBRILLATOR AND OTHERS	P 282,008.00	GENERAL FUND	30 CD
QCU-23-IT-1057	QUEZON CITY UNIVERSITY	SUPPLY, DELIVERY, INSTALLATION, TESTING AND COMMISSIONING OF QCU INTEGRATED LIBRARY SYSTEM	P 300,000.00	GENERAL FUND	60 CD
QCU-23-PP-1064	QUEZON CITY UNIVERSITY	MONOBLOC ARM CHAIR	P 793,138.50	GENERAL FUND	30 CD
QCU-23-SERVICES-1058	QUEZON CITY UNIVERSITY	SUBSCRIPTION TO ENGINEERING E-JOURNALS FOR QUEZON CITY UNIVERSITY LIBRARY	P 563,038.00	GENERAL FUND	15 CD
QCYDO-23-AAS2-0988B	QUEZON CITY YOUTH DEVELOPMENT OFFICE	SUPPLY AND INSTALLATION OF AIRCODITIONING UNITS	P 417,450.00	GENERAL FUND	30 CD
QCYDO-23-OE-0989B	QUEZON CITY YOUTH DEVELOPMENT OFFICE	VARIOUS OFFICE EQUIPMENT (PHOTOCOPIER, PAPER TRIMMER, AND OTHERS)	P 295,911.68	GENERAL FUND	30 CD
SDO-23-DM-0528B	SCHOOLS DIVISION OFFICE	DRUGS AND MEDICINES FOR DENTAL	P 918,495.00	GENERAL FUND	30 CD
SSDD-23-GI2-1032	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	VARIOUS GROCERY ITEMS AND OTHERS FOR FAMILY DAY	P 681,939.50	GENERAL FUND	15 CD
CONSO-23-OE-1180	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	SHREDDER AND OTHERS	P 129,227,70	GENERAL FUND	30 CD
SSDD-23-JS2-0884	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	VARIOUS JANITORIAL SUPPLIES	P 763,767.00	GENERAL FUND	15 CD
SSDD-23-KITCHENWARE- 0870	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	VARIOUS KITCHEN SUPPLIES	P 424,844.19	GENERAL FUND	15.CD
SSDD-23-PCP1-0926	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	HYGIENE KIT BAG AND OTHERS	P 791,672.00	GENERAL FUND	15 CD
SSDD-23-TA-0925B	SOCIAL SERVICES DEVELOPMENT DEPARTMENT	MEDALS AND OTHERS	P 521,575.00	GENERAL FUND	15 CD
	0997 PAISD-23-PPSA-0570 QCCCD-23-OSD-0677B QCGH-23-MSLI-0991C QCGH-23-MSLI-0991C QCGH-23-SERVICES-1228 QCPL-23-OSD-1075 QCSBCDPO-23-CS1-1116 QCU-23-HME-1096 QCU-23-HME-1096 QCU-23-FP-1064 QCU-23-SERVICES-1058 QCYDO-23-AAS2-0988B QCYDO-23-AAS2-0988B SDO-23-DM-0528B SDO-23-DM-0528B SSDD-23-GI2-1032 CONSO-23-OE-1180 SSDD-23-KITCHENWARE-0870 SSDD-23-PCP1-0926	PAISD-23-PPSA-0570 PAISD-23-PPSA-0570 PUBLIC AFFAIRS AND INFORMATION SERVICES DEPARTMENT QCCCD-23-OSD-0677B QUEZON CITY CENTER FOR CHILDREN WITH DISABILITIES QCGH-23-MSLI-0991C QUEZON CITY GENERAL HOSPITAL QCGH-23-SERVICES-1228 QUEZON CITY GENERAL HOSPITAL QCPL-23-OSD-1075 QUEZON CITY PUBLIC LIBRARY QC SMALL BUSINESS AND COOPERATIVES DEVELOPMENT AND PROMOTIONS OFFICE QCU-23-HME-1096 QUEZON CITY UNIVERSITY QCU-23-HME-1096 QUEZON CITY UNIVERSITY QCU-23-PP-1064 QUEZON CITY UNIVERSITY QCU-23-SERVICES-1058 QUEZON CITY UNIVERSITY QCU-23-SERVICES-1058 QUEZON CITY UNIVERSITY QCU-23-AAS2-0988B QUEZON CITY YOUTH DEVELOPMENT OFFICE SDD-23-DM-0528B SCHOOLS DIVISION OFFICE SSDD-23-GI2-1032 SOCIAL SERVICES DEVELOPMENT DEPARTMENT SSDD-23-PCP1-0926 SOCIAL SERVICES DEVELOPMENT DEPARTMENT SSDD-23-PCP1-0926 SOCIAL SERVICES DEVELOPMENT DEPARTMENT SSDD-23-PCP1-0926 SOCIAL SERVICES DEVELOPMENT DEPARTMENT SOCIAL SERVICES DEVELOPMENT DEPARTMENT	Deference of the properties of	PAPTOP AND PRINTER P200,000,00	PAISD-25-PPS-4-0570 PUBLIC AFFAIRS AND INFORMATION SERVICES DEPARTMENT PAISD-25-PPS-4-0570 PUBLIC AFFAIRS AND INFORMATION SERVICES DEPARTMENT QCCCD-25-OSD-06776 QUEZON CITY CENTER FOR CHILDREN WITH DEABLITTES QUEZON CITY CENTER FOR CHILDREN WITH DEABLITTES QCGH-25-MSLL-0991C QUEZON CITY GENERAL HOSPITAL AND OTHERS QCGH-25-SERVICES-1228 QUEZON CITY GENERAL HOSPITAL MAND OTHERS QCGH-25-SERVICES-1228 QUEZON CITY GENERAL MOSPITAL MAND OTHERS QCGH-25-SERVICES-1228 QUEZON CITY PUBLIC LIBRARY QCGH-25-SERVICES-1228 QCGH-26-SERVICES-1228 QCGH-26-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-27-SERVICES-1228 QCGH-28-SERVICES-1058 QCGH-28-SERVICES-1058 QCGH-28-SERVICES-1058 QCGH-28-SERVICES-1058 QUEZON CITY UNIVERSITY QCGH-27-SERVICES-1058 QUEZON CITY UNIVERSITY QCGH-27-

- The QUEZON CITY LOCAL GOVERNMENT, through the General Fund of various years intends to apply the sums stated above being the ABC to payments under the contract for the above stated projects of contract for each lot/item. Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The QUEZON CITY LOCAL GOVERNMENT now invites bids for various Projects. Delivery of the Goods is required as stated above. Bidders should have completed, within the last three (3) years from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II. Instructions to Bidders.

- Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" 3. criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No.
 - Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.
- Prospective Bidders may obtain further information from QUEZON CITY GOVERNMENT Bids and Awards 4. Committee (BAC) Secretariat and inspect the Bidding Documents at the address given below during weekdays from 8:00 a.m. - 5:00 p.m.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders on Monday, August 07, 2023 from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB. The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person.

STANDARD RATES:

Approved Budget for the Contract	Maximum Cost of Bidding Documen (in Philippine Peso)	
500,000 and below	500.00	
More than 500,000 up to 1 million	1,000.00	

The following are the requirements for purchase of Bidding Documents;

- PhilGEPS Registration Certificate (Platinum 3 pages)
- 2. Document Request List (DRL)
- Authorization to Purchase Bidding Documents
 - 3.1 Corporate Secretary Certificate for corporation (specific for the project)
 - 3.2 Special Power of Attorney for single proprietorship (specific for the project)
- Notarized Joint Venture Agreement (as applicable)
- 6. Bids must be duly received by the BAC Secretariat through manual submission at the 2nd Floor, Procurement Department, Finance Building, Quezon City Hall Compound on or before 10:00 A.M. of Monday, August 14, 2023. Late bids shall not be accepted.
- 7. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 14.
- Bid opening shall be on 11:00 A.M. of Monday, August 14, 2023 at the given address below and/or via Zoom. Bids 8. will be opened in the presence of the bidders' representatives who choose to attend the activity.

Topic: BAC-GOODS & SERVICES BIDDING

Join Zoom Meeting

https://us02web.zoom.us/j/85850855933?pwd=R2dZUUp4Z3lyU29iZGV1WmdKRjZCdz09

Meeting ID: 858 5085 5933

Passcode: 118682

- 9. The Quezon City Local Government reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 10. For further information, please refer to:

ATTY. DOMINIC B. GARCIA

OIC, Procurement Department 2nd Floor, Procurement Department, Finance Building, Quezon City Hall Compound Elliptical Road, Barangay Central Diliman, Quezon City. Email Add: bacgoods.procurement@quezoncity.gov.ph Tel. No. (02)8988-4242 loc. 8506/8710

Website: www.quezoncity.gov.ph

11. You may visit the following websites:

For downloading of Bidding Documents: www.quezoncity.gov.ph

By:

Digitally signed by Santos Ma Margarita Trinidad Date: 2023.08.03 13:56:24 +09'00'

MS. MA. MARGARITA T. SANTOS, DPA Chairperson, QC-BAC-Goods and Services

Section II. Instructions to Bidders

Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

1. Scope of Bid

The Procuring Entity, **Quezon City Local Government** wishes to receive Bids for the **PROCUREMENT OF AUTOMATED EXTERNAL DEFIBRILLATOR AND OTHERS** with identification number **OCU-23-HME-1096**.

[Note: The Project Identification Number is assigned by the Procuring Entity based on its own coding scheme and is not the same as the PhilGEPS reference number, which is generated after the posting of the bid opportunity on the PhilGEPS website.]

The Procurement Project (referred to herein as "Project") is composed of **Twelve** (12) items, the details of which are described in Section VII (Technical Specifications).

2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for 2023 in the amount of TWO HUNDRED EIGHTY TWO THOUSAND EIGHT PESOS AND 00/100 ONLY (Php282,008.00).
- 2.2. The source of funding is:
 - a. LGUs, the Annual or Supplemental Budget, as approved by the Sanggunian.

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. Foreign ownership exceeding those allowed under the rules may participate pursuant to:

- i. When a Treaty or International or Executive Agreement as provided in Section 4 of the RA No. 9184 and its 2016 revised IRR allow foreign bidders to participate;
- ii. Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
- iii. When the Goods sought to be procured are not available from local suppliers; or
- iv. When there is a need to prevent situations that defeat competition or restrain trade.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:
 - a. For the procurement of **Non-Expendable Supplies and Services**: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least **fifty percent (50%)** of the ABC.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that: Subcontracting is not allowed.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address and/or through videoconferencing as indicated in paragraph 6 of the **IB**.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the

IB, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII** (Checklist of Technical and Financial **Documents**).
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within *the last three* (3) *years* prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an Apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in **Section VIII (Checklist of Technical and Financial Documents)**.
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, exwarehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;
 - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
 - iv. The price of other (incidental) services, if any, listed in e.

- b. For Goods offered from abroad:
 - i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
 - ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications).**

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:
 - a. Philippine Pesos.

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration¹ or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security in no case shall exceed One Hundred Twenty (120) calendar days from the date of opening of bids, unless duly extended by the bidder upon the request of the Head of the Procuring Entity (HoPE) of the Quezon City Local Government. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

¹ In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time through manual submission as indicated in paragraph 7 of the **IB**.

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "passed," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII** (**Technical Specifications**), although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows:

One Project having several items that shall be awarded as one contract.

19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

20.1. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**.

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

Section III. Bid Data Sheet

Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

- a. Information that specifies and complements provisions of the ITB must be incorporated.
- b. Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

Bid Data Sheet

ITB			
Clause			
5.3	For this purpose, contracts similar to the Project shall be:		
	a. A single contract similar to the item/s to be bid and must be at least fifty percent (50%) of the ABC.		
	b. Completed within the last three (3) years prior to the deadline for the submission and receipt of bids substantially in a FORM prescribed by the QC-BAC-GOODS AND SERVICES, must be accompanied by a copy of Certificate of Acceptance by the end-user or Official Receipt (O.R) or Sales Invoice (S.I.) issued for the Contract.		
7.1	Subcontracting is not allowed.		
12	The price of the Goods shall be quoted DDP <i>within Quezon City</i> or the applicable International Commercial Terms (INCOTERMS) for this Project.		
14.1	The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:		
	a. The amount of not less than <i>Php5,640.16</i> or equivalent to two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or		
	b. The amount of not less than <i>Php14,100.40</i> or equivalent to five percent (5%) of ABC if bid security is in Surety Bond.		
19.3	BREAKDOWN OF APPROVED BUDGET FOR THE CONTRACT (ABC)		
	For Item Nos. 1 – 3 P 23,064.00		
	For Item Nos. 4 – 11 P 248,684.00		
	For Item No. 12 P 10,260.00		
	Total P 282,008.00		
20.2	List of required licenses and permits relevant to the Project and the corresponding law requiring it.		
	No additional requirement		
21.2	Additional required documents relevant to the Project that are required by existing laws and/or the Procuring Entity		
	• Copy of valid, current License to Operate from DOH Accreditation as Supplier, Distributor or Manufacturer for Medical or Hospital Equipment or Devices.		
	• Statement of Warranty – minimum of one (1) year.		
-			

Section IV. General Conditions of Contract

Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the SCC, Section IV (Technical Specifications) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.

6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

- a. Information that complements provisions of the GCC must be incorporated.
- b. Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

Special Conditions of Contract

	Special Conditions of Contract
GCC Clause	
1	[List here any additional requirements for the completion of this Contract. The following requirements and the corresponding provisions may be deleted, amended, or retained depending on its applicability to this Contract:]
	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	[For Goods supplied from abroad, state:] "The delivery terms applicable to the Contract are DDP delivered [indicate place of destination]. In accordance with INCOTERMS."
	[For Goods supplied from within the Philippines, state:] "The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is [indicate name(s)].
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements: Select appropriate requirements and delete the rest.
	 a. performance or supervision of on-site assembly and/or start-up of the supplied Goods; b. furnishing of tools required for assembly and/or maintenance of the supplied Goods; c. furnishing of a detailed operations and maintenance manual for each
	appropriate unit of the supplied Goods; d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
	 e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods. f. [Specify additional incidental service requirements, as needed.]
	The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

Spare Parts -

The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:

Select appropriate requirements and delete the rest.

- a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
- b. in the event of termination of production of the spare parts:
 - i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
 - ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (**Schedule of Requirements**) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of [indicate here the time period specified. If not used indicate a time period of three times the warranty period].

Spare parts or components shall be supplied as promptly as possible, but in any case, within [insert appropriate time period] months of placing the order.

Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity Name of the Supplier

Contract Description **Final Destination** Gross weight Any special lifting instructions Any special handling instructions Any relevant HAZCHEM classifications A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging. Transportation -Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price. Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price. Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure. The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination. **Intellectual Property Rights –** The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof. [If partial payment is allowed, state] "The terms of payment shall be as follows: 2.2 will 4 inspections and tests that be conducted are: **Product** Presentation/Demonstration/Site Inspection, if applicable.

Section VI. Schedule of Requirements

PROJECT NAME: PROCUREMENT OF AUTOMATED EXTERNAL DEFIBRILLATOR AND OTHERS PROJECT NO. QCU-23-HME-1096

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Unit of Issue	Quantity	Delivered, Weeks / Months
	With minimum technical specifications:			
1	Oxygen Regulator with Humidifier Compatible with ALL Oxygen Tanks Oxygen Flow Range 1-10L/Min Pressure Reducing Range 2.0 – 3.0kg Relief Valve Pressure Range 3.5kg +/- 0.5kg 1 set	piece	3	
2	Oxygen Tank Holder Painted Oxygen tank holder for 50lbs.	piece	4	
3	Oxygen Tank Refill 50lbs. refill	refill	6	
4	Automated External Defibrillator AED Plus Defibrillator Unit 1 AED CPR-D Pads with CPR feedback 1 Rescue Kit- CPR Barrier, Gloves, Towel, Scissors, Razor, Antiseptic Wipe 10 Type 123 Lithium Batteries 1 Administrator Guide CD 1 Quick Setup CD 1 AED Soft case One (1) Year Manufacture Warranty	piece	1	
5	BP Apparatus with Wheels Square shape 145mm x 145mm dial Plastic caster with metal reinforced base for stability; 360° swivel for easy-reading; Gradient adjustable for easy-reading; 4-wheel with brake; The height of aluminum pole is adjustable (With range of 90cm - 125cm); Metal basket; Cotton cuff with D-ring; 2-tube adult latex bladder; Standard latex bulb; Air-release valve with spring; Standard end valve; Spiral PVC tubing, Plastic connector; Glow in the dark gauge	piece	1	Within Thirty (30) Calendar Days Upon Issuance of Notice to Proceed
6	Glucometer Kit Includes: Glucose Meter 25 Test Strips; Case; Batteries; Owner Booklet and Quick Reference Guide; Fast results in just 5 seconds; No more coding; Easy to read display; 350-test memory; 7, 14 and 30 day averages	piece	1	
7	Nebulizer In the box contents: Carrying Bag, Compressor, air Tube, 5 pcs. Replacement Filters, jet air Nebulizer, Mouthpiece, Instruction Manual, Adult Mask, Child Mask Key Features: All 5 Micro m Particle Size Breathe Enhanced Nebulizer Design Patented Pump Design Compressor Nebulizer 6ml Medication Capacity 6ml Capacity Average Nebulization Rate of 0.2 ml /min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (Ml): 6ml Mmad (Micro M): 5 µm	piece	1	

	Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White			
	Type: Compressor Nebulizer			
8	Pulse Oximeter Blood Oxygen Saturation Measurement	piece	2	
	Pulse Rate Measurement One Key Measurement			
	TFT HD Color Screen Four Directions Display			
	5 Seconds Automatic Shutdown Specifications:			
	Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm			
	Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard			
	Power Requirement: AAA Battery x 2pcs.			
9	Spine Board With holes around the stretcher for convenient transportation.	piece	1	
	On head end there is a space to fix head immobilizer. Floats in water.			
	Equipped with 3 safety belts.			
	Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm			
10	Load capacity: 160kg. Thermal Scanner	piece	5	-
10	1. Non-contact, no need to hold hands to avoid cross infection.	piece	3	
	2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min).			Within
	3. High temperature measurement accuracy, accuracy tolerance:			Thirty (30) Calendar
	±0.2 (10~40°C) 4. With warning light for detection failure and warning light for			Days Upon
	abnormal temperature. 5. Can be connected to USB power, charging treasure, self-			Issuance of Notice to
	installed lithium battery.			Proceed
	6. High-definition display, 5 meters viewing distance.7. Intelligent infrared thermometer, no need to hold, can be			
	hung/double-sided tape/fixed bracket, etc. Package Contents:			
	1 x Infrared Thermometer			
	1 x USB cable 1 x Mounting Accessories (tripod)			
11	Weighing Scale Physician Dial-Type	piece	1	=
	Big Dial Face Height rod			
	Wide base			
	Powder coated Specifications:			
	Max. Weighing: 120kg.			
	Min. Value Per Division: 0.5kg.			
	Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm			
	Load Platform Area (L x W): 375mm x 275mm			
	Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
	Gross Weight: 17kg.			
12	Oxygen Tank	piece	1	
	Cylinders are cleaned for medical oxygen service. Safety paint protects cylinder sidewall & provides heat detection.			
	Cylinder finish is easy to clean & maintain.			
	Straight thread design eliminates thread damage. 50 Pounds			
	(Height: 141cm x Circumference: 67cm) ***			

 $Schedule\ of\ Requirements\ Page\ 2\ of\ 3$

I hereby certify to comply and deliver all the above requirements.

Name:	
Legal Capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of:	

Schedule of Requirements Page 3 of 3

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "or at least equivalent." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

Technical Specifications

PROJECT NAME: PROCUREMENT OF AUTOMATED EXTERNAL DEFIBRILLATOR AND OTHERS PROJECT NO. QCU-23-HME-1096

Item	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and crossreferenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
Α.	With minimum technical specifications:	
1	Oxygen Regulator with Humidifier Compatible with ALL Oxygen Tanks Oxygen Flow Range 1-10L/Min Pressure Reducing Range 2.0 – 3.0kg Relief Valve Pressure Range 3.5kg +/- 0.5kg 1 set	
2	Oxygen Tank Holder Painted Oxygen tank holder for 50lbs.	
3	Oxygen Tank Refill 50lbs, refill	
4	Automated External Defibrillator AED Plus Defibrillator Unit 1 AED CPR-D Pads with CPR feedback 1 Rescue Kit- CPR Barrier, Gloves, Towel, Scissors, Razor, Antiseptic Wipe 10 Type 123 Lithium Batteries 1 Administrator Guide CD 1 Quick Setup CD 1 AED Soft case One (1) Year Manufacture Warranty	
5	BP Apparatus with Wheels Square shape 145mm x 145mm dial Plastic caster with metal reinforced base for stability; 360° swivel for easy-reading; Gradient adjustable for easy-reading; 4- wheel with brake; The height of aluminum pole is adjustable (With range of 90cm - 125cm); Metal basket; Cotton cuff with D-ring; 2-tube adult latex bladder; Standard latex bulb; Air-release valve with spring; Standard end valve; Spiral PVC tubing, Plastic connector; Glow in the dark gauge	
6	Glucometer Kit Includes: Glucose Meter 25 Test Strips; Case; Batteries; Owner Booklet and Quick Reference Guide; Fast results in just 5 seconds; No more coding; Easy to read display; 350-test memory; 7, 14 and 30 day averages	
7	Nebulizer In the box contents: Carrying Bag, Compressor, air Tube, 5 pcs. Replacement Filters, jet air Nebulizer, Mouthpiece, Instruction Manual, Adult Mask, Child Mask Key Features:	

All S Micro m Particle Size Breathe Enhanced Chellitzer Design Patented Pump Design Compressor Nebolitzer Guil Capacity Guil Capacity Guil Capacity Guil Capacity Average Nebultzation Rate of 0.2 ml /min Silent Operation Medical Specifications: Average Nebultzation Rate (ml/min): 0.2 ml/min Medicals Specifications: Average Nebultzation Rate (ml/min): 0.2 ml/min Medicalon Capacity Mig. 6ml Minad (Micro Mr. 3 jum Operating Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Operating Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Particle Size (Micro Mr. 3 jum Design Att Flow Rate: 4.0 L/min Design Rate: 4.0 L/min De			
Patented Pump Design Compressor Nebulizers oml Medication Capacity Average Nebulization Rate of 0.2 ral /min Sileat Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Medicat Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Medication Capacity (MI): 6ml Operating AP Flav Rate; 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement One Key Measurement TFF HD Color Sereen Four Directions Display 5 Seconds Automatic Shudown Specifications: Material: Plastic = Silicone Product Size: 28mm x 30mm x 34mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x		All 5 Micro m Particle Size	
Patented Pump Design Compressor Nebulizers oml Medication Capacity Average Nebulization Rate of 0.2 ral /min Sileat Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Medicat Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Medication Capacity (MI): 6ml Operating AP Flav Rate; 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement One Key Measurement TFF HD Color Sereen Four Directions Display 5 Seconds Automatic Shudown Specifications: Material: Plastic = Silicone Product Size: 28mm x 30mm x 34mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 40mm Box Size: 71:5m x 51mm x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x 51mm Box Size: 71:5m x 51mm x 51mm x		Breathe Enhanced Nebulizer Design	
Compressor Nebulizar Oml Mcdication Capacity Oml Capacity Oml Capacity Oml Capacity Oml Capacity Average Nebulization Rate of 0.2 ml /min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Mcdicandor Capacity (Mt): 6 ml Mmad (Micro My. 3 pm Operating Air Plany Rate: 4.0 L/min Particle Size (Micro M): 3 pm Produce Details: Type: Compressor Nebulizer Pube Colineter Blood Oxygen Salmation Measurement One Key Measurement TFF HD Color Screen Four Directions Display Seconds Automatic Shutdown Specifications: Material: Plantic + Silicone Produced Size: 28mm x 32mm x 34mm Box Size: 17.15mm x 61 mm x 40mm Accessories: Manual-Lanyard Power Requirement: AAA Buttery x 2pex. Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety bells. Spider State (pottonal) Size: Length: 184-ma x Width: 45cm x Height: 6cm Loud capacity: 160kg. 1 Non-sornace, no need to hold hands to avoid cross infection. 2 Using a new thip, the induction time is faster; the pass rare per minute is greatly improved (50/min). 3. High temperature measurement accuracy, tolerance: +0.2 (10-40°C) 4. With warning light for devection failure and warning light for ahonormal temperature. 5. Can be acconnected to USB power, charging treasure, self-installed lithium hartery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tage literal produces of the connected of USB power, charging treasure, self-installed lithium hartery. 8. High referred thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height For New York William Scales (No. S. M. William) Measurement (L. W. X H): 695mm x 286mm x 930mm Net Weight: 158g.			
oml Medication Capacity Average Nebulization Rate of 0.2 ml/min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (Ml): 6ml Mmad (Micro M): 5mm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5mm Product Details: Color: White Type: Compressor Nebulizer 8			
6ml Capacity Average Nebulization Rate of 0.2 ml /min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (Mi): 6ml Mmdd (Micro M): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer Ruise Osinates Ruise Osinates Ruise Osinates One Key Measurement One Key Measurement One Key Measurement TFF IID Color Screen Four Directions Display Seconds Automatic Shutdown Specifications: Material: Plastic 4 Silicone Product Size: 28mm x 32mm x 34mm Box Size: 7.15mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. Spine Board With Index around the stretcher for conventient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 sufesty belts. Spider strapt (optimal) Size: Length: 184cm x Width: 45cm x Height: 6cm Loud capacity: 160kg. 10 Thermal Scanner 10 Thermal Scanner 10 Loud capacity: 160kg. 11 White the imbaction time is faster: the pass rate per minute is greatly improved (50min). 3. High kemperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abortand temperature. 5. Can be connected to USB power, changing trassure, self-installed hithum battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer is VUSB cable 1 x Mounting Accessories (ripod) 1 Weighing Scale Physician Dial-Type 1 Big Dial Tace 1 Height Part Division: 0.5 kg. 1 High Tack Mithum Author Physician Dial-Type 1 Big Dial Tace 1 Hight Tack Mithum Author Physician Dial-Type 1 Big Dial Tace			
6ml Capacity Average Nebulization Rate of 0.2 ml /min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (Mi): 6ml Mmdd (Micro M): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer Ruise Osinates Ruise Osinates Ruise Osinates One Key Measurement One Key Measurement One Key Measurement TFF IID Color Screen Four Directions Display Seconds Automatic Shutdown Specifications: Material: Plastic 4 Silicone Product Size: 28mm x 32mm x 34mm Box Size: 7.15mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. Spine Board With Index around the stretcher for conventient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 sufesty belts. Spider strapt (optimal) Size: Length: 184cm x Width: 45cm x Height: 6cm Loud capacity: 160kg. 10 Thermal Scanner 10 Thermal Scanner 10 Loud capacity: 160kg. 11 White the imbaction time is faster: the pass rate per minute is greatly improved (50min). 3. High kemperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abortand temperature. 5. Can be connected to USB power, changing trassure, self-installed hithum battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer is VUSB cable 1 x Mounting Accessories (ripod) 1 Weighing Scale Physician Dial-Type 1 Big Dial Tace 1 Height Part Division: 0.5 kg. 1 High Tack Mithum Author Physician Dial-Type 1 Big Dial Tace 1 Hight Tack Mithum Author Physician Dial-Type 1 Big Dial Tace		6ml Medication Capacity	
Average Nebulization Rate of 0.2 ml/min Silent Operation Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Mmad (Micro M): 5 ml Operating Air Flow Rate: 4.0 fl/min Particle Size (Micro M): 5 ml Product Details: Color: White Type: Compressor Nebulizer **Pubs Commeter** Blood Oxygen Saturation Measurement Pubs Rate Measurement One Key Measurement One Key Measurement TH THO Color Screen Four Directions Display Seconds Automate Stuttown Material: Plastic : Silicone Product Size: 28 ml x 32 mm x 34 mm Box Size: 71.5 mm x 51 mm x 40 mm Avessories Manual-Lanyard Power Requirement: AAA Battery x 2pcs. Power Requirement: AAA Battery x 2pcs. Power Requirement: AAA Battery x 2pcs. Power Requirement: East of the ad immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Langht: 184cm x Width: 45cm x Height: 6cm Load capacity; 160kg. 10 Thermal Scanner 1 Themal Scanner 1 Description of the American Scanner of the Size of the American Scanner of the American Scanner of the Size of the American Scanner of the Americ			
Silent Operation Medical Specifications: Average Nebalization Rate (ml/min): 0.2 ml/min Medication Capacity (Mil): 6ml Mmad (Micro My.): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro My.): 5 µm Product Details: Color: White Type: Compressor Nebalizer 8 Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastel 4-Silicone Product Size: 28 mm x 3 mm x 3 mm Box Size: 71.5mm x 5 1 mm x 4 mm Box Size: 71.5mm x 5 1 mm x 4 mm Box Size: 71.5mm x 5 1 mm x 4 mm Accessories: Manual Lanyard Power Requirement: AAA Battery x 2 pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water, Flaginged with 3 safety betts. Spiter strap (optional) Size: Length: 184cm x Widhi: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Seamer 11. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (Omm). 3. High temperature insetsurement accuracy, accuracy tolerance: ±0.2 0. With varning light for detection failure and warning light for almost temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared Hermonmeter, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermonmeter 1 x USB cable 1 1. Mounting Accessories (tripod) Wide have Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Ranger To Be Measured: 70km - 190km Min. Value Of Plovision: 0.5kg. Height Ranger To Be Measured: 70km - 190km Min. Value Of Playing Langer 10 per Measurement (L. W. x 11): 695mm x 286mm x 930mm Net Weight: 15kg.			
Medical Specifications: Average Nebulization Rate (ml/min): 0.2 ml/min Medication Capacity (MI): 6ml Mmad (Miror M): 5 mn Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 mn Product Details: Color White Type: Cumpressor Nebulizer 8			
Average Nebulization Rate (ml/min) 0.2 ml/min Medication Capacity (Mil): 6ml Memal (Micro M): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer 8 Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic i Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manufal-Lanyard Power Requirement: AAA Bartery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider sing (optional) Size: Length: 184-nx Width: 45cm x Height: 6cm Load capacity; 160kg. 10 Thermal Scamer 1 Non-contact, no need to hold hands to avoid cross infaction. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High emperature measurement accuracy, accuracy tolerance: +0.2 (I) With swaring light for detection failure and warning light for abnormal temperature. 3. Can be connected to USB power, charging treasure, self-installed lithium battery. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Uffared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wide hase Powder coated Specifications: Max. Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide hase Powder coated Specifications: Max. Weighin: 15kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Paldrom Area (L. x W. H): 695mm x 286mm x 930mm New Weight: 15kg.		Silent Operation	
Average Nebulization Rate (ml/min) 0.2 ml/min Medication Capacity (Mil): 6ml Memal (Micro M): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color: White Type: Compressor Nebulizer 8 Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic i Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manufal-Lanyard Power Requirement: AAA Bartery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider sing (optional) Size: Length: 184-nx Width: 45cm x Height: 6cm Load capacity; 160kg. 10 Thermal Scamer 1 Non-contact, no need to hold hands to avoid cross infaction. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High emperature measurement accuracy, accuracy tolerance: +0.2 (I) With swaring light for detection failure and warning light for abnormal temperature. 3. Can be connected to USB power, charging treasure, self-installed lithium battery. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Uffared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wide hase Powder coated Specifications: Max. Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide hase Powder coated Specifications: Max. Weighin: 15kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Paldrom Area (L. x W. H): 695mm x 286mm x 930mm New Weight: 15kg.		Medical Specifications:	
Medication Capacity (MI): 6ml Mmad (Mirro M; 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color White Type: Compressor Nebulizer Pulse Coximeter Blood Oxygen Saluration Measurement Pulse Rate Measurement One Key Measurement One Key Measurement TIT IID Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material Plastic = Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 31mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Flotas in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: =0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infraced (50/min). 8. High definition display, 5 meters viewing distance. 9. Intelligent infraced thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 Mounting Accessories (tripod) 1 Weighing Scale Physician Dial-Type Big Dial Face Height tod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Per Division: 0.5kg. High Langer To Be Measured: 70cm - 190cm Min. Value Per Division: 0.5kg. Higher Langer Comment of the product of			
Mmad (Micro M): 5 µm Operating Air Flow Rate: 4.0 L/min Particle Size (Micro M): 5 µm Product Details: Color White Type: Compressor Nebulizer 8 Puse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFT BD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71, 5mm x 51mm x 40mm Accessories: Manual Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strang (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity; 106tg. 1 Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50°min). 3. High temperature measurement accuracy accuracy tolerance: +0.2 (10–40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared (50°min). 8. The formal Scander of the stress			
Operating Air Flow Rate: 4.0 L/min Particle Nize (Micro M): 5 µm Product Details: Color White Type: Compressor Nebulizer Type: Compressor Nebulizer 8 Pulse Oximater Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFI HD Color Screen Four Directions Display 3 Seconds Automatice Shutdown Specifications: Material: Plastic + Silicone Product Size: 28 mm x 32 mm x 34 mm Box Size: 71.5 mm x 51 mm x 40 mm Accessories: Manual Lanyard Power Requirement: AAA Bartery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head cnd there is a space to fix head immobilizer. Floats in water. Flous in water. Flous in water. Flousier stray (optional) Size: Length: 184 mx Width: 45 cm x Height: 6 cm Load capacity; 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass-rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40/°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Cam be connected to USB power, charging treasure, self-installed lithium battery, 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed brancket, etc. Package Contents. 1 x Nounting Accessories (tripod) Wighing Scale Physician Dial-Type Big Dial Face Height road Man, Value of the Physician Dial-Type Big Dial Face Powder coated Specifications: Max. Weighing: 120kg. Min. Value of the Physician Dial-Type Height Range To Be Measured. 70 cm - 190 cm Min. Value of Height Per Division: 0.5 cm Load Paltforn Area (L. x W. 31 5 mm x 275 mm Measurement (L. x W. x 1): 695 mm x 286 mm x 930 mm Nestwerement (L. x W. x 1): 695 mm x 286 mm x 930 mm Nestwerement (L. x W. x 1): 695 mm x 286 mm x 930 mm		Medication Capacity (MI): 6ml	
Operating Air Flow Rate: 4.0 L/min Particle Nize (Micro M): 5 µm Product Details: Color White Type: Compressor Nebulizer Type: Compressor Nebulizer 8 Pulse Oximater Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement TFI HD Color Screen Four Directions Display 3 Seconds Automatice Shutdown Specifications: Material: Plastic + Silicone Product Size: 28 mm x 32 mm x 34 mm Box Size: 71.5 mm x 51 mm x 40 mm Accessories: Manual Lanyard Power Requirement: AAA Bartery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head cnd there is a space to fix head immobilizer. Floats in water. Flous in water. Flous in water. Flousier stray (optional) Size: Length: 184 mx Width: 45 cm x Height: 6 cm Load capacity; 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass-rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40/°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Cam be connected to USB power, charging treasure, self-installed lithium battery, 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed brancket, etc. Package Contents. 1 x Nounting Accessories (tripod) Wighing Scale Physician Dial-Type Big Dial Face Height road Man, Value of the Physician Dial-Type Big Dial Face Powder coated Specifications: Max. Weighing: 120kg. Min. Value of the Physician Dial-Type Height Range To Be Measured. 70 cm - 190 cm Min. Value of Height Per Division: 0.5 cm Load Paltforn Area (L. x W. 31 5 mm x 275 mm Measurement (L. x W. x 1): 695 mm x 286 mm x 930 mm Nestwerement (L. x W. x 1): 695 mm x 286 mm x 930 mm Nestwerement (L. x W. x 1): 695 mm x 286 mm x 930 mm		Mmad (Micro M): 5 μm	
Particle Size (Micro M): 5 µm Product Details: Color White Type: Compressor Nebulizer 8 Pute Oximeter Blood Oxygen Saturation Measurement Palse Rate Measurement One Key Measurement TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28 mm s 23 mm s 3 dmm Box Size: 71.5 mm x 51 mm x 40 mm Accessories: Mmatell. Annyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water: Floats in water: Floats in water: Floats in water: Floats in water and the stretcher for convenient transportation. On bead end there is a space to fix head immobilizer. Floats in water: Floats in water: Floats in water and the stretcher for convenient for the spin of the stretcher for convenient for convenient for convenient for the spin of the spin o			
Product Details: Color: White Type: Compressor Nebulizer Pulse Oximeter Blood Oxygen Saturation Measurement Pulse Rate Measurement One Key Measurement One Key Measurement TFF HD Color Serven FFOU Directions Display Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual Tanyard Power Requirement: AAA Battery x 2pcs. Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: +0.2 (10–40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x forecast Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height road Wink base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5cm Load Platform Area (La W x 1H): 695mm x 286mm x 930mm Measurement (La W x 1H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Color: White Type: Compressor Nebulizer Pulse Oximeter Blood Oxygen Saturation Measurement One Rey Measurement One Rey Measurement One Rey Measurement TIP IH Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Fauirpped with S safety belts. Synider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1 Non-vontact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10–40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer: 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Pet Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Patterom Area (L. x W): 3.75mm x 275mm Measurement (L. x W x H): 605mm x 286mm x 930mm Net Weight: 15kg.			
Type: Compressor Nebulizer 8		Product Details:	
Type: Compressor Nebulizer 8		Color: White	
8 Pulse Oximeter Blood Oxygen Saturation Measurement Dulse Rate Measurement One Key Measurement TFF HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Faquipped with 3 safetya belts. Spider strap (optional) Size: Length: 184cm x Wildt: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is gesuly improved (30min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 Weighing Scale Physician Dial-Type Big Dal Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L. x W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Blood Oxygen Saturation Measurement Pulse Rate Measurement TFF HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 1600g. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Measurement (1. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Pulse Rate Measurement One Key Measurement TFF HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pes. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C') 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tupe/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Monunting Accessories (tripod) With base Powder coated Specifications: Max. Weighing: 120kg, Min. Value Per Division: 0.5kg, Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg,	8		
Pulse Rate Measurement One Key Measurement TFF HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pes. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C') 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tupe/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Monunting Accessories (tripod) With base Powder coated Specifications: Max. Weighing: 120kg, Min. Value Per Division: 0.5kg, Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg,		Blood Oxygen Saturation Measurement	
One Key Measurement TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: +0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape-fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value of Height Per Division: 0.5cm Load Platform Area (L. x W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
TFT HD Color Screen Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1 Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wigh base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (f. x W); 375mm x 275mm Measurement (f. x W x H); 695mm x 286mm x 930mm Net Weight: 15kg.			
Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm = 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L. X W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Four Directions Display 5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm = 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L. X W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		TFT HD Color Screen	
5 Seconds Automatic Shutdown Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fis head immobilizer. Floats in water. Equipped with 3 safety belts. Spider stray (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scamer 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50 min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape-fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value of Polivision: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L. X W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Specifications: Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Hoats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner I. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (30/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value of Height Por Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Por Division: 0.5cm Load Platform Area (L. x W): 375mm x 275mm Measurement (L. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		± •	
Material: Plastic + Silicone Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided taperfixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Wieghing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water: Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C') 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided taper/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Of Height Per Division: 0.5kg. Heigh Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Measurement (1. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Specifications:	
Product Size: 28mm x 32mm x 34mm Box Size: 71.5mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water: Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C') 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided taper/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Of Height Per Division: 0.5kg. Heigh Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Measurement (1. x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Material: Plastic + Silicone	
Box Size: 71.5mm x 51mm x 40mm Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 1844cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value of Feligh Per Division: 0.5km Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Met Weight: 15kg.			
Accessories: Manual/Lanyard Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Pelight Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Per Division: 0.5kg. Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x W): 695mm x 286mm x 930mm Net Weight: 15kg.			
Power Requirement: AAA Battery x 2pcs. 9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value Per Division: 0.5kg. Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x W): 695mm x 286mm x 930mm Net Weight: 15kg.		Accessories: Manual/Lanyard	
9 Spine Board With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg, Min. Value Per Division: 0.5kg, Height Range To Be Measured: 70cm - 190cm Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 286mm x 930mm Net Weight: 15kg.			
With holes around the stretcher for convenient transportation. On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W W: 375mm x 275mm Measurement (L x W W: 375mm x 275mm Net Weight: 15kg.			
On head end there is a space to fix head immobilizer. Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.	9		
Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10~40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Wounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		With holes around the stretcher for convenient transportation.	
Floats in water. Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10~40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Wounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Equipped with 3 safety belts. Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value of Height Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		•	
Spider strap (optional) Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10−40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg, Min. Value Per Division: 0.5kg, Height Range To Be Measured: 70cm − 190cm Min. Value Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Equipped with 3 safety belts.	
Size: Length: 184cm x Width: 45cm x Height: 6cm Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Spider strap (optional)	
Load capacity: 160kg. 10 Thermal Scanner 1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weigh: 15kg.			
1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
1. Non-contact, no need to hold hands to avoid cross infection. 2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.	10	Thermal Scanner	
2. Using a new chip, the induction time is faster; the pass rate per minute is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10~40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
is greatly improved (50/min). 3. High temperature measurement accuracy, accuracy tolerance: ±0.2 (10−40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
3. High temperature measurement accuracy, accuracy tolerance: ±0.2 ((10-40°C)) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
(10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		is greatly improved (50/min).	
(10-40°C) 4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		3. High temperature measurement accuracy, accuracy tolerance: ±0.2	
4. With warning light for detection failure and warning light for abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
abnormal temperature. 5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
5. Can be connected to USB power, charging treasure, self-installed lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		abnormal temperature.	
lithium battery. 6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
6. High-definition display, 5 meters viewing distance. 7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
7. Intelligent infrared thermometer, no need to hold, can be hung/double-sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
sided tape/fixed bracket, etc. Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		7. Intelligent infrared thermometer, no need to hold, can be hung/double-	
Package Contents: 1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
1 x Infrared Thermometer 1 x USB cable 1 x Mounting Accessories (tripod) 11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
1 x USB cable 1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		1 x Infrared Thermometer	
1 x Mounting Accessories (tripod) Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		1 x USB cable	
11 Weighing Scale Physician Dial-Type Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Big Dial Face Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.	11		
Height rod Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Big Dial Face	
Wide base Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Powder coated Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Specifications: Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Powder coated	
Max. Weighing: 120kg. Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Specifications:	
Min. Value Per Division: 0.5kg. Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		-	
Height Range To Be Measured: 70cm - 190cm Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Min. Value of Height Per Division: 0.5cm Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.		Height Range To Be Measured: 70cm - 190cm	
Load Platform Area (L x W): 375mm x 275mm Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Measurement (L x W x H): 695mm x 286mm x 930mm Net Weight: 15kg.			
Net Weight: 15kg.			
Net Weight: 15kg.		Measurement (L x W x H): 695mm x 286mm x 930mm	
Gross weight: 1/kg.			
		Gross weight: 1/kg.	
	ĺ		
		1	I

12	Oxygen Tank	
	Cylinders are cleaned for medical oxygen service.	
	Safety paint protects cylinder sidewall & provides heat detection.	<u> </u>
	Cylinder finish is easy to clean & maintain.	
	Straight thread design eliminates thread damage. 50 Pounds (Height:	
	141cm x Circumference: 67cm)	
В.	Compliance to the Schedule of Requirements (Section VI)	

I hereby certify to comply and deliver all the above requirements.

Name:	
Legal Capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of: _	

Technical Specifications Page 3 of 3

Section VIII. Checklist of Technical and Financial Documents

Notes on the Checklist of Technical and Financial Documents

The prescribed documents in the checklist are mandatory to be submitted in the Bid, but shall be subject to the following:

- a. GPPB Resolution No. 09-2020 on the efficient procurement measures during a State of Calamity or other similar issuances that shall allow the use of alternate documents in lieu of the mandated requirements; or
- b. Any subsequent GPPB issuances adjusting the documentary requirements after the effectivity of the adoption of the PBDs.

The BAC shall be checking the submitted documents of each Bidder against this checklist to ascertain if they are all present, using a non-discretionary "pass/fail" criterion pursuant to Section 30 of the 2016 revised IRR of RA No. 9184.

Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE

Class "A" Documents

Legal Do	Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages) in accordance with Section 8.5.2 of the IRR;
<u>Technica</u>	al Documents
(b) S	Statement of the prospective bidder of all its ongoing government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES); and
(c)	Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the relevant period as provided in the Bidding Documents (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES); and
(d)	Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission;
(e)	or Original copy of Notarized Bid Securing Declaration; <u>and</u> Conformity with Section VI. (Schedule of Requirements) and Section VII. (Technical Specifications), which may include production/delivery schedule, manpower requirements, and/or after-sales/parts, if applicable; <u>and</u>
(f)	Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.
Financia (g)	The prospective bidder's computation of Net Financial Contracting Capacity (NFCC) (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES); or
	A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation.
(h)	Class "B" Documents If applicable, a duly signed joint venture agreement (JVA) in case the joint venture is already in existence; or
	duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.
<u>Other do</u> ☐ (i)	[For foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government office of their country stating that Filipinos are allowed to participate in
(j)	government procurement activities for the same item or product. Certification from the DTI if the Bidder claims preference as a Domestic Bidder or Domestic Entity.

II.	FI	NANCIAL COMPONENT ENVELOPE
	(a)	Original of duly signed and accomplished Financial Bid Form; and
	(b)	Original of duly signed and accomplished Price Schedule(s).
III.	REQU	JIRED DOCUMENTS in BDS SECTION 20.2 and 21.2
N	Manuf	of valid, current License to Operate from DOH Accreditation as Supplier, Distributor or acturer for Medical or Hospital Equipment or Devices. ent of Warranty – minimum of one (1) year.
No	te:	
1.	Pleas	se refer to
		os://drive.google.com/file/d/1uiYurh5WrpBL5B_pqpzAb62yucAblR1p/view?usp=
		ng] for the following requirements:
		Computation of NFCC; List of All Ongoing Contracts/List of Contracts already awarded but not yet
	0.	Elist of the organization and of contracts under a united out not yet

2. Please refer to GPPB Resolution No. 16-2020 for the following requirements:

c. Statement of Single Largest Completed Contract

- a. Bid Form;
- b. Price Schedule (for Goods Offered from Abroad/ Within the Philippines)
- c. Bid Securing Declaration; and
- d. Omnibus Sworn Statement

