



**REQUEST FOR QUOTATION
NEGOTIATED PROCUREMENT
SECTION 53.1**

DATE : NOVEMBER 28, 2023

PROJECT NO. : QCU-23-CE1-1573

Name of Company : _____

Address : _____

Contact No. : _____

Project Title : PROCUREMENT OF ACTIVE POWERED SPEAKER AND OTHERS

Approved Budget of
the Contract : Php891,141.40

End-User /
Implementing Office : QUEZON CITY UNIVERSITY

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **DECEMBER 1, 2023; 8:30 a.m.** Philippine Standard Time, together with the following documents of your company:

- 1 PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2023);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2022) (For ABCs above P500,000.00)
- 7 If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** issued by QC BAC- Goods and Services.

(SGD.) MA. MARGARITA T. SANTOS, DPA
Chairperson, BAC- Goods and Services

TERMS AND CONDITIONS

- 1. Bidders shall **provide correct and accurate** information required in this form.
- 2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
- 3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
- 4. Quotation **exceeding** the Approved Budget for the Contract (ABC) shall be **rejected**.
- 5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- 7. The City General Services Department (CGSD) shall have the right to inspect the goods.
- 8. Non-submission of eligibility documents shall mean disqualification of Quotation.
- 9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

ITEM NO.	ITEM & DESCRIPTION	UNIT OF ISSUE	QTY.	UNIT PRICE	ITEM TOTAL
	With minimum technical specifications:				
1	ACTIVE POWERED SPEAKER Multi-purpose, 2-way active loudspeaker 2000 Watts Class-D amplifier module Intrinsic Correction tuning and loudspeaker management Directivity Matched Transition (DMT) design provides excellent power response and consistent performance across the listening area Rugged ABS enclosure Deployment in either main PA or floor monitor position Factory Presets and savable/recallable Scenes for commonly-used application Multi-function digital display for control and selection of loudspeaker functions including cross-over, EQ, delay and frequency contour Dual pole cup mounts (standard and 7.5 degree down-tilt) M10 fittings for flown applications Complete EASE and CAD information available online ITEM NAME/DESCRIPTION SRIVATION LF Transducer 305mm (12-inch), cone HF Transducer 35.6mm (1.4-inch) titanium diaphragm compression driver Frequency Response (-6 dB) 50 Hz - 20 kHz Frequency Range (-10 dB) 45 Hz - 20 kHz Nominal Coverage Angle 75° Axisymmetric Maximum Rated SPL1 Amplifier Cooling 132 dB @ 1 M, peak 126 dB @ 1 M, continuous Class D Peak: 1800 W (LF), 225 W (HF) Low-noise, variable speed fan Controls Power 3 x Level	unit	2		

	<p>Rotary encoder (push) 2 × selection buttons Indicators Monochrome LCD Display 1.75-inch x 1-inch (45mm x 25.4mm) 2 x Power LED (front and rear) 3 x Input Signal LED Input A Mic selected LED Input B Hi-Z selected LED Limiter active LED Connectors 2 x locking XLR/F ¼-inch combo (Mic/Line Input and Hi-Z/Line Input) 1 x 3.5mm TRS (Stereo Input) 2 × XLR/M (Loop-thru Output) 1 × XLR/M (Mix Output) 1 x locking IEC power connector AC Power Input Universal power supply 100 - 240 VAC, 50 - 60 Hz AC Power Consumption 1/8th Power 2 100 VAC, 2.1 A / 120 VAC, 1.9 A / 240 VAC, 1.1 A AC Power Consumption - Standby 0.2 A at any voltage Enclosure Impact Resistant ABS Attachment Points 2 × M10 threaded inserts plus Pull-Back Color Black (RAL 9011) Grille 18 Gauge powder coated steel, internal cloth lining</p>				
2	<p>RACKMOUNTABLE DIGITAL MIXER 16 Mono Inputs (TRS + XLR), 3 Stereo Inputs (TRS), 4 Stereo FX Returns, 16 Busses, and 12 Mix Outputs (LR, Mono Mix 1-4, Stereo Mix 1-3), 19 inches Rack mountable with moving faders and recallable AnaLOG preamps, Direct multitrack recording/playback on USB drives and USB Audio Streaming, 800×480 Touchscreen, iPad App Inputs: 16 Mono / 3 Stereo Mixes: 4 Mono / 3 Stereo / LR 24×22 USB Audio Interface Comprehensive Channel Processing and FX Intuitive Interface with Full Colour Touchscreen Range of Remote Expanders 19 inches Rack Mountable 16 Mono Mic/Line Inputs (TRS + XLR) 3 Stereo Inputs (TRS) 12 Mix Outputs (XLR) 7 Monitor Mixes (4 mono + 3 stereo) 4 FX Engines 2 dedicated FX Sends / Returns 4 Mute Groups 4 DCA Groups AES Digital Out 24×22 USB Audio Interface Remote Audio Port 17 Motor Faders 800×480 Touchscreen 4 Soft Keys Trim, polarity, HPF, gate, insert, 4-band PEQ, compressor, delay on all Inputs</p>	unit	1		

	Insert, 4-band PEQ, 1/3 octave GEQ, compressor, delay on all Outputs Automatic Mic Mixer Channel Ducker on all Inputs ProFactory Mic Presets RackFX Library Built-in Signal Generator RTA with Peak Band indication Spectrogram to aid feedback elimination and room acoustics Qu-Drive Direct Multitrack Recording / Playback on USB drives DAW MIDI Control				
3	ANALOG AUDIO MIXER Type: Analog Channels: 8 Computer Connectivity: USB (2 x 2) Faders: 9 x 60mm Throw Inputs - Mic Preamps: 4 x XLR Phantom Power: 4 Inputs - Line: 8 x TRS, 2 x RCA Outputs - Main: 2 x XLR, 2 x TRS Outputs - Other: 2 x RCA Aux Sends: 1 x Pre, 1 x Post Send/Return I/O: 2 x ¼ inch (Send) 4 x ¼ inch (Return) Busses/Groups: 2 x Bus Headphones: 1 x ¼ inch, USB: 1 x Type B EQ Bands: 3-band Rackmountable: YES (includes Rack Ears)	unit	1		
4	POWERED SUBWOOFER SYSTEM High output 18LX loudspeaker. Polarity switch (0°-180°). Filtered output defeat switch. Variable 80-125 Hz low-pass filter. Gain control. Nominal LF Amplifier Power: 1500 Wpeak (Class D) Frequency Range (-10 dB): Loud: 35 Hz - 125 Hz. Deep: 30 Hz - 125 Hz Rated Peak SPL at 1 m: 134 dB Connectors: INPUT: Female XLR, LOOP THRU: Male XLR, AC INPUT: powerCON AC Requirements: 115 V, 50 Hz/60 Hz, 230 V, 50 Hz/60 Hz Enclosure Material: Birch Plywood Color/Finish: Black ISO-flex Paint	unit	2		
5	POWERED SPEAKER POINT SOURCE Twin 15 inches powered 3-way system. Increased output capacity. Ultra lightweight Class D amplifier with SMPS. User definable DSP with LCD screen. Wireless streaming of music. Rigging points. Amplifier Power: 2250 Wpeak, Class D, Tri-amplified Frequency Range (-10 dB): Loud: 40 Hz - 20 kHz Rated Peak SPL at 1 m: 138 dB Dispersion: 90 deg x 50 deg	unit	1		

	Enclosure Material: Birch Plywood Color/Finish: Black ISO-flex Paint Connectors: INPUT: Female XLR, LOOP THRU: Male XLR, AC INPUT: powerCON AC Requirements: 115 V, 50 Hz/60 Hz, 230 V, 50 Hz/60 Hz				
TOTAL:					

Amount in Words: _____

Delivery Period : **Sixty (60) Calendar Days**
Warranty : _____

Signature over Printed Name

Office Telephone No./Fax/Mobile No.

Date

Email Address

Other Requirement:
<ul style="list-style-type: none">Statement of Warranty – minimum of one (1) year for all items.