

REPUBLIC OF THE PHILIPPINES QUEZON CITY GOVERNMENT BIDS AND AWARDS COMMITTEE – GOODS AND SERVICES



PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

PROCUREMENT OF PAPER SHREDDER AND OTHERS

PROJECT NO. HCDRD-24-OE-1179

Government of the Republic of the Philippines

Sixth Edition July 2020

Ja Kund A

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.
- b. Specific details, such as the "name of the Procuring Entity" and "address for bid submission," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.
- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.

- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

Glossar	y of Acronyms, Terms, and Abbreviations	4
Section	I. Invitation to Bid	7
Section	II. Instructions to Bidders	11
1.	Scope of Bid	12
2.	Funding Information	12
3.	Bidding Requirements	12
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	12
5.	Eligible Bidders	13
6.	Origin of Goods	13
7.	Subcontracts	13
8.	Pre-Bid Conference	14
9.	Clarification and Amendment of Bidding Documents	14
10.	Documents comprising the Bid: Eligibility and Technical Components	14
11.	Documents comprising the Bid: Financial Component	14
12.	Bid Prices	14
13.	Bid and Payment Currencies	15
14.	Bid Security	15
15.	Sealing and Marking of Bids	16
16.	Deadline for Submission of Bids	16
17.	Opening and Preliminary Examination of Bids	16
18.	Domestic Preference	16
19.	Detailed Evaluation and Comparison of Bids	. 16
20.	Post-Qualification	17
21.	Signing of the Contract	17
Section	III. Bid Data Sheet	18
Section	IV. General Conditions of Contract	20
1.	Scope of Contract	21
2.	Advance Payment and Terms of Payment	21
3.	Performance Security	21
4.	Inspection and Tests	21
5.	Warranty	21
6.	Liability of the Supplier	22
Section	V. Special Conditions of Contract	23
Section	VI. Schedule of Requirements	27
Section	VII. Technical Specifications	29
Section	VIII. Checklist of Technical and Financial Documents	33

Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR - Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF – Cost Insurance and Freight.

CIP - Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP - Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

 $\mathbf{EXW} - \mathbf{Ex}$ works.

FCA – "Free Carrier" shipping point.

FOB - "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project—Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC - Government-owned and/or -controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP - Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs - Local Government Units.

NFCC - Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency

which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC - Securities and Exchange Commission.

SLCC - Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.

Section I. Invitation to Bid

Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (e.g., the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IB must conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



Republika ng Pilipinas



Lungsod Quezon

BIDS AND AWARDS COMMITTEE -- GOODS & SERVICES
Second Floor, Civic Center Building F, Quezon City Hall Complex, Elliptical Road, Quezon City
8988-4242 local 8712 / 8710 / 8709 Procurement@quezoncity.gov.ph

INVITATION TO BID

August 27, 2024

NO.	PROJECT NO.	OFFICE	PROJECT NAME	AMOUNT	SOURCE OF	DELIVERY PERIOD
1.	CAO(TFS)-24-AAS2-1321	CITY ADMINISTRATOR'S OFFICE (TASK FORCE STREETLIGHTS)	ASK FORCE WINDOW TIPE P 119,250.00		GENERAL FUND	30 CD
2.	CAO(TFS)-24-OE-1320	CITY ADMINISTRATOR'S OFFICE (TASK FORCE STREETLIGHTS)	MULTI-FUNCTIONAL COPIER	P 161,102.60	GENERAL FUND	30 CD
3.	CAO(ZAU)-24-OE-1225	CITY ADMINISTRATOR'S OFFICE (ZONING ADMINISTRATION UNIT)	DIGITAL DUPLICATOR	P 429,530.00	GENERAL FUND	30 CD
4.	CGSD-24-SOP-1192	CITY GENERAL SERVICES DEPARTMENT	TRAFFIC BARRIERS, RAINCOAT AND OTHERS	P 253,530.00	GENERAL FUND	30 CD
5.	CONSO-24-IS-1163B	PUBLIC AFFAIRS AND INFORMATION SERVICES DEPARTMENT	INTERNET SUBSCRIPTION WITH DEVICE	P 183,750.00	GENERAL FUND	3 MONTHS
6.	CTO-24-BEVERAGES-1341	CITY TREASURER'S OFFICE	SUPPLIES FOR COFFEE VENDING MACHINE	P 985,424.00	GENERAL FUND	3 MONTHS
7.	DSQC-24-SOP-1317	DEPARTMENT OF SANITATION AND CLEANUP WORKS OF QUEZON CITY	HAND GLOVES AND OTHERS	P 139,800.00	GENERAL FUND	60 CD
8.	HCDRD-24-OE-1179	HOUSING, COMMUNITY DEVELOPMENT AND RESETTLEMENT DEPARTMENT	PAPER SHREDDER AND OTHERS	P 466,938.20	GENERAL FUND	30 CD
9.	HEALTH-24-CE1-1204B	QUEZON CITY HEALTH DEPARTMENT	SMART PHONE FOR ONLINE VALIDATION	P 933,155.00	GENERAL FUND	30 CD
10.	HEALTH-24-ITPAP-1199	QUEZON CITY HEALTH DEPARTMENT	DIGITAL VOLTAGE TESTER AND OTHERS	P 611,491.10	GENERAL FUND	30 CD
11.	OCEMEDINA-24-FOODSTUFF- 1311	OFFICE OF COUN, ERIC Z. MEDINA	CUPCAKE AND JUICE DRINKS	P 147,980.00	GENERAL FUND	30 CD
12.	OCM(GAD)-24-CS1-1327	OFFICE OF THE CITY MAYOR (GAD COUNCIL OFFICE)	FOOD AND DRINKS, AND OTHERS	P 226,584.00	GENERAL FUND	3 MONTHS
13.	OCM(HRMD)-24-SERVICES-0937D	OFFICE OF THE CITY MAYOR (HUMAN RESOURCE MANAGEMENT DEPARTMENT)	MENTAL HEALTH SERVICES PLAN	P 448,000.00	GENERAL FUND	3 MONTHS
14.	OCM(POPS)-24-CS1-1370	OFFICE OF THE CITY MAYOR - POPS PLAN	FOOD AND DRINKS	P 990,000.00	GENERAL FUND	3 MONTHS
15.	OCM-24-CG-1070	OFFICE OF THE CITY MAYOR	CUSTOMIZED UMBRELLA	P 650,000.00	GENERAL FUND	30 CD
16.	OCVGENEROSO-24-FIXTURES- 0347	OFFICE OF COUN. VITO SOTTO GENEROSO	SUPPLY AND INSTALLATION OF MODULAR PARTITION WALL AND OTHERS	P 257,760.71	GENERAL FUND	30 CD
17.	QCADAAC-24-APP-1328	QUEZON CITY ANTI-DRUG ABUSE ADVISORY COUNCIL	VARIOUS APPLIANCES (CHEST FREEZER, TELEVISION, AND OTHERS)	P 117,906.00	GENERAL FUND	30 CD
18.	QCADAAC-24-FIXTURES-1330	QUEZON CITY ANTI-DRUG ABUSE ADVISORY COUNCIL	SUPPLY AND INSTALLATION OF ACCORDION ROOM DIVIDERS AND DOORS	P 400,000.00	GENERAL FUND	30 CD

NO.	PROJECT NO.	OFFICE	PROJECT NAME	AMOUNT	SOURCE OF FUND	DELIVERY PERIOD
19.	QCADAAC-24-GM-1329	QUEZON CITY ANTI-DRUG ABUSE ADVISORY COUNCIL	GENERAL MERCHANDISE (TOOTHBRUSH, MOP, COOKWARE SET, CAMERA BAG, AND OTHERS)	P 519,023.00	GENERAL FUND	30 CD
20.	QCSBCDPO-24-GM-0321	QUEZON CITY SMALL BUSINESS AND COOPERATIVES DEVELOPMENT AND PROMOTIONS OFFICE	STORAGE TRAY AND OTHERS	P 878,474.00	GENERAL FUND	3 MONTHS
21.	QCSBCDPO-24-HLMF-1308	QUEZON CITY SMALL BUSINESS AND COOPERATIVES DEVELOPMENT AND PROMOTIONS OFFICE	HOTEL ACCOMMODATION AND OTHERS	P 420,525.00	GENERAL FUND	3 MONTHS
22.	QCU-24-SERVICES-1294	QUEZON CITY UNIVERSITY	SUBSCRIPTION TO PHILIPPINE E- JOURNALS FOR QUEZON CITY UNIVERSITY LIBRARY	P 276,000.00	TRUST FUND	30 CD
23.	RMBGH-24-SA-1187B	ROSARIO MACLANG BAUTISTA GENERAL HOSPITAL	SUPPLY AND INSTALLATION OF SIGNAGE	P 172,900.00	GENERAL FUND	30 CD
24.	SDO-24-PS2-1310	SCHOOLS DIVISION OFFICE	PRINTING OF IBANG KLASE SA QC NEWSLETTER	P 259,800.00	GENERAL FUND	30 CD

- The QUEZON CITY LOCAL GOVERNMENT, through the General Fund and Trust Fund of various years
 intends to apply the sums stated above being the ABC to payments under the contract for the above stated projects
 of contract for each lot/item. Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The QUEZON CITY LOCAL GOVERNMENT now invites bids for various Projects. Delivery of the Goods is required as stated above. Bidders should have completed, within the last three (3) years from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II. Instructions to Bidders.
- 3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.
 - a. Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.
- 4. Prospective Bidders may obtain further information from QUEZON CITY GOVERNMENT Bids and Awards Committee (BAC) Secretariat and inspect the Bidding Documents at the address given below during weekdays from 7:00 a.m. 5:00 p.m.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders on Thursday, August 29, 2024 from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB. The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person.

STANDARD RATES:

Approved Budget for the Contract	Maximum Cost of Bidding Documents (in Philippine Peso)
500,000 and below	500.00
More than 500,000 up to 1 million	1,000.00

The following are the requirements for purchase of Bidding Documents;

- 1. PhilGEPS Registration Certificate (Platinum 3 pages)
- 2. Document Request List (DRL)
- 3. Authorization to Purchase Bidding Documents
 - 3.1 Corporate Secretary Certificate for corporation (specific for the project)
 - 3.2 Special Power of Attorney for single proprietorship (specific for the project)
- 4. Notarized Joint Venture Agreement (as applicable)
- 6. Bids must be duly received by the BAC Secretariat through manual submission at the 2nd Floor, Procurement Department, Finance Building, Quezon City Hall Compound on or before 10:00 A.M. of Thursday, September 5, 2024. Late bids shall not be accepted.
- 7. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 14.
- 8. Bid opening shall be on 11:00 A.M. of Thursday, September 5, 2024 at the given address below and/or via Zoom. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.

Topic: BAC-GOODS & SERVICES BIDDING

Join Zoom Meeting

 $\underline{https://us02web.zoom.us/j/85850855933?pwd} = \underline{R2dZUUp4Z31yU29iZGV1WmdKRjZCdz09}$

Meeting ID: 858 5085 5933

Passcode: 118682

- 9. The Quezon City Local Government reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 10. For further information, please refer to:

ATTY. DOMINIC B. GARCIA

OIC, Procurement Department 2nd Floor, Procurement Department,

Finance Building, Quezon City Hall Compound

Elliptical Road, Barangay Central Diliman, Quezon City.

Email Add: bacgoods.procurement@quezoncity.gov.ph

Tel. No. (02)8988-4242 loc. 8506/8710

Website: www.quezoncity.gov.ph

11. You may visit the following websites:

For downloading of Bidding Documents: www.quezoncity.gov.ph

Ву:

MS. MA. MARGARITA S. MEJIA, DPA Chairperson, QC-BAC-Goods and Services

Section II. Instructions to Bidders

Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

1. Scope of Bid

The Procuring Entity, Quezon City Local Government wishes to receive Bids for the PROCUREMENT OF PAPER SHREDDER AND OTHERS with identification number HCDRD-24-OE-1179.

[Note: The Project Identification Number is assigned by the Procuring Entity based on its own coding scheme and is not the same as the PhilGEPS reference number, which is generated after the posting of the bid opportunity on the PhilGEPS website.]

The Procurement Project (referred to herein as "Project") is composed of *ten* (10) items, the details of which are described in Section VII (Technical Specifications).

2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for 2024 in the amount of FOUR HUNDRED SIXTY-SIX THOUSAND NINE HUNDRED THIRTY-EIGHT PESOS AND 20/100 ONLY (Php 466,938.20).
- 2.2. The source of funding is:
 - a) LGUs, the Annual or Supplemental Budget, as approved by the Sanggunian.

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

Nyw pot

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. Foreign ownership exceeding those allowed under the rules may participate pursuant to:
 - i. When a Treaty or International or Executive Agreement as provided in Section 4 of the RA No. 9184 and its 2016 revised IRR allow foreign bidders to participate;
 - ii. Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
 - iii. When the Goods sought to be procured are not available from local suppliers; or
 - iv. When there is a need to prevent situations that defeat competition or restrain trade.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:
 - a. For the procurement of Non-Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under ITB Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that: Subcontracting is not allowed.

IN am of

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address and/or through videoconferencing as indicated in paragraph 6 of the IB.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 10.2. The Bidder's SLCC as indicated in ITB Clause 5.3 should have been completed within *the last three (3) years* prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an Apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the IB shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Bid Prices

12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:

- a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, exwarehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;
 - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
 - iv. The price of other (incidental) services, if any, listed in e.

b. For Goods offered from abroad:

- i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
- ii. The price of other (incidental) services, if any, as listed in Section VII (Technical Specifications).

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:
 - a. Philippine Pesos.

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration¹ or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security in no case shall exceed One Hundred Twenty (120) calendar days from the date of opening of bids, unless duly extended by the bidder upon the request of the Head of the Procuring Entity (HoPE) of the Quezon City Local Government. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15

¹ In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time through manual submission as indicated in paragraph 7 of the **IB**.

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the IB. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "passed," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII** (**Technical Specifications**), although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.

- 19.4. The Project shall be awarded as follows:
 - One Project having several items that shall be awarded as one contract.
- 19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

20.1. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the BDS.

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

Section III. Bid Data Sheet

Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

- a. Information that specifies and complements provisions of the ITB must be incorporated.
- b. Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

Bid Data Sheet

ITB						
Clause						
5.3	For this purpose, contracts similar to the Project shall be:					
	a. A single contract similar to the item/s to be bid and must be at least fifty percent (50%) of the ABC.					
	b. Completed within the last three (3) years prior to the deadline for the submission and receipt of bids substantially in a FORM prescribed by the QC-BAC-GOODS AND SERVICES, must be accompanied by a copy of Certificate of Acceptance by the end-user or Official Receipt (O.R) or Sales Invoice (S.I.) issued for the Contract.					
7.1	Subcontracting is not allowed.					
12	The price of the Goods shall be quoted International Commercial Terms (INCOT	DDP within Quezon City or the applicable ERMS) for this Project.				
14.1	The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:					
	a. The amount of not less than <i>Php 9,338.76</i> or equivalent to two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or b. The amount of not less than <i>Php 23,346.91</i> or equivalent to five percent (5%) of ABC if bid security is in Surety Bond.					
19.3						
	ITEM	ABC				
	Item no. 1-2	P 77,350.00				
:	Item no. 3-5	P 148,834.40				
	Item no. 6-10	P 240,753.80				
	TOTAL	P466,938.20				
] -	-					
20.2	List of required licenses and permits releven requiring it.	vant to the Project and the corresponding law				
	No additional requirement					
21.2	Additional required documents relevant to the Project that are required by existing laws and/or the Procuring Entity.					
	Statement of warranty- minimu Project Number. /	um of One (1) year with Project Name and				

Section IV. General Conditions of Contract

Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the SCC.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the SCC, Section IV (Technical Specifications) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.

6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

- a. Information that complements provisions of the GCC must be incorporated.
- b. Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

Special Conditions of Contract

GCC	Special Conditions of Contract
Clause	
1	[List here any additional requirements for the completion of this Contract. The following requirements and the corresponding provisions may be deleted, amended, or retained depending on its applicability to this Contract:]
	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	[For Goods supplied from abroad, state:] "The delivery terms applicable to the Contract are DDP delivered [indicate place of destination]. In accordance with INCOTERMS."
	[For Goods supplied from within the Philippines, state:] "The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is [indicate name(s)].
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements: Select appropriate requirements and delete the rest.
	a. performance or supervision of on-site assembly and/or start-up of the supplied Goods;
	b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;
	c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
	d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
	 e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods. f. [Specify additional incidental service requirements, as needed.]
	The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

Spare Parts -

The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:

Select appropriate requirements and delete the rest.

- a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
- b. in the event of termination of production of the spare parts:
 - i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
 - ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (Schedule of Requirements) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of [indicate here the time period specified. If not used indicate a time period of three times the warranty period].

Spare parts or components shall be supplied as promptly as possible, but in any case, within [insert appropriate time period] months of placing the order.

Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity Name of the Supplier

Contract Description Final Destination Gross weight Any special lifting instructions Any special handling instructions Any relevant HAZCHEM classifications A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging. Transportation – Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price. Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price. Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure. The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination. Intellectual Property Rights -The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof. [If partial payment is allowed, state] "The terms of payment shall be as follows: 2.2 4 The inspections and tests that will be conducted Product Presentation/Demonstration/Site Inspection, if applicable.

Section VI. Schedule of Requirements

PROJECT NAME: PROCUREMENT OF PAPER SHREDDER AND OTHERS PROJECT NO. HCDRD-24-OE-1179

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Unit of Issue	Quantity	Delivered, Weeks/ Months
1.	Paper Cutter /	unit	1	MAURITIES
	Heavy duty ream Cutter A3 A4, manual	_ uiui _		
	Thick Layer paper cutter			
	Size: A4 size (210mm x 300mm), A3 size (297mm x 420 mm)			
	Cutting Capacity: A4: 12.6" Cutting Width; A3: 17" Cutting			
	Width			
	Heavy duty with all steel body			
	Rubber feet for non-slip desktop use			
2.	Paper Shredder	unit	2	
	Cross-Cut shredder			
	Feed Type: Traditional	1		
	Auto Start/Stop: Yes - Electronic -			
	Basket Type: Pull-out Bin			
	Bin Full Light: Yes			
	Can Shred: Staples, Credit Cards, Paper Clips, CDs/DVDs			
	Cut Size (inches): 5/32" x 1-1/2" .			
	Cut Type: Cross-Cut			
	DIN Level - Paper: P-4			
	Maximum Run Time (minutes): 20 min on / 30 min off			
	Energy Efficient Features: Energy Savings System	1		
	Material Type: Plastic			
	Paper Entry Width (inches): 9			
	Speed (Feet Per Minute): 10			
	Usage: Personal	j		
•	Strength: SOHO	l		
	Bin Capacity (gallons): 6			
	Run Time (minutes): Up to 20			
	Sheet Capacity: 16			
	Shreds Per Sheet: 397			Within
3.	Audio Recorder	Unit	17	Thirty (30) Calendar
	Digital Voice Recorder; 4GB with Radio;	Oint	11	Days Upon
	Record in MP3/LPCM; Built-in Storage			Issuance of Notice
	expandable Micro SD; Direct USB built-in for easy			to Proceed
i	connection to PC Built-in Lithium			Within
				WILLILL
	batteries with 3-minute quick charge			
4.	Portable Speaker with Wireless Mic	Unit	2	
	12" speaker with USB			
	Portable Speaker, 500 watts, Rechargeable			
	with 2 wireless microphones			
5.	Voice Recorder	Unit	5	
	Type: digital voice recorder; Interface: mini USB 2.0	0,44	/	
	Format: WAM, mp3; Battery: built-in 500mah		,	
	Sound quality: 32-1536kbps; Recording time: 20h			
	Microphone: omnidirectional microphone	i		
6.	Drone Camera			
0.		Unit	1	
	Flight Ceiling 3.7 Miles / 6000 m			
	Max Ascent Speed 22.4 mph / 10 m/s	-		
	Max Horizontal Speed 47.0 mph / 21 m/s	i		
ŀ	Max Descent Speed 22.4 mph / 10 m/s			
	Max Flight Time 46 mins /	İ		
	Remote/Trigger .			
	Max Operating Distance 12.4 Miles / 20 km			
	Camera/Video Camera	Į		
İ	Display 5.5" / LCD			
	Megapixel & Sensor Effective: 48 Megapixel			
	Lens			
	,		ļ	
j	Focal Length 24 to 70mm (35mm Equivalent)		ļ	
	Aperture Max f/2.8, Min f/1.7			
	Wide-Angle Camera FOV: 82°			
	HC1V - X7 ^o .			

-	· · · · · · · · · · · · · · · · · · ·				
	Format Equivalent: 24 mm				
	Aperture: f/1.7	1			
1	Focus: 1 m to 90				
	Video Terrories				
	Video Transmission			i	
	Video Transmission System				
	94				
	Live View Quality				
7.	DSLR CAMERA	TT			
/-		Unit	1		
	Type: Single lens reflex digital camera -		/		
	lens mount: F Bayonet Mount				
	Effective pixels: 24.2 megapixels				
	Sensor Size: 32.5 mm x 15.6 mm -				
	Image Sensor Format: DX				
	Image Sensor Type: CMOS				
		! !			
	ISO Sensitivity: ISO 100 - 25, 600	i I			
	Card Slot: 1 Secure digital (SD)	!			
	Monitor Size: 3.0 inches' diagonal				
	Battery: EN-EL14a Rechargeable Li-ion Battery				
	AC Adapter: EH-5c AC Adapter, requires EP-5A Power				
i	Connector, Battery Charger: MH-24 Quick Charger	.			
8.	Action camera	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
0.		Unit	1		
	Sensor Resolution: 23 MP	[1		
	Audio Format; AAC, WAV				
	IP Streaming: RTMP, RTMPS 1920X1080	İ			
	Shutter Speed: 1/2000 to 1/30 second in photo mode				
	ISO Sensitivity: Photo/Video 100 to 6400				
	Image Stabilization: Digital				
	Wireless connection: Wi-Fi, Bluetooth				
	input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and				
	Video Output				
	Battery type, capacity, charge time: Rechargeable				
	battery pack, 1720 mAh, 3 hours				
	Charging method: USB				
9.					
9.	Global Positioning Satellite	Unit	1		
	Dimension: 9.19x18.3x3.27cm;				
	Weight: 410g; Water rating: IPX7;	1	/		
	MIL-STD-810: Thermal, water, shock;	İ			
İ	Touchscreen; Display Resolution: 480x800 pixels;				
	Rechargeable Lithium-ion Battery;				
	16CB momory and migraCD and alat for a dditional atoms				,
	16GB memory and microSD card slot for additional storage;				
	Able to add maps; Preloaded basemaps;				
	Map Segment 15000+;				
	Satellite Imagery: Direct to Device;		i		
	Hydrographic views;		l		
	Navigation routes: 100 courses;				
	Automatic Routing;				i
	History: up to 200hrs;				!
1	Connectivity: Bluetooth, Ant+, WI-FI;				
	High-Sensitivity Receiver;	1			1
	GPS; Glonass; Galileo;				
	Barometric Altimeter; Tilt-compensated 3-axis;	ŀ			-
	Ambient light sensor; Connect IQ;				ĺ
7.0	Livetrack; Area Calculation; Picture viewer;				
10.	Laser Meter	Unit	2		
1 1	Battery: 2 AAA		,		İ
1	IP Rating: IP 54		/		
	Laser Beam Color: Red				
i	Measuring Accuracy: Typ. +/- 1/16 - in (1.5 mm)				
	Range: Un to 165 ft 0 Managed 15-14		ļ		
	Range: Up to 165 ft. 9 Measures distance, calculates area &	İ			İ
	volume				
	Continuous measurement		-		-
	Addition/subtraction		1		

					I

I hereby certify to comply and deliver all the above requirements.

Name:	
Legal Capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of:	

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (e.g. production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "or at least equivalent." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

Technical Specifications

PROJECT NAME: PROCUREMENT OF PAPER SHREDDER AND OTHERS PROJECT NO. HCDRD-24-OE-1179

Item	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and crossreferenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
A	With minimum technical specifications:	
1.	Paper Cutter Heavy duty ream Cutter A3 A4, manual Thick Layer paper cutter Size: A4 size (210mm x 300mm), A3 size (297mm x 420 mm) Cutting Capacity: A4: 12.6" Cutting Width; A3: 17" Cutting Width Heavy duty with all steel body Rubber feet for non-slip desktop use	
2.	Paper Shredder	
	Cross-Cut shredder Feed Type: Traditional Auto Start/Stop: Yes - Electronic Basket Type: Pull-out Bin Bin Full Light: Yes Can Shred: Staples, Credit Cards, Paper Clips, CDs/DVDs Cut Size (inches): 5/32" x 1-1/2" Cut Type: Cross-Cut DIN Level - Paper: P-4 Maximum Run Time (minutes): 20 min on / 30 min off Energy Efficient Features: Energy Savings System Material Type: Plastic Paper Entry Width (inches): 9 Speed (Feet Per Minute): 10 Usage: Personal Strength: SOHO Bin Capacity (gallons): 6 Run Time (minutes): Up to 20 Sheet Capacity: 16 Shreds Per Sheet: 397	
3.	Audio Recorder Digital Voice Recorder; 4GB with Radio;	
:	Record in MP3/LPCM; Built-in Storage expandable Micro SD; Direct USB built-in for easy connection to PC Built-in Lithium batteries with 3-minute quick charge	
4.	Portable Speaker with Wireless Mic 12" speaker with USB Portable Speaker, 500 watts, Rechargeable with 2 wireless microphones	
5.	Voice Recorder	
	Type: digital voice recorder; Interface: mini USB 2.0 Format: WAM, mp3; Battery: built-in 500mah	

South Castley 3-2, 50-50-69; Recording time 2 for Mary Annual Section Countries Chairs and Mary Annual Section Castley 3-10 my 1, 2 my 6 Mary Absent Speed 24 of mph 7, 21 my 6 Max Descent Speed 24 of mph 7, 21 my 6 Max Descent Speed 24 of mph 7, 10 my 7 Max Pight Time 36 mins Remote 7, 176 pp 1, 10 my 8 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Max Operating Distance 12.4 Miles / 20 km Comman 7, 176 pp 2 Miles Angle Counter Foot Langth 24 to 70 mm (Simm Equivolent) Aparture Max (12, 8, 1 mm 1, 1 m) Aperture Max (12, 8, 1 mm 1, 1 m) Aperture Max (12, 8, 1 mm 1, 1 m) Aperture Max (12, 8, 1 m) Aperture 17 m Aperture		Court of the 20 152011 P. It is not	
Fight Ceiling 37 Miles / 5000 m Max Ascent Speed 22.4 mph / 10 m/s Max Ascent Speed 22.4 mph / 10 m/s Max Descent Speed 22.4 mph / 10 m/s Max Descent Speed 22.4 mph / 10 m/s Max Descent Speed 22.4 mph / 10 m/s Max Fight Time 46 milms Remotely Pringer Max Fight Time 46 milms Remotely Pringer Max Fight Time 46 milms Remotely Pringer Remotely Pringe		Sound quality: 32-1536kbps; Recording time: 20h	
Flight Cedling 3.7 Miles / 6000 m Max Ascen Speed 2.4 mph / 10 m/s Max Horizonals Speed 4.73 mph / 10 m/s Max Flight Time 66 mins Remotor Friegor Max Operating Ibstance 12.4 Miles / 20 km Camear Video Camear Display 3.5 / 1.CD Mayoptical & Sensor Effective: 68 Megagized Display 3.5 / 1.CD Mayoptical & Sensor Effective: 68 Megagized Feed Length 64 to 70 man (55 mm Equivalent) Aperture Max (7.2 Miles / 1.7 Wide-Angle Camear POV: 827 Formst Equivalent 24 mm Aperture: f/L7 Focus: 1 m to 10 Video Transmission Video Transmissi			
Max Ascerd Speed 22.4 mph / 10 m/s Max Descerd Speed 22.4 mph / 10 m/s Max Descerd Speed 22.4 mph / 10 m/s Max Descerd Speed 22.4 mph / 10 m/s Max Piglap Time 66 mins Remote/Trigger Max Operating Distance 12.4 Miles / 20 fcm Camera/Video Camera Display 30.7 / LCD Megaptical & Sensor Effective: 48 Megaptical Beal Length 24 to 70mm (Simm Equivalent) Aperture Max (72.8, Mm f/1.7) Wilds Angle Camera POV: 427 Somme Equivalent: 24 mm Aperture: (71.7) Focus: In to 10 Video Transmission Video Transmission System O4 Live View Quality DSLR CAMERA Type Single Iran reflex digital camera lens mount: Floyonet Mount Effective polas: 32 th megapticals Sensor Size: 32 mm v 10.5 mm Image Sensor Type: CMOS Both Sensitivity: 150 100 - 25, 600 Card Silot 15 secure digital (SD) Mouttur Size: 3.0 inchest diagonal Battery: FlowTill Lat Rechargeable Li-ion Battery AC Adapter: FF5 x AC Adapter, requires BP-5A Power Cornacter, Battery Champage MF-24 Quick Charger 8. Artion camera Sensor Secondinic: 23 MP Audio Format, AAC, WAY P Steaming: RTMR, KTAME-1220/1080 Statuter Speed: 1/2000 to 1/30 second in photo mode SIS Sensitivity: Pfonto; Video 100 to 6200 Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (2000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital Windown Company, RTMS (1000) Image Stabilitation: Digital W	0.		
Max Horizontal Speed 47.0 mph / 21 m/s Max Picplet Time 46 mins Remotor Prigger Max Operating Distance 12.4 Miles / 20 km Currany Video Cumera Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display Display St. / LCD Display			
Max Descent Speed 22.4 mph / 10 m/s Max Filght Time 6 mins Remote/Trigger Max Operating Distance 12.4 Miles / 20 km Camera/Video Camera Display 35' / 1.CD Megaphael 4 Serieor Riffective 48 Megaphael Lea Following Langth 34 to 70mm (Simm Equivalent) Westerland May (7.2 Mm 1/2.7) Wideo Analysia Camera FOV: 93' Format Equivalent: 24 mm Aperture (1/1.7) Focus: 1 no to e Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission State View Quality DISLR CAMERA Type Single Iera reflex digital camera lens mount if Bayonet Mount Effective Prois's 242 magaphesis Sensor Sizes 35.7 mm x 15.6 mm Image Sensor Type CMOS ISO Sensitivity: 150 100 - 25. 600 Card Silot 15 Sensor (1) mchair diagonal Battery: EN-ELLa Rechargeable Li-ion Battery AC Adapter: FFS: AC Adapter, requires BP-5A Power Cornactor, Battery Chranges ME 24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAY I Steasming: RTMR, RTMPS 1220X1080 Shutter Speed: 17, 200 to 1, 730 second in photo mode SIS Sensitivity: Profox Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bioterooth Wideo Output Battery: Prop. expectly, clade 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bioterooth Wideo Output Battery: Prop. expectly, clade 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bioterooth Wideo Output Battery: Prop. expectly, clade 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bioterooth Wideo Output Battery: Prop. expectly, clade 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bioterooth Wideo Output Battery: Prop. expectly, claded basemapre, May Degenent 13000+; Stabilization: 1916 Stabilization routes: 100 courses; Arbite to add maps; Prebaced base and states; Arbite to add maps; Prebaced base and states; Arbite to add maps; Prebaced base and states; Arbite to add maps Prebaced base and states; Arbite to add maps Prebaced base and states; Arbite to add map			
Max Fight Time 46 mins Remote / Trigger Max Operating Distance 12.4 Miles / 20 km Camera / Video Camera Display 5.5 / LCD Megaphoid & Sensor Effective 48 Megaphoel Lens Focal Length 24 to 70mm (35mm Equivalent) Apperture Max (72.8 Mm f/1.7 Wide-Angle Camera ROV: 22 Roman Equivalent: 24 mm Angle Camera ROV: 25 Roman Equivalent: 24 mm Focus: 1 m to a Video Transmission Video Sensor Format DX Image Sensor Format DX Image Sensor Format DX Image Sensor Format DX Image Sensor Type: CMOS Sio Sensitivity: Sio 100 - 22, 600 Card Siot T. Secure digital (Sib) Moretor Size 3.5 mm x 15.6 mm Image Sensor Format DX Image Sensor Format DX Image Sensor Type: CMOS Sio Sensitivity: PSO 100 - 22, 600 Card Siot T. Secure digital (Sib) Moretor Size 3.5 mchast diagonal Sentory: PSD-Ella & Rechargeable Li-ion Battery Ac Adapter: Ell-S AC Adapter, requires EP-SA Power Connection, Battery Charges and Video Commentar Ac Way PS Streaming RTMP, RTMPS 19200080 Shutter Spend 1, 12000 to 1,790 secured in photo mode ISO Sensitivity: Photo/ Video 100 to 6400 Image Simblikation Digital Wireless connection: W.F.E. Blactooth input Connector: 1 x USE S. C. 31/3.2 Cen 2 Charge and Video Output Battery type, capacity, charge time Rechargeable battery pack, 1720 mAA, 3 hours Charging method: USE Global Positioning Satellite Dimension: 9.193.8.83.22 Cen; Weight: 410g: Watter ming: IEV7, ML-ET-Bill: Thermal, watter, shock Touchscreen; 1936 Jap. Account Matter, Mr-IP; High-Sensitivity Protot to			
Remote/Trigger Mas Operating Distance 12.4 Miles / 20 km Camera/Video Camera Display 5.5 / I.C.D Megaphysel & Sensor Effective: 48 Megapizel Lens Focal Length 24 to 70mm (35mm Equivalent) Aperture Mas 1/2.3, Min f.1.7 Wide-Angle Camera FOV: 82* Format Equivalent: 24 mm Aperture: f/1.7 Focuse 1 m to o Video Transmission System Lens Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Video Transmission System Lens Steplay Lens reflex digital camera lens mount: It Bayonet Mount Leffective pixels: 24.2 megapivels Sensor Size 3.5 mm x 15.6 mm Image Sensor Formats DX Image Senso			
Max Operating Distance 12.4 Miles / 20 km Camera / Video Camera Display 5.5" / LCD Megaphoid & Sensor Effective: 48 Megaphoel Lons Focal Length 24 to 70mm (35mm Equivalent) Aperture Mas 1/28, Min 1/1.7 Wiles Angle Camera FOV: 32" Format Equivalent: 24 mm Aperture 1/1.7 Takes Transmission Video Transmission System Of Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital camera lens nour. If Bayonet Mount Effective pixels: 24.2 megaphoel sensor nour. If Seyonet Mount Effective pixels: 24.2 megaphoel sensor pixer (EMCS) Sensor Sines 25.5 mm x.15.6 mm Image Sensor Pormate DX Image Sensor Type: CMCS So Sensitivity: 150 100 - 25, 600 Card Silot 1 Secure digital (St)) Monthur Size: 3.0 mches' diagonal Battery: EV-BLIAR Rechargeoide Li-sion Battery AC Adapter. BF-5 AC Adapter, requires BF-5 A Power Connector, Battery Change, Mif-124 Quick Charger A Action camera Sensor Resolution CA WAY If Surcaming RIMP, RYMPS: 1900X198 Shutter Speed: 1/2001 to 1,790 secund in photo mode ISO Sensitivity: Photo Video 100 to 6400 Image Sabiblization Digital Wireless connection: Wi-Fi, Bluebooth input Connector: 1 x USBS- 3.1/3.2 Cen 2 Charge and Video Output Battery Pack. 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9,19x18-3.3.2 Ten; Weight: 4.10g Water rating: IFV7; ML-STD-810-187 Termath water, shock; Touchscreen, Display Resolution: 480-800 pixels; Rechargeable Littlumin contents; 1869 Sensitivity: Photo Video 100 course; 1860 May Segment 12000+; Stellite Imagery: Direct to Device; 1940 Groups pixel views; 1869 Sensitivity: Bluetooth, Art+ WI-FI; 1869-Sensitivity: Receiver; 1789 Clorous; Califice, 1800 Commentive; Bluetooth, Art+ WI-FI; 1869-Sensitivity: Receiver; 1789 Clorous; Califice, 1800 Receiver; 1800 Learner Meter Pixel Views; 1800 Learner Meter Pixel Views; 1800 Learner Meter Pixel Views; 1800 Learner Meter Pixel Views; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiver; 1800 Receiv			
Camera/Video Camera Display 5:7 / LCD Megapisel & Sensor Effective: 43 Megapixel Lans Focal Length 24 to 70mm (35mm Equivalent) Aperture Max (7/2.8, Mm f/1.7) Wide-Angle Camera FOV: 8;2* Format Equivalent: 24 mm. Aperture: f/1.7 Fecus: 1 m to so Video Transmission System Live Video Transmission System Video Comment ACA, WAV IP Streaming RTMP, RTMPS 1920X1080 Shutter Speed 1,1/2000 to 1/30 second in photo mode ISO Sensitivity; Photo/Video 100 to 6400 Image Salabihaniton Epital I Wireless connection: Wi-F, Bluedooth Input Connector 1x USEC - 31/A-2 Gen 2 Charge and Video Output Battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimensions 19316 SaSE - 31/A-2 Gen 2 Charge Map Segment 15009; May Streaming Streaming Photosock Industrian 19316 SaSE - 31/A-2 Gen 2 Charge Map Segment 15009; Satellite Imagery: Direct to Device; Hydrographic Video; Navigation routes: 100 courses; Automatic Routing: History up to 200ms; Connectivity: Bluetooth,Ant-Wi-Fi; High-Sensitivity: Receiver; GFS, Clinanse Calludo Live Transmission System Live Video Transmission System Live Video Transmission System Live Video Transmission System Live Video Transmissi			
Display 5.5" LCD Megaphed & Sensor Effective: 48 Megaphed Lens Focal Length 24 to 70mm (25mm Equivalent) Aperture Mas (7.28, Min f.f.1.7 Wilds-Angle Camera FOV: 82° Format Equivalent: 24 mm Aperture: f.f.1.7 Focus: Im to ce Video Transmission Video Transmission System O4 Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital camera lens mount: F Bayonet Mount Effective plock: 34.2 megapheds Sensor Size: 32.5 mm x 15.6 mm Image Sensor Format DX Image Sensor Format			
Megapixel & Sensor Effective: 48 Megapixel Lons Focal Length 24 to 70mm (20mm Equivalent) Aperture Max 1/2.8 Min f.1/7 Wide-Angle Camera FOV: 82* Format Equivalent: 24 mm Aperture: 1/1.7 Focus: 1 m to so Video Transmission Transmission Effective pixels: 24.2 megapixels Sensor Stee 32.5 mm x 15.6 mm Image Sensor Formate DX Image Sensor Formate DX Image Sensor Type: CMOS ISO Sensitivity: 180 100 - 25, 600 Card Silot 1 Seoure digital (SD) Monitor Size: 3.0 inchest diagonal Battery: EN-BLIA Rackentgraphic Li-ion Batlery AC Adapter: EIT-Sc AC Adapter, requires EIT-SA Power Connector, Buttery Chartery EMH-24 Quick Charger 4. Action camera Sensor Keolution: 23 MP Audio Format: AAC, WAV IF Streaming: RTIMP, RTIMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo: Video 100 to 64000 Image Sabilization: Digital Wireless connection: Wis-Fi, Bluetooth input Connector: 1x USPG-3x1/32. Cen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable Battery type, capacity, charge time: Rechargeable Battery type, capacity, charge time: Rechargeable Dimension: 9,19x16.3-x3.2/cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen Uspalya Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 1630 Immonry and mixting: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreener Uspalya Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 1630 Immonry and mixting: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreener Uspalya Resolution: 480x800; Novel			
Lens Focal Length 23 to 70mm (35mm Equivalent) Aperture Max 1/28, Min 1/1.7 Wide Angle Camera FOV: 82? Pormat Equivalent 24 mm Aperture: 1/1.7 Focus: I m to Video Transmission System O4 Live View Quality 7. DSLR CAMERA Type: Single Ions reflex digital camera lens mount: P Bayonet Mount Effective peaks: 24.7 may gaptivels Sensor Size: 32.5 mm x 13.6 mm Image Sensor Type: CMOS SO Sensitivity: ISO 100 - 22.6 600 Card Side: 1 Secure digital (SD) Monitor Size: 30 inches' diagonal Battary: EN-EliJak Rechargeable Li-ion Battery AC: Adapter: Eli-Ga CA dapter: requires EP-5A Power Connector, Interest Charge: Mil-24 Quick Charger Sensor Records: AAC WAY P Stream get EMB ENTINES 1590X1080 Shutter Speed: 1/2000 to 1/30 secural in photo mode ISO Sensitivity: FOO 100 to 6400 Image Schillaration: Digital Wireless connection: Wi-E, Bluebooth input Connector: 1 x USB-C 3.1/3.2 Cen 2 Charge and Video Output Balley type: capacity, charge time: Rechargeable battery pack, 1720 mAb, 3 nours Cherging method: USB. Global Positioning Satellite Dimension: 9.10x18.3c.2.2/cm Weight: 410g. Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen Display Resolution: 480x600 pixels; Rechargeable Lithium ion Battery; ISGB memory and microSD card slot for additional storage; Albie to add maps: Peloaded basemaps; Map Segment 135009; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200trs; Connectivity: Bluectoch, Ant-Wi-Pi; High-Sensitivity Receiver: GPS Global Sensitivity Receiver: GPS Global Sensitivity Receiver: GPS Globass Gallies Barometra: Altimeter; Iills-compensated 3-axis; Ambient light-sensor, Connect 100 Leave Mere			
Fecal Length 24 to 70mm (35mm Equivalent) Aperture Max 1/28, Minf 1/17 Wide-Angle Canera FOV: 82° Format Equivalent 29 mm Aperture: \$1/17 Focus 1 m to \$\infty\$ Video Transmission Type: Single lens reflex digital camera lens mount F Bayoret Mount Effective pixeles 24.2 mm x 15.6 mm Image Sensor Format DX Image Sensor Format DX Image Sensor Format DX Image Sensor Format DX Image Sensor Type: CMOS EO Sensitivity; EO 100 - 25, 600 Card Silet 1 Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-ELL4a Ecchargeable Li-ion Battery AC Adapter. EH-5s: AC Adapter, requires Bi-5A Fower Cornector, Battery Charger MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Andio Format: AAC, WAV P Streaming: RTIMF, STAPPS 1520X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo-Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bilectooth input Connector: 1 x USB-C 31./32 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAA, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19xil.83x2.27cm; Weight: 410g. Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 490x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000*; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing History: up to 200hus; Connectivity: Bhetooth, Anth., WI-FJ; High-Sensitivity Receiver: CFS, Glo			
Apecture Max (7.28, Min f/1.7 Wide-Angle Camera FOV: 82° Format Equivalent: 24 mm Aperture: f/1.7 Forus: In to 50 Video Transmission Video Transmission System O4 Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital camera lens mount: F Bayonet Mount Effective pixels: 242 may 15.6 mm Image Sensor Type: CMOS Sensor Fize: 32.5 mm x 15.6 mm Image Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Action Type: CMOS Action Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Single Sensor Type: CMOS Action Camera Sensor Resolution: 23 MP Action Camera Sensor Resolution: 23 MP Audio: Format: AAC, Adapter: requires EIF-3A Power Connector, Bettray Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio: Format: AAC, WAV III Streaming: RTMP: RTMPS: 1900X1089 Sinter Speed: 1/2000 to 1/30 secretain in photo mode ISO Sensievity: Photo/Video 100 to 6400 Image Stabilization: Digital Content of the Minipal Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Curput Bettry type: capacity, charge time: Rechargeable battery pack, J720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 91,048.3-5.2/cm; Weight: 410g; Water rating: IPX7; MILSTD-310: Thermal, water, shock; Touchecureer, Display Resolution: 480x000 pixels; Rechargeable Lithium-ion Battery; 16GB memory and mixeroSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000S; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing: History: up to 200ths; Connectivity: Bluetooth;Anrit-,WI-FI; High-Sensitivity Receiver: GPS; Globass; Gallico; Connect IQ Livetnick; Ambient light sensor; Connective; Ille Livetnick; Ambient light sensor; Connective; Ille Livetnick;		i	
Wide-Angle Camera FOV: 82* Format Equivalent: 24 mm Aperture: \$\frac{1}{17}\$ Focus: In to \$\infty\$ Video Transmission Infract Sensor Format Exc Insuration Infract Sensor Format Exc Insuration Infract Sensor Format Exc Insuration Infract Sensor Format Exc Insuration Infract Sensor Format Part Video Transmission Infract Part Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmission Infract Part Video Transmis			
FOV: 82* Format Equivalent: 24 mm Apertune: 4/1.7 Forus: Im to 20 Video Transmission Video Transmissio			
Format Equivalent: 24 mm Aperture: (f.1.7) Focus: 1 m to av Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Video Transmission Type: Single lens reflex digital camera lens mount: F Bayonet Mount Effective pixels: 24.2 megaphoels Sensor Size 32.5 mm x 15.5 mm Image Sensor Type: CMOS ISO Sensitivity: 100 100 - 25, 600 Card Sloe 1 Secure digital (SD) Monitur Size 3.0 inches' diagonal Battary: EN-ELIAR Rechurgeable Li-ion Battery AC Adapter: EHS-6 AC Adapter, requires EH-5A Power Connector, Battery Charger: MH-24 Quick Charger Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IF Stransming: RTMP, RTMPS 1920X1080 Schutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1x USB-C 3.1/3.2 Cen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19413.8 3.2 2 cm; Weight: 410g: Water rating: IPX/ ML-STD-810: Thermal, water, shock; Touchscreen: Display Resolution: 480x800 pixels: Rechargeable Lithium-ton Battery; 16GB memory and mixerSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000-1 Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Reuting; History: up to 200hrs; Connectivity: Bluebooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Gallice; Connectivity: Bluebooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Gallice; Connectivity: Bluebooth, Ant+, WI-Fi; High-Sensitivity Receiver; CPS; Glonass; Gallice; Connectivity: Bluebooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Gallice; Connect (Q) Livetrack; Area Calculation; Picture viewer;			
Aperture: f/L/7 Focus: I m to o Video Transmission Video Output Video Outpu			
Focus: 1 m to o Video Transmission Video Transmission System Od Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital Camera lens mount if Bayonet Mount Effective pixels: 24.2 megapixels Sensor Size: 32.5 mm x 15.6 mm Image Sensor Type: CMOS ESO Sensibitivi; ISO 100 - 25.600 Card Slot: 1 Secure digital (SD) Monitor Size: 30 inches' diagonal Battery: EN-BILMA Rechargeable Lision Battery AC Adapter: EH-Sc AC Adapter, requires EH-SA Power Connector, Battery Charger; MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV Ir Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ESO Sensivity: Photoly/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1/20 mAh. 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18.336.3/2 cm; Weight: 410g: Water rating: ITX/; ML-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200trs; Connectivity: Bluebooth, Antt-WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Galliee; Berometric Altmeter; Tife-compensated 3-axis; Amibemt light sensor; Connect (Q) Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Video Transmission System OA Live View Quality 7. DSLR CAMERA Type Single Ions reflex digital camera lens mount F Bayonet Mount Effective pixels: 242 megapixels Sensor Size 325 mm x 156 mm Image Sensor Format DX Image Sensor Format DX Image Sensor Format DX Image Sensor Iype CMOS ESO Sensitivity: ISO 100 - 25, 600 Card Slet T Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-ELLAR Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EF-5A Power Connector, Battery Charger: Mft-24 Quick Charger Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Limage Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Cen 2 Charge and Video Output Battery type, capacity, charge time. Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.13-018, 3-3.2 Cen; Weight: 410g: Water rating: IPX7; MIL-STD-80: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lifthium-ion Battery; I6GB memory and microSD card slot for additional storage; Able to add maps; Perleaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluebooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; (Clonass; Gallice) Connectivity: Bluebooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; (Clonass; Gallice) Livertack; Area Calculation; Picture viewer; 10. Laser Meter			
Video Transmission System O4 Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital camera lens mount F Bayonet Mount Effective pixels: 242 pmegapixels Sensor Size: 325 mm x 156 mm lmage Sensor Type: CMOS IND Sensitivity: 150 100 - 25, 600 Card Slot: 1 Secure digital (SD) Monitor Size: 30 inchesé diagonal Battery: IN-B-Lida Rechargeable Li-ion Battery AC Adapter: EFF-5a CA Adapter, requires EF-5a Power Connector, Battery Charger; MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format: AAC, WAV IF Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photoly Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1/20 mAh, 3 hours Charging method: USB Global Positioning Satallite Dimension: 9.19518 533.27cm; Weight: 410g: Water rating: IPX/; ML-5T-510: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium ion Battery; 16CB memory and microSD eard slot for additional storage; Able to add maps; Freloaded basemaps; Map Segment 15000+; Satellite Inagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing: History: up to 200trs; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Ant-t, WI-FI; High-Sensitivity Receiver; GFS; Glonass; Gallice; Connectivity: Buetooth, Anti-wiewer; 10. Laser Meter			
O4 Live View Quality 7. DSLR CAMBRA Type: Single lons reflex digital camera lens mount: F Bayonet Mount Effective pixels: 24.2 megapixels Sensor Size: 32.5 mm x 15.6 mm linage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Type: CMOS ISO Sensitivity: ISO 100 - 25, 600 Card Slot: 1 Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-ELLak Bechargeable Li-ion Battery AC Adapter: EH-5x: AC Adapter, requires EP-5A Power Connector, Buttery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMFS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Slabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18.383.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-410: Thermal, water, shock: Touchscreen; Display Resolution: 440x80 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Perloaded basemaps; Map Segment: 15000+; Satellite Imagers: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 2000rs; Connectivity: Bluetooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Gallico; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Live View Quality 7. DSLR CAMERA Type: Single lens reflex digital camera lens mount: Flayonet Mount Effective pixels: 242 megapixels Sensor Size: 32.5 mm x 15.6 mm Image Sensor Type: CMCS ISO Sensitivity: 150 100 - 25, 600 Card Slot: 15 secure digital (SD) Monitor Size: 3.0 inches' diagonal Battiery: EN-ELLBa Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EF-5A Power Connector, Battery Charger MH-24 Quick Charger Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 31/3-2. Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.2 Zerm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps: Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing: History: up to 200brs; Connectivity: Bluetooth, Anter, WI-Fi; High-Sensitivity Receiver; GPS; Clonass; Galileo; Barometric Atlumeter; Tile-compensated 3-axis; Amblent light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Type Single lens reflex digital camera lens mount F Bayonet Mount Effective pixels: 24.2 megapixels Sensor Size 25.2 mux 15.6 mm limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Format: DX limage Sensor Book (aginal (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-ELIAR Rechargeable Li-ion Battery AC Adapter: EH-5s: AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Andio Format: AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/ Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 14. USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MfL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 440x800 pixels; Rechargeable: Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment: 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200bre; Connectivity: Bluetooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Gaillee; Barometric Alltmeter; Tilf-compensated 3-axis; Ambient light sensor; Connect tiQ: Livetrack; Area Calculation; Picture viewer;			
Type: Single lens reflex digital camera lens mount F Bayonet Mount Effective pixels: 24.2 megapixels Sensor Size: 32.5 mm x 15.6 mm Image Sensor Type: CMOS ISO Sensivity: 150 100 - 25, 600 Card Slot: 1 Secure digital (SD) Monitor Size: 30 inchest diagonal Battery: EN-EL14a Rechargeable Li-ion Battery AC Adapter: EH-5r. AC Adapter, requires EP-5A Power Connector, Battery Charger MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Phots/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fl, Bluetooth input Connector: 1x USB-C 31/3-2 Cen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 915x18.3x3.2/cm; Weight: 410g Water rating: IPX7; MIL-5TD-810: Thermal, water, shock; Touchscreen, Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 160B memory and microSD card slot for additional storage; Able to add maps: Preloaded basemaps; Map Segment 15000er; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing: History: up to 200hrs; Connectivity: Bluetooth, Antr. WI-Fl; High-Sensitivity, Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilb-compensated 3-axis; Amblent light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer;			
lens mount: F Bayonet Mount Effective pixels: 24.2 megaphyels Sensor Size 32.5 mm x 15.6 mm Image Sensor Format: DX Image Sensor Format: DX Image Sensor Format: DX Image Sensor Size (Misser Company) Image Sensor Size (Misser Company) Image Sensor Size (Misser Company) Image Sensor Size (Misser Company) Image Sensor Size (Misser Company) Image Sensor Size (Misser Company) Image Sensor Sensolution: 23 MP Action camera Sensor Resolution: 23 MP Audio Format AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18, 33.3 Zrm; Weight: 410g: Water rating: IPX7; VMIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; InGB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200ths; Connectivity: Bluetooth, Ant+, WI-Fi; High-Sensitivity Receiver; GPS; Glonass; Galilee; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect (Q: Livetnack; Area Calculation; Picture viewer; 10.1	/.		
Effective pixels: 2At 2 megapixels Sensor Sizes 2.5 mix × 15.6 mm Image Sensor Format DX Image Sensor Format DX Image Sensor Type: CMOS ISO Sensitivity: ISO 100 - 25, 600 Card Slot 1 Secure digital (SD) Monitor Size: 3.0 inchest diagonal Battery: EN-EL14a Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires FP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Andio Format: AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1/20 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g Water rating: IPX/; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ton Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing: History: up to 200ths; Connectivity: Bluetooth, Ant+, Wi-Fi; High-Sensitivity Receiver; GPS; Clonass; Galileo; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect IQ Livetrack; Area Calculation; Picture viewer:			
Sensor Size: 23.5 mm x 15.6 mm Image Sensor Type: CMOS ISO Sensitivity: ISO 10.0 - 25, 600 Card Slot 1 Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-EILJA Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger Action camera Sensor Resolution: 23 MP Andio Format, AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-FI, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Statilite Dimension: 91.918.38.33.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; Inchargeable Lithium-ion Battery; Satellite Imagery: Direct to Device; Hydrographic views; Nap Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing History: up to 200tns; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; CPS; Clonass; Galileo; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect 1Q: Livetrack; Area Calculation; Picture viewer;			
Image Sensor Type: CMOS ISO Sensitivity: ISO 100 - 25, 600 Card Slot 1 Secure digital (SD) Monitor Size: 30 inches' diagonal Battery: EN-FL14a Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EP-5A Power Connector, Battery Chargen MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/ Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9,19x18-3x3.2/cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 490x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity: Receiver; GFS; Glonass; Galileo; Barometric Altimeter; Tilf-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack, Area Calculation; Picture viewer;			
Image Sensor Type: CMOS ISO Sensitivity: ISO 100 - 25, 600 Card Slot: I Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-B-IL4R acchargeable Li-ion Battery AC Adapter: EH-Sc AC Adapter, requires EP-SA Power Connector, Battery Charger; MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/ Video 1010 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable: Lithum-ton Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity: Receiver; GPS; Glonass; Galllee; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack, Area Calculation; Picture viewer;			
ESO Sensitivity: ISO 100 - 25, 600 Card Slot 1 Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-FLL4a Rechargeable Li-ion Battery AC Adapter: EH-5s AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x13.33.2/7cm; Weight 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hus; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galilee; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack, Area Calculation; Picture viewer;			
Card Slot: 1 Secure digital (SD) Monitor Size: 3.0 inches' diagonal Battery: EN-EL14a Rechargeable Li-ion Battery AC Adapter: EH-Sc AC Adapter, requires EP-SA Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming: RTIMP, RTIMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1/20 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g Water rating: IPX/; MIL-STD-310: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS, Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Monitor Size: 3.0 inches' diagonal Battery: EN-EL14a Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming: RTIMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 u/SB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Battery: EN-EL14a Rechargeable Li-ion Battery AC Adapter: EH-5c AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 91-94.83-33.2 Cm; Weight: 410g: Water rating: IPX7; MIL-5TD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views, Navigation routes: 100 courses; Automatic Routing; History: up to 200ths; Connectivity: Bluetooth, Ant+, Wi-Fi; High-Sensitivity Receiver; GPS, Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
AC Adapter, EH-5c AC Adapter, requires EP-5A Power Connector, Battery Charger: MH-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format, AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g. Water rating: IPX7; MIIISTD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, Wi-Fi; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer;			
Connector, Battery Charger: MFI-24 Quick Charger 8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/ Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USF-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USF 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200tus; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPs; Clonoas; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer;			
8. Action camera Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1/720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 919x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter, Tilt-compensated 3-axis; Ambient light sensor; Connect IC; Livetrack; Area Calculation; Picture viewer;			
Sensor Resolution: 23 MP Audio Format; AAC, WAV IP Streaming; RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galliene; Barometric Altimeter; Till-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack, Area Calculation; Picture viewer;			
Audio Format, AAC, WAV IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;	8.		
IP Streaming: RTMP, RTMPS 1920X1080 Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Gailleo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;		**	
Shutter Speed: 1/2000 to 1/30 second in photo mode ISO Sensitivity: Photo/Video 100 to 6400 Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
ISO Sensitivity: Photo/Video 100 to 6400° Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Image Stabilization: Digital Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g: Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer;			
Wireless connection: Wi-Fi, Bluetooth input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
input Connector: 1 x USB-C 3.1/3.2 Gen 2 Charge and Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ: Livetrack; Area Calculation; Picture viewer;			
Video Output Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Battery type, capacity, charge time: Rechargeable battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
battery pack, 1720 mAh, 3 hours Charging method: USB 9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Charging method: USB Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MfL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
9. Global Positioning Satellite Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;	ļ		
Dimension: 9.19x18.3x3.27cm; Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonas; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Weight: 410g; Water rating: IPX7; MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;	9.		
MIL-STD-810: Thermal, water, shock; Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Touchscreen; Display Resolution: 480x800 pixels; Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Rechargeable Lithium-ion Battery; 16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
16GB memory and microSD card slot for additional storage; Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;			
Able to add maps; Preloaded basemaps; Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;		Rechargeable Lithium-ion Battery;	
Map Segment 15000+; Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer;		16GB memory and microSD card slot for additional storage;	
Satellite Imagery: Direct to Device; Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Hydrographic views; Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Navigation routes: 100 courses; Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter		Satellite Imagery: Direct to Device;	
Automatic Routing; History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter		Hydrographic views;	
History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter		Navigation routes: 100 courses;	
History: up to 200hrs; Connectivity: Bluetooth,Ant+,WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter		Automatic Routing;	
Connectivity: Bluetooth, Ant+, WI-FI; High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
High-Sensitivity Receiver; GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
GPS; Glonass; Galileo; Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Barometric Altimeter; Tilt-compensated 3-axis; Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Ambient light sensor; Connect IQ; Livetrack; Area Calculation; Picture viewer; 10. Laser Meter			
Livetrack; Area Calculation; Picture viewer; 10. Laser Meter		Ambient light sensor: Connect IO	
10. Laser Meter		Livetrack; Area Calculation: Picture viewer	
	10.		

	IP Rating: IP 54	<u> </u>	
	Laser Beam Color: Red		
	Measuring Accuracy: Typ. +/- 1/16 - in (1.5 mm)		
	Range: Up to 165 ft. 9 Measures distance, calculates area &		
	volume		
	Continuous measurement		
	Addition/subtraction		
В.	Compliance to the Schedule of Requirements (Section VI)		 -

I hereby certify to comply and deliver all the above requirements.

Name:	
Legal Capacity:	_
Signature:	
Duly authorized to sign the Bid for and behalf of:	

Technical Specifications Page 3 of 3

Section VIII. Checklist of Technical and Financial Documents

Notes on the Checklist of Technical and Financial Documents

The prescribed documents in the checklist are mandatory to be submitted in the Bid, but shall be subject to the following:

- a. GPPB Resolution No. 09-2020 on the efficient procurement measures during a State of Calamity or other similar issuances that shall allow the use of alternate documents in lieu of the mandated requirements; or
- b. Any subsequent GPPB issuances adjusting the documentary requirements after the effectivity of the adoption of the PBDs.

The BAC shall be checking the submitted documents of each Bidder against this checklist to ascertain if they are all present, using a non-discretionary "pass/fail" criterion pursuant to Section 30 of the 2016 revised IRR of RA No. 9184.

Checklist of Technical and Financial Documents 1. TECHNICAL COMPONENT ENVELOPE

Class "A" Documents

Lega	al Doc	<u>cuments</u>
	(a)	Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages) in accordance with Section 8.5.2 of the IRR;
<u>Teci</u>	<u>hnical</u>	<u>Documents</u>
	(b)	Statement of the prospective bidder of all its ongoing government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES); and
	(c)	Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the relevant period as provided in the Bidding Documents (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES); and
	(d)	Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission; or Original copy of Notarized Bid Securing Declaration; and
	(e)	Conformity with Section VI. (Schedule of Requirements) and Section VII. (Technical Specifications), which may include production/delivery schedule, manpower requirements, and/or after-sales/parts, if applicable; and
	(f)	Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.
Fina	ncial	Documents
	(g)	The prospective bidder's computation of Net Financial Contracting Capacity (NFCC) (in a FORM prescribed by the QC-BAC-GOODS AND SERVICES);
		or A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation.
		Class "B" Documents
	(h)	If applicable, a duly signed joint venture agreement (JVA) in case the joint venture is already in existence;
		or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.
Othe.	r doci	mentary requirements under RA No. 9184 (as applicable)
	(i)	[For foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government office of their country stating that Filipinos are allowed to participate in government procurement activities for the same item or product.
	(j)	Certification from the DTI if the Bidder claims preference as a Domestic Bidder or Domestic Entity.

II. FINANCIAL COMPONENT ENVELOPE

(a)	Original of duly signed and accomplished Financial Bid Form; and
	Original of duly signed and accomplished Price Schedule(s)

III.REQUIRED DOCUMENTS in BDS SECTION 20.2 and 21.2

 Statement of warranty- minimum of One (1) year with Project Name and Project Number./

Note:

1. Please refer to

[https://drive.google.com/file/d/1uiYurh5WrpBL5B_pqpzAb62yucAblR1p/view?usp=sh_aring] for the following requirements:

- a. Computation of NFCC;
- b. List of All Ongoing Contracts/List of Contracts already awarded but not yet started;
- c. Statement of Single Largest Completed Contract
- 2. Please refer to GPPB Resolution No. 16-2020 for the following requirements:
 - a. Bid Form;
 - b. Price Schedule (for Goods Offered from Abroad/ Within the Philippines)
 - c. Bid Securing Declaration; and
 - d. Omnibus Sworn Statement

ten xi

