



Republika ng Pilipinas  
Lungsod Quezon

**BIDS AND AWARDS COMMITTEE – GOODS & SERVICES**  
Second Floor, Civic Center Building F, Quezon City Hall Complex, Elliptical Road, Quezon City  
8988-4242 local 8712 / 8710 / 8709  
[bacgoods.procurement@quezoncity.gov.ph](mailto:bacgoods.procurement@quezoncity.gov.ph)



**REQUEST FOR QUOTATION  
NEGOTIATED PROCUREMENT  
SECTION 35.1**

DATE : OCTOBER 02, 2025

PROJECT NO. : PAISD-25-AVE-0581B

Name of Company : \_\_\_\_\_  
Address : \_\_\_\_\_  
Contact No. : \_\_\_\_\_  
Project Title : PROCUREMENT OF ROBOTIC PAN AND TILT HEAD AND OTHERS  
Approved Budget of the Contract : Php 1,319,990.00  
End-User / Implementing Office : PUBLIC AFFAIRS AND INFORMATION SERVICE DEPARTMENT

| BREAKDOWN OF APPROVED BUDGET FOR THE CONTRACT |                     |
|---|---------------------|
| Item Nos. 1-3                                 | 385,970.00          |
| Item Nos. 4-5                                 | 130,000.00          |
| Item Nos. 6-10                                | 564,820.00          |
| Item Nos. 11-13                               | 239,200.00          |
| <b>TOTAL</b>                                  | <b>1,319,990.00</b> |

Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided. Submit your quotation duly signed by you or your duly authorized representative not later than **OCTOBER 07, 2025 10:00 AM** Philippine Standard Time, together with the following documents of your company:

- 1 PhilGEPS certificate (not expired on the time of opening of quotations);
- 2 Business Registration (DTI/SEC)
- 3 Mayor's/Business Permit (2025);
- 4 Tax Clearance; and
- 5 Omnibus Sworn Statement prescribed by the **QC BAC- Goods and Services**
- 6 Income/Business Tax Return (for FY 2024) (For ABCs above P500,000.00)
- 7 If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.

in a **SEALED LONG BROWN ENVELOPE** issued by QC BAC- Goods and Services.

**NOTE: Submission of a Document Request List (DRL) is required prior to the issuance of the Long Brown Envelope.**

**MA. MARGARITA S. MEJIA, DPA**  
Chairperson, BAC Goods and Services



Management System  
ISO 9001:2015  
www.tuv.com  
ID 300003413



**TERMS AND CONDITIONS**

1. Bidders shall **provide correct and accurate** information required in this form.
2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission.
3. Price quotation/s, to be denominated in Philippine Peso shall include all taxes, duties and/or levies payable.
4. Quotation **exceeding** the Approved Budget for the Contract (ABC) shall be **rejected**.
5. Award of contract shall be made to the lowest quotation (for goods) or the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
7. The City General Services Department (CGSD) shall have the right to inspect the goods.
8. Non-submission of eligibility documents shall mean disqualification of Quotation.
9. Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CGSD shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
10. Failure to follow these instructions will disqualify your entire quotation.

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s as follows:

| ITEM NO. | ITEM & DESCRIPTION   | UNIT OF ISSUE | QTY. | UNIT PRICE | ITEM TOTAL |
|----------|--|---------------|------|------------|------------|
| 1        | <b>SDI/HDMI Wireless Video Transmitter/ receiver</b><br>- Wireless Video Transmitter/Receiver Set<br>- Transmitter HDMI/SDI Input, SDI Loop Out<br>- Receiver HDMI & 2 x SDI Outputs<br>- OLED Screen, USB Type-C Power Input<br>- 1000' Line-of-Sight 1080p60 Transmission<br>- 5.1 to 5.9 GHz Frequency Range<br>- AES-128 Encryption, 40 ms Latency<br>- L-Series Battery Plates on TX/RX<br>- DC Adapter Power or Optional Battery   | piece         | 2    |            |            |
| 2        | <b>Multi D-Tap Heavy-Duty Digital Battery 14.4V 220Wh (V-Mount)</b><br>Key Features<br>- Square-Shaped Design for Cine Cameras<br>- Up to 150W/12A Continuous Output<br>- Powers ARRI ALEXA for Approx. 2.5 Hours<br>- Powers ENG Cameras for Approx. 7 Hours - Four D-Tap Outputs<br>- USB Port<br>- Intelligent LCD<br>- Communicates Runtime Info to RED & Sony<br>- Supports 6A Fast Charging<br>- Circuit Protection<br><b>Specifications:</b><br>Mount / Series Type: V-Mount<br>Chemistry: Lithium-Ion<br>Battery Capacity: 15,300 mAh / 220 Wh<br>Output Voltage: 14.4 VDC<br>Maximum Load: 150 W, 12 A Accessory I/O: 4x D-Tap / P-Tap<br>Maximum Load (Accessory I/O): 120 W, 10 A (D-Tap)<br>USB Output: 5 V, 2 A | piece         | 2    |            |            |
| 3        | <b>PTZ Multicam Combo</b><br>3 * Pan/Tilt/Zoom Camera Pack<br>1 * Smart Remote Controller<br>3 * NDI License Key<br>3 * USB-C to Ethernet Adapter<br>3 * Micro HDMI to HDMI Cable<br>AI chip<br>Integrated AI chip, Trillions of calculations per second<br>Camera<br>Image sensor: 1/1.8-inch CMOS<br>Macro pixel size: 2.0µm*2.0µm   | lot           | 1    |            |            |



Management System  
ISO 9001:2015  
www.tuv.com  
ID: 900003413



|   |   |       |   |  |  |
|---|---|-------|---|--|--|
|   | <p>Effective pixels: 8.4 million<br/> Effective pixel resolution: 3856x2176<br/> Lens system: 8 Optical Lenses<br/> Zoom range: 4X digital zoom<br/> FOV (D): 85°<br/> FOV (H): 77.3°<br/> ISO range: 100-6400<br/> Exposure value: ±3EV<br/> Electronic shutter speed: 1/8000 s to the limit of frames per second<br/> Focus: Auto Focus/Manual Focus<br/> Aperture: f/1.8<br/> Equivalent focal length: 23mm<br/> White balance: 2000K-10000K<br/> Gyroscope: 6-axis Gyroscope</p> <p>Shooting<br/> Photo resolution: 4K, 1080P<br/> Video resolution: 4K@30/29.97/25/24 fps<br/> 1080@/60/59.94/50/48/30/29.97/25/24 fps<br/> 720@/60/59.94/50/48/30/29.97/25/24 fps<br/> Max video storage bit rate: H264: 100Mbps, H265: 80Mbps<br/> Video format: MJPEG, H264, H265</p> <p>2-axis gimbal<br/> Gimbal installation: Non-removable<br/> Controllable range: Pan: ±150°; Tilt: -65°~32°<br/> Mechanical range: Pan: ±160°; Tilt: ±90°<br/> Max controllable speed: 120°/s<br/> Angle jitter: ±0.02°</p> <p>Audio<br/> Audio input: Built-in Two MEMS Microphones<br/> Built-in 3.5mm TRS Connector (AUX)<br/> Support MIC IN/LINE IN<br/> Audio modes: Noise Reduction/Stereo Sound<br/> Audio format: AAC/PCM</p> <p>Wi-Fi<br/> Operating frequency: 2.4 G/5.8 GHz<br/> Signal transmission range: 2.4G 140m, 5.8G 80m<br/> Transmission power: 2.4 GHz: &lt;18 dBm (FCC/CE/SRRC/MIC)<br/> 5.1 GHz: &lt;15 dBm (FCC/CE/SRRC/MIC)<br/> 5.8 GHz: &lt;15 dBm (FCC/CE/SRRC)</p> |       |   |  |  |
| 4 | <p><b>Monitor Controller and Interface</b></p> <ul style="list-style-type: none"> <li>- 4x Sources and 3x Monitor Pairs</li> <li>- Classic Big Knob Volume Control</li> <li>- Independent Trim on All Sources</li> <li>- Mono, Mute, and Dim Functions</li> <li>- 2x4 USB Recording Interface</li> <li>- 24-Bit/192 kHz Recording and Playback</li> <li>- Compatible with Windows &amp; Mac Computers</li> <li>- Sturdy Design</li> <li>- Includes Tracktion Recording Software</li> <li>- Resolution 24-bit/192 kHz</li> </ul>   | piece | 2 |  |  |
| 5 | <p><b>Audio Mixer Tour Case with Folding Table</b></p> <ul style="list-style-type: none"> <li>- Compatible with PreSonus StudioLive 32SC</li> <li>- Made from 7 mm plywood</li> <li>- Coated in brown phenolic resin</li> <li>- Aluminium edges: 30 x 30 mm</li> <li>- 4 x Butterfly latches, medium</li> <li>- 4 x Folding handles, medium</li> <li>- 4 x Rounded ball corners, medium</li> <li>- 4 x Rounded ball corners, medium L-corner</li> <li>- 2 x Skid strips</li> </ul>  | piece | 1 |  |  |



Management System  
ISO 9001:2015  
www.tuv.com  
ID: 900029412



|   |   |     |   |  |  |
|---|---|-----|---|--|--|
|   | <ul style="list-style-type: none"> <li>- Foam padding inside</li> <li>- Includes a cable duct</li> <li>- External dimensions (W x D x H): 510 x 760 x 287 mm</li> </ul>   |     |   |  |  |
| 6 | <p><b>Carbon Fiber Tripod &amp; Fluid Head System</b></p> <p>Key Features</p> <ul style="list-style-type: none"> <li>- 2-Stage Carbon Fiber Tripod, 75mm Bowl</li> <li>- 15.4 lb Payload</li> <li>- 25.8 to 68.7 inches Operating Height</li> <li>- 4 Steps of Counterbalance</li> <li>- 4 Grades of Pan and Tilt Drag</li> <li>- Independent Pan and Tilt Locks</li> <li>- Pan Bar and Ground Spreader Included</li> <li>- Flip Lock Leg Levers</li> </ul> <p>Specifications:</p> <p>Camera Plate</p> <p>Camera Mounting Screw: 1 x 1/4 inch-20 Male with Locating Pin, 1 x 3/8 inch-16 Male</p> <p>Head</p> <p>Base Mount: 75 mm Half Ball</p> <p>Counter Balance: Incremental 4-Step</p> <p>Pan Handle Fittings: 2 x Rosette</p> <p>Pan &amp; Tilt</p> <p>Drag Control</p> <p>Pan: 4-Step</p> <p>Tilt: 4-Step</p> <p>Drag Type: Fluid</p> <p>Vertical Tilt: 90° to -68°</p> <p>Legs</p> <p>Leg Lock Type: Flip Lock</p> <p>Leg Sections: 3</p> <p>Spreader: Ground (Included)</p> <p>General</p> <p>Load Capacity: 15.43 lb / 7 kg</p> <p>Maximum Working Height: 68.70 inches / 174.5 cm</p> <p>Minimum Working Height: 25.79 inches / 65.5 cm</p> <p>Materials: Carbon Fiber</p> | set | 1 |  |  |
| 7 | <p><b>Carbon Fiber Tripod System with Ace XL Head &amp; Ground Spreader</b></p> <p>Key Features</p> <ul style="list-style-type: none"> <li>- Ace XL Fluid Head</li> <li>- Two-Stage Carbon Fiber Tripod</li> <li>- 17.6 lb Load Capacity</li> <li>- 9-Step + 0 Counterbalance</li> <li>- 3-Step + 0 Pan/Tilt Drag</li> <li>- Ground Spreader</li> </ul> <p>Key Specs:</p> <p>Camera Mounting: 1/4 inch-20 Screw (Quick Release with Sliding Balance Plate)</p> <p>Head Type: Fluid Head</p> <p>Drag Control: Yes</p> <p>Load Capacity: 17.6 lb / 8 kg</p> <p>Head</p> <p>Camera Mounting: 1/4 inch-20 Screw (Quick Release with Sliding Balance Plate)</p> <p>Head Type: Fluid Head</p> <p>Base Mount: Flat Base with 3/8 inch-16 Female (75 mm Half Ball via Included Adapter)</p>   | set | 1 |  |  |



Management System  
ISO 9001:2015



www.tuv.com  
ID: 900025413

|   |  |     |   |  |  |
|---|--|-----|---|--|--|
|   | <p>Counter Balance: Incremental 9-Step Plus 0<br/> Dimensions: Camera Plate: 5.5 x 2inches / 140.00 x 50.00 mm<br/> Pan &amp; Tilt<br/> Drag Control: Yes<br/> Vertical Tilt: +90° to -75°<br/> General<br/> Load Capacity: 17.6 lb / 8 kg<br/> Bubble Level: Yes (Illuminated)</p> <p>Bluetooth<br/> Bluetooth protocol: BLE 5.0<br/> Bluetooth operation frequency range: 2.400 GHz to 2.4835 GHz<br/> USB<br/> USB: 2.0</p> <p>Charger &amp; Battery<br/> Input: 5V/2A<br/> Charging time: 90 Minutes (Power off status)<br/> Operating time: 154 minutes<br/> Battery type: Lithium Polymer(Li-po)<br/> Battery capacity: 1500mAh<br/> Battery energy: 11.4Wh<br/> Battery voltage: 7.6V</p> <p>Auxiliary<br/> Functions: Gesture Control<br/> Memory card type: Micro SD Card (up to 512GB) -exFAT (Recommended)/FAT32; U3 card (minimum write speed 30MB/S) recommended.</p> <p>Operating environment<br/> Camera working environment temperature: -10°C-40°C<br/> Battery charging ambient temperature: -10°C-40°C<br/> Battery operating ambient temperature: - 10°C-40°C<br/> Charging will stop when the battery temperature exceeds 45°C.</p> |     |   |  |  |
| 8 | <p><b>Robotic Pan and Tilt Head (HDBaseT)</b><br/> Key Features<br/> - Tripod, Wall, and Ceiling Mountable<br/> - Pans and Tilts PTZ Your Camera Remotely<br/> - HDBaseT Video Output and Control<br/> - Supports up to 8.8 lb, Tally Light 3G-SDI and HDMI Video Input/Outputs<br/> - RS-232/422 Serial Support<br/> - D-Tap Power Output, Selectable Voltage</p> <p>Video Connectors<br/> Video In:<br/> 1 x 3G-SDI<br/> 1 x HDMI</p> <p>Input/Output:<br/> 1 x RJ45 HDBaseT Video/Control Port<br/> Video Output Connectors<br/> 1 x 3G-SDI<br/> 1 x HDMI</p> <p>Serial Connector<br/> 1 x RJ45 RS-422 Output Control Port<br/> 1 x 9-Pin Sub-D RS-232 Output Control (Not in Use)</p> <p>Other I/O<br/> 1 x Remote Port, Zoom and Focus Camera Control<br/> 1 x USB, Firmware Upgrade</p>  | set | 1 |  |  |



Management System  
ISO 9001:2015  
www.tsv.com  
ID: 300003413



|    |   |     |   |  |  |
|----|---|-----|---|--|--|
|    | <p>1 x 3.5 mm Jack, Tally In<br/>1 x 3.5 mm Jack, Tally Out</p> <p>Status<br/>4 x LEDs</p> <p>Output Resolution<br/>2160p: 29.97/25<br/>1080p: 59.94/50<br/>1080i: 59.94/50<br/>720p: 59.94/50</p> <p>Pan &amp; Tilt Range<br/>Pan: 340°<br/>Tilt : ±45°</p> <p>Pan &amp; Tilt Speed<br/>Pan: 0.2 to 15° Seconds Tilt: 0.1 to 10° Seconds</p> <p>Control Protocol<br/>Sony VISCA and DVIP</p> <p>Remote Control Distance<br/>RS-422: 3937' / 1200 m<br/>DVIP: 328' / 100 m</p> <p>Maximum Load Capacity<br/>8.8 lb / 4 kg</p> <p>Power Requirements<br/>Without Camera: 12 to 18 VDC, 3 A with Camera: 12 to 18 VDC, 5 A</p> <p>Power Output<br/>12, 10, 8.4, 7.4 VDC, 24 W Maximum (Selectable)</p> <p>Power Input<br/>1 x DC Screw Barrel Jack, 12 VDC Power Input<br/>1 x D-Tap Power Output<br/>RJ45 Power-over-Ethernet</p> <p>Material of Construction<br/>Aluminum</p> |     |   |  |  |
| 9  | <p><b>Dual Square Compact Battery &amp; Charger Kit</b><br/>Description<br/>For Select Smaller Cameras<br/>148Wh Li-Ion Battery<br/>5V, 2A USB Output Dual D-Tap Ports V-Mount Interface<br/>4-Level LED Power Indicator<br/>Rechargeable; No Memory Effect<br/>Protective Rubber Cap<br/>Working Temperature -4 to 131°F</p>   | set | 1 |  |  |
| 10 | <p><b>Portable Solar Panel</b><br/>General<br/>Dimensions (unfolded) (cm): 82.0 x 183.5 x 2.5<br/>Dimension (Unfolded) (inch): 32.3 x 72.2 x 1.0<br/>Dimension (folded) (inch): 32.3 x 19.7 x 1.3<br/>Dimensions (folded) (cm): 82.0 x 50.0 x 3.2<br/>Rated Power<br/>220W (±5W)* front, 155W (±5W)* rear</p>   | set | 1 |  |  |
| 11 | <p><b>Portable Power Station</b><br/>Description<br/>Specifications<br/>Capacity: 3600Wh<br/>Extra Battery: Support up to two DELTA Pro Smart Extra Battery/Smart<br/>Generator<br/>AC Output: 5 outlets, 3600W total (Surge 7200W)<br/>Max Device(s) Power Supported by X-Boost: 4500W<br/>USB-A Output: 2 ports, 5V, 2.4A, 12W Max per port<br/>USB-A Fast Charge: 2 ports, 5V, 2.4A / 9V, 2A / 12V, 1.5A, 18W Max per port</p>   | set | 1 |  |  |



|              |   |     |   |  |  |
|--------------|---|-----|---|--|--|
|              | USB-C Output: 2 ports, 5/9/12/15/20V, 5A, 100W Max per port<br>Car Power Output: 12.6V, 10A, 126W Max<br>DC5521 Output: 2 ports, 12.6V, 3A, 38W Max per port<br>Anderson Port: 12.6V, 30A<br>AC Charging Input: 1800W Max, 120V~15A, 3000W Max, 240V~12.5A<br>Solar Charging Input: 1600W Max, 11-150V, 15A Max<br>Car Charging Input: Support 12V/24V battery, 8A<br>Battery Chemistry: LFP<br>Cycle Life: 6,500 cycles to 50% capacity, 3,500 cycles to 80% capacity<br>Connection: Wi-Fi, Bluetooth<br>Dimension: 25x11.2x16.4 inches/63.5x28.4x42cm |     |   |  |  |
| 12           | <b>PORTABLE SOLAR GENERATOR</b><br>Description<br>Portable Solar Generator 42000mah 155WH Lithium ION Battery upto 100w Capacity<br>AC, USB and 12V DC OUTPUTS: includes 220V AC outlet (100W Cont output), 3 - 12V DC ports max 180W, with an extra cigarette socket cable), 3 - 5V USB ports<br>3 CHARGING MODES: solar panel (SOLD SEPARATELY), wall outlet, car 12V socket (Car charger included)<br>Rechargeable Battery<br>155WH 42000mAh lithium ion batteries<br>Dimensions: 7.67x6.73x3.54 inch  | set | 1 |  |  |
| 13           | <b>IMPACT DRILL TOOL SET</b><br>Specifications:<br>650 Watts<br>13mm / 1/2inch<br>100pcs Accessories and with Hand Tools Heavy Duty 1year parts and Service Warranty  | set | 1 |  |  |
| <b>TOTAL</b> |   |     |   |  |  |

**Amount in Words:**

---



---

|  |
|--|
| <b>OTHER REQUIREMENT/S:</b> <ul style="list-style-type: none"> <li>Statement of Warranty with project number and project title - minimum of one (1) year.</li> </ul> |
|--|

Delivery Period : **Thirty (30) Calendar Days**

Warranty : \_\_\_\_\_

\_\_\_\_\_  
Signature over printed name

\_\_\_\_\_  
Office Telephone No./Fax/Mobile No.

\_\_\_\_\_  
Date

\_\_\_\_\_  
Email Address



Management System  
ISO 9001:2015  
www.tuv.com  
ID: 900023413

